



Hikvision Demo DVR

<p>DVR Model: DS-7716NI-SP/16 Description: 16 Channel Embedded Plug&Play NVR</p> <p>H.264, 5MP resolution, 100Mbps Bit Rate Input Max, HDMI output: 1920x1080, VGA output: 1920x1080, 3 simultaneously output (HDMI, VGA, BNC), 16ch 4CIF sync playback, Plug & Play with 16 independent PoE network interfaces, Audio In: 16ch, Alarm Out: 4, Alarm In: 16 Alarm Out: 4, Dual Gigabit network interfaces</p>			 <p>DVR Model: DS-7716NI-SP/16 Demo IP Address: 173.200.91.72 Username: Hikvision Password: guest Port: 8000</p>
IP Channel	Camera Model	Description	Notes:
D1	DS-2CD2512-I	1.3MP Mini Dome Network Camera	
D2	DS-2CD2332-I	3.0MP EXIR Turret Network Camera	
D3	DS-2CD2012-I	1.3MP IR Mini Bullet Network Camera	
D4	DS-2CD4012FWD-A	1.3MP WDR Box Camera	
D5	DS-2CD2232-I5	3.0MP EXIR Bullet Network Camera	
D6	DS-2CD4224F-IZS	2.0MP Full HD IR Bullet Network Camera	
D7	DS-2DF7276-A	1.3MP 30X IP IR PTZ Dome Camera	
D8	DS-2CD2232-I5	3.0MP EXIR Bullet Network Camera	

Note: The guest account does have limitations. All features regarding configuration may not be available.

<p>DVR Model: DS-7316HQHI-SH Description: 16 Channel Turbo HD DVR</p> <p>H.264, Full Channel @ 1080P Resolution, 80Mbps Bit Rate Input Max, HDMI output: 1920x1080, VGA output: 1920x1080, 3 simultaneously output (HDMI, VGA, BNC), 16ch 4CIF sync playback, up to 16ch IP Video, Audio In: 4ch, Audio Out: 2, Alarm In: 16 Alarm Out: 4, Dual Gigabit network interfaces</p>			 <p>DVR Model: DS-7316HQHI-SH Demo IP Address: 173.200.91.71 Username: Hikvision Password: guest Port: 8000</p>
Analog Channel	Camera Model	Description	Notes:
A1	DS-2CE15C2N-VFIR3	960H Analog Vari-focal IR Bullet Camera	<ol style="list-style-type: none"> Analog Channels 8-16 have been disabled IP Cameras D1 and D2 have been added Compare A1 against A2 (Standard Analog vs. HDTVI) Compare A3 against A4 (Standard Analog vs. HDTVI) Compare A5 against D1 (Turbo HD vs. IP Camera) Compare A6 against D2 (Turbo HD vs. IP Camera) You have remote VOD playback rights on DVR
A2	DS-2CE16D5T-AVFIT3	1080P Outdoor EXIR Bullet Camera	
A3	DS-2CC5173N-VF	960H Analog Indoor Dome Camera	
A4	DS-2CE56C5T-VFIR	HD720P Indoor IR Camera	
A5	DS-2CE56C5T-VFIT3	HD720P Outdoor EXIR Turret Camera	
A6	DS-2CE56C5T-VFIR	HD720P Indoor IR Camera	
A7	DS-2CE55C2N-VFIR	960H Analog IR Camera	
IP Channel	Camera Model	Description	
D1	DS-2CD4124F-IZ	2.0MP Full HD Indoor Dome Camera	
D2	DS-2CD4312F-IZS	1.3 MP Low-light Outdoor Dome Camera	



DVR Model: DS-9016HWI-ST

Demo IP Address: 173.200.91.70

Username: Hikvision

Password: guest

Port: 8000

DVR Model: DS-9016HWI-ST **Description:** 16 Channel Hybrid DVR

H.264, 5MP resolution, 80Mbps Bit Rate Input Max, HDMI output: 1920x1080, VGA output: 1920x1080, 3 simultaneously output (HDMI, VGA, BNC), 16ch 4CIF sync playback, up to 32ch (16 Analog + 16 IP) or 32ch IP Video, Audio In: 16ch, Alarm Out: 2, Alarm In: 16 Alarm Out: 4, Dual Gigabit network interfaces, ONVIF Compliant

Analog Channel	Camera Model	Description	Notes:
A1	DS-2CE55C2N	Indoor Dome Camera	<ol style="list-style-type: none"> Analog Channels 5-16 have been disabled Compare A4 against D4 (Standard Analog vs. IP Camera) D2 and D3 are in Rotate mode (Hallway) Line Crossing (Hallway) Video Content Analytics is enabled (Great to Demoing Smart Playback) D6 to D10 all streams come from DS-2CD6362F-I (fisheye 6.0 MP Camera) Hybrid DVR Channel Allocation: 16ch Analog + 16ch IP up to 32ch (Analog + IP) (200Mbps Bit Rate Input Max) PTZ Control is Enabled for D8-D11
	DS-2CE16C2N-IT3	EXIR Bullet Camera	
A3	DS-2CC5173N-VF	Vari-Focal Indoor Dome Camera	
A4	DS-2CE15C2N-VFIR	Vari-focal IR Bullet Camera	
IP Channel	Camera Model	Description	
D1	DS-2CD2132-I	3.0MP IR Fixed Focal Dome Camera	
D2	DS-2CD4132FWD-IZ	3.0MP WDR Indoor Dome Camera	
D3	DS-2CD2012-I	1.3MP IR Mini Bullet Camera	
D4	DS-2CD4232FWD-IZ	3.0MP WDR IR Bullet Camera	
D5	DS-2CD2232-IS	3.0MP EXIR Bullet Camera	
D6	DS-2CD6362F-I	6.0 MP Fisheye Camera	
D7	DS-2CD6362F-I (D6)	De-warped Panoramic view	
D8	DS-2CD6362F-I (D6)	De-warped PTZ – 1 Fisheye Camera	
D9	DS-2CD6362F-I (D6)	De-warped PTZ – 2 Fisheye Camera	
D10	DS-2CD6362F-I (D6)	De-warped PTZ – 3 Fisheye Camera	
D11	DS-2DF7286-A	2.0MP IR PTZ Dome Camera	

Camera Model: DS-2DF7276-A **Description:** 1.3 MP Network

Speed Dome H.264, 30x zoom 1.3 megapixel 6" speed dome camera, Linux embedded, 1/3" Sony Progressive Scan CCD, audio in/out, alarm in/out, 0.5Lux@F1.6(color), 0.05Lux@F1.6 (B&W), 4.3-129mm lens, 0.1-160°/s Pan, 1-120°/s Tilt, Day&Night: ICR, dual stream, SD card, IP66

Camera Model: DS-2DF7276-A

Demo IP Address: 173.200.91.68

Username: Hikvision

Password: guest

Port: 8000