

DS-VD22D-B/HW7/PAK Cloud Storage Management Server



- Innovate at scale with challenging and emerging workloads
- Increase efficiency and accelerate operations with autonomous collaboration
- Built-in proactive resilience through a complete portfolio of solutions



Specification Hardware Specification

| Hardware Specifications | |
|---------------------------------------|---|
| CPU | Xeon Scalable processors 4410T (10 core 2.7GHz) ×2 |
| Hard Disk | 960G SATA SSD×3/480G SATA SSD×1 |
| Device Dimensions | Form factor: Rack (2U) |
| | Height: 86.8 mm (3.41 inches) |
| | Width :482 mm (18.97 inches) |
| | Depth: |
| | 707.78 mm (27.85 inches) without bezel |
| | 721.62 mm (28.4 inches) – with bezel |
| | For reference only |
| Memory | 32GB DDR5×2 RDIMM |
| Storage Controller | SAS_H355 |
| Power Supply | 800 W (1 + 1) |
| Bezel | security bezel |
| Embedded Management | iDRAC9 |
| | iDRAC Direct |
| | iDRAC RESTful API with Redfish |
| | iDRAC Service Module |
| | Quick Sync 2 wireless module |
| OpenManage™ Software | OpenManage Enterprise |
| | OpenManage Power Manager plugin |
| | OpenManage SupportAssist plugin |
| | OpenManage Update Manager plugin |
| Integrations and Connections | Integrations: BMC Truesight; Microsoft System Center; OpenManage Integrations; Red |
| | Hat Ansible Modules; VMware vCenter and vRealize Operations Manager |
| | Connections: IBM Tivoli Netcool/OMNIbus; IBM Tivoli Network Manager IP Edition; |
| | Micro Focus Operations Manager; OpenManage Connections; Nagios Core; Nagios XI |
| Security | Cryptographically signed firmware |
| | Data at Rest Encryption (SEDs with local or external key mgmt) |
| | Secure Boot |
| | Secure Erase |
| | Secured Component Verification (Hardware integrity check) |
| | Silicon Root of Trust |
| | System Lockdown (requires iDRAC9 Enterprise or Datacenter) |
| | TPM 2.0 FIPS, CC-TCG certified, TPM 2.0 China NationZ |
| I/O & Ports | Front Ports: 1 x iDRAC Direct (Micro-AB USB) port, 1 x USB 2.0, 1 x VGA Internal Ports: |
| | 1 x USB 3.0 (optional) |
| | Rear Ports: 1 x Dedicated iDRAC Ethernet port, 1 x USB 2.0, 1 x USB 3.0, 1 x VGA, 1 x |
| 6 1 10 11 6 1 | Serial (optional) |
| Supported Operating Systems | Not configured by default |
| Physical and Environmental Parameters | |
| Net Weight (without package) | 28.6 kg (63.00 lb.) |
| Gross Weight (with package) | 37.2 kg (82.01 lb.) For reference only |



Available Model

DS-VD22D-B/HW7



Headquarters

No.555 Qianmo Road, Binjiang District, Hangzhou 310051, China T +86-571-8807-5998 www.hikvision.com

Follow us on social media to get the latest product and solution information.





HikvisionHQ



HikvisionHQ



Hikvision_Global



Hikvision Corporate Channel



hikvisionhq