

HUGE PANORAMAS, INCREDIBLE VIEWS

Hikvision Panovu Series Network Camera



What Is The Panovu Camera?

Public plazas, sports arenas, airports, busy traffic intersections – monitoring such large and busy areas today requires security cameras with more and greater requirements than what has traditionally been available. Conventional cameras were not designed for such high-demand installations, and no one wants to fit dozens of new cameras into their budget. More cameras and video channels lead to higher costs and install time, not to mention more difficult system integration.

In very large settings, security personnel need to see more with just one camera – not just a panoramic image, but zoomed-in, detailed views as well.

With that in mind, Hikvision designed the PanoVu Series – all-in-one cameras that capture both excellent panoramas and close-up details. Panoramic images are captured with multiple sensors, rendering 180- and 360-degree panoramic imaging with real-time ultra-HD resolution. The PanoVu Series enhances security system integration, image quality, and cost-efficiency.

The PanoVu product family features high definition panoramic views, as well as ColorVu technology for clear imaging in extremely dark environments. Along with a wide array of smart functions, the PanoVu cameras also utilize AR technology, making advanced video analysis even more efficient. And with one data cable and a power supply, PanoVu cameras guarantee cost-effective installation, along with a user-friendly UI for easy and flexible operation.



Panoramic Views



ColorVu Technology



Smart Functions



AR Technology




Cost-effective Installation

Panoramic Views

Combining several built-in horizontal lenses with PTZ power, one PanoVu camera can capture panoramic images as well as close-up images. Their high-performance lenses present clear, high-resolution, and detailed images.

Each PanoVu camera provides panoramic views using image stitching or quad-directional channels. For example, embedded with an “all-in-one” design, a single product serves as a system that enables seamless image stitching for fluid 180- to 360-degree coverage that’s void of blind spots – ideal for wide open areas.

Equipped with four independently adjustable lenses in one housing, the PanoVu cameras also provide indoor scenarios with security in every direction. Four channels deliver an all-around view, consistently focusing on key regions.



Quad-directional Channels



Image Stitching



ColorVu Technology


The latest panoramic-lens PanoVu cameras are specially equipped with Hikvision's advanced ColorVu low-light imaging technology, featuring a large F1.0 aperture and high-performance sensors. PanoVu cameras guarantee excellent effects in low-lux conditions all day long and rendering rich color images even at night.



Smart Functions

With advanced video analysis and multi-target tracking algorithms selected, PanoVu Cameras also feature a wide range of smart functions in panoramic mode, including automated detection of intrusion, line crossing, unattended baggage, crowd density, and object removal, as well as bullet-dome camera linkage.

A pioneer in the industry, Hikvision designed bullet-PTZ cameras for automatically 3D positioning, activated by just clicking on the target or choosing a region at any position in the panoramic image. The PTZ camera will adjust the focal direction and zoom to the exact place for close-up images. Even more, a crowd density alarm, based on three levels of human density counts, helps to easily manage public safety.



AR Augmented Reality Technology (AR)

AR monitoring not only provides the full coverage of a scene, but also integrates multidimensional information into video imaging to achieve an effective combination of real-world and business data.



Civic Construction




Scenic Areas



Airports



Airports Industrial Parks



Application Scenarios

With intelligent and powerful features, the PanoVu Series Cameras can be used extensively in places like airports, transit stations, gymnasiums, scenic ports, and public squares needing expansive video security coverage.




Squares



Airports



City



Intersection



Intersections



Gym



Parking lot

Cost-effective Installation

With PanoVu equipment, users will enjoy simple and time-saving installation and maintenance – comparable to installing a dome camera, with one data cable and a power supply. It features handy functions and options along with a user-friendly UI to enable flexible and easy operation. Users get panoramas in ultra high resolution, not missing a single detail from the big picture. They can also zoom in to the center to see close-up details just by clicking on the image.



Solution Topology

With intelligent and powerful features, the PanoVu Series Cameras can be used extensively in places like airports, transit stations, gymnasiums, scenic ports, and public squares needing expansive video security coverage.



Panoramic Cameras

I-Series NVR

4K Monitor

Product Family

DS-2CD6984G0-HIS (2.8mm)

180° Stitched 32 MP
PanoVu Camera



1/1.8" Progressive scan CMOS
Max. resolution 8160 x 3616 @ 30 fps in panorama display mode
Panoramic field of view: Horizontal 180°, vertical 95°
Multiple display modes available
Panorama, original, panorama + ePTZ, and divided panorama
Four IR LEDs, up to 20 m IR distance
H.265, H.264
BLC, 3D DNR, HLC, defog, EIS (only in original mode)
Audio and alarm I/O, optional
Flexible power supply options
IP67, IK10

DS-2CD6944G0-HIS (2.8mm)

180° Stitched 16 MP
PanoVu Camera



1/1.8" Progressive Scan CMOS
Max. resolution 4800 x 2688 @ 30 fps in panorama display mode
Multiple display modes available: Panorama, original, panorama + ePTZ, and divided panorama
Up to 20 m IR distance
H.265+, H.264+
BLC, 3D DNR, HLC, defog, EIS (only the original mode supports)
Audio and alarm I/O
IP67, IK10

DS-2CD6924G0-HIS (2.8mm)

180° Stitched 8 MP
PanoVu Camera



180° Image splicing to present all scenes covered by the camera
Built-in heater, ultra-low temperature start up - down to -40
Water and dust resistant (IP67) and vandal proof (IK10)
Smart human density counting and public behavior analysis to increase public area safety

DS-2DP3236ZIXS-D/440

360° Stitched 32 MP
PanoVu Camera
with PTZ



Panoramic Camera
Eight 1/1.8" 4 MP progressive scan CMOS
Up to 2 x 5520 x 2400 resolution @ 30 fps
Field of view: Horizontal : 2 x 180°; vertical: 85°
Min. illumination
Color: 0.0005 Lux @ (F1.6, AGC On)
B/W: 0.0001 Lux @ (F1.6, AGC On)
Supports people density detection in panoramic channel
Tracking PTZ Camera
1/1.8" 4 MP progressive scan CMOS
Up to 2560 x 1440 resolution @ 30 fps
Pan and tilt range: 360° Pan, -15° to 90° Tilt
Min. illumination
Color: 0.0005 Lux @ (F1.2, AGC On)
B/W: 0.0001 Lux @ (F1.2, AGC On)
0 Lux with IR
40x Optical Zoom, 16x Digital Zoom
IR distance: 250 m

DS-2DP2427ZIXS-DE/440

270° Stitched 24 MP
PanoVu Camera
with PTZ



Panoramic Camera
Six 1/1.8" 4 MP progressive scan CMOS
Up to 8160 x 2400 resolution @ 30 fps
Field of view: Horizontal 270°; vertical: 85°
Min. illumination
Color: 0.0005 Lux @ (F1.6, AGC On)
B/W: 0.0001 Lux @ (F1.6, AGC On)
Supports people density detection in panoramic channel
Tracking PTZ Camera
1/1.8" 4 MP progressive scan CMOS
Up to 2560 x 1440 resolution @ 30 fps
Pan and tilt range: 360° Pan, -15° to 90° Tilt
Min. illumination
Color: 0.0005 Lux @ (F1.2, AGC On)
B/W: 0.0001 Lux @ (F1.2, AGC On)
0 Lux with IR
40x Optical Zoom, 16x Digital Zoom
WDR: 120 dB
IR distance: 250 m

DS-2DP1618ZIXS-DE/440

180° Stitched 16 MP
PanoVu Camera
with PTZ



Panoramic Camera
Four 1/1.8" 4 MP progressive scan CMOS
Up to 5520 x 2400 resolution @ 30 fps
Field of view: Horizontal 180°; vertical: 85°
Min. illumination
Color: 0.0005 Lux @ (F1.6, AGC On)
B/W: 0.0001 Lux @ (F1.6, AGC On)
Supports people density detection in panoramic channel
Tracking PTZ Camera
1/1.8" 4 MP progressive scan CMOS
Up to 2560 x 1440 resolution @ 30 fps
Pan and tilt range: 360° Pan, -15° to 90° Tilt
Min. illumination
Color: 0.0005 Lux @ (F1.2, AGC On)
B/W: 0.0001 Lux @ (F1.2, AGC On)
0 Lux with IR
40x Optical Zoom, 16x Digital Zoom
WDR: 120 dB
IR distance: 250 m

DS-2DP0818ZIXS-DE/440

180° Stitched 8 MP
PanoVu Camera
with PTZ



Panoramic Camera
Four 1/1.8" 2 MP progressive scan CMOS
Up to 4096 x 1800 resolution @ 30 fps
Field of view: Horizontal 180°; vertical: 85°
Min. illumination
Color: 0.0005 Lux @ (F1.6, AGC On)
B/W: 0.0001 Lux @ (F1.6, AGC On)
Supports people density detection in panoramic channel
Tracking PTZ Camera
1/1.8" 4 MP progressive scan CMOS
Up to 2560 x 1440 resolution @ 30 fps
Pan and tilt range: 360° Pan, -15° to 90° Tilt
Min. illumination
Color: 0.0005 Lux @ (F1.2, AGC On)
B/W: 0.0001 Lux @ (F1.2, AGC On)
0 Lux with IR
40x Optical Zoom, 16x Digital Zoom
WDR: 120 dB
IR distance: 250 m

DS-2PT3306IZ-DE3 (2mm)

Triple-Directional
PanoVu Mini Camera



Three 1/2.8" progressive scan CMOS
Up to 3 ch of 1920 x 1080 @ 30 fps resolution
Min. illumination:
Color: 0.05 Lux @ (F2.0, AGC On)
B/W: 0.01 Lux @ (F2.0, AGC On)
0 Lux with IR
Field of view: Horizontal 3 x 128.5°;
vertical FOV: 75.7°
Up to 10 m IR radius

DS-2CD6D54G1-ZS/RC (2.8-8mm)

Quad-Directional
Varifocal
PanoVu Camera



Four adjustable lenses in one camera cover up to a 360° field of view, eliminating blind areas; tilt angle can be adjusted
Up to 5 MP lenses, capturing clear images and more details; can be displayed on a video wall
In-ceiling mounting makes the fisheye camera unnoticeable and user friendly
True 120 dB WDR technology means clear imaging against strong back light
Water and dust resistant (IP67) and vandal proof (IK10)
3D DNR technology delivers clean and sharp images
Audio and alarm interface available

**DS-2CD6D54FWD-IZHS
(2.8-12mm)**

Quad-Directional
Varifocal
PanoVu Camera



1/2.7" Progressive Scan CMOS
2560 x 1920 @ 25 fps
Field of view
Horizontal 30° to 101°
Vertical 22.4° to 73°
Diagonal: 37° to 137°
H.265, H.264, H.265+, H.264+
Fiber optic transmission, optional
10 m to 30 m IR range
IP67, IK10
Four flexible lenses
Six behavior analyses, four exception detections,
face detection

**DS-2CD6D24FWD-IZHS
(2.8-12mm)**

Quad-Directional Varifocal
PanoVu Camera



1/2.7" Progressive Scan CMOS
1920 x 1080 @ 30 fps
Field of view
Horizontal 30° to 96.3°
Vertical 17° to 54°
Diagonal: 34° to 121°
H.264, H.264+, H.265, H.265+
Fiber optic transmission, optional
10 m to 30 m IR range
IP67, IK10
Four flexible lens
Six behavior analyses, four exception detections,
face detection

**DS-2CD6D54G1-IZS
(2.8-8mm)**

Quad-Directional
Varifocal
PanoVu Camera



Four adjustable lenses in one camera cover up to a
360° field of view, eliminating blind areas; tilt angle
can be adjusted
Up to 5 MP lenses, capturing clear images and more
details; can be displayed on a video wall
True 120 dB WDR technology means clear imaging
against strong back light
Water and dust resistant (IP67) and vandal proof (IK10)
3D DNR technology delivers clean and sharp images
-S: Audio and alarm interface available

DS-2PT5326IZ-DE

Triple-Directional
PanoVu Camera
with PTZ



Panoramic Camera
Three 1/2.8" progressive scan CMOS
Up to 3 channels of 1920 x 1080 @ 30 fps
Min. illumination:
Color: 0.005 Lux @ (F1.6, AGC On)
B/W: 0.001 Lux @ (F1.6, AGC On)
0 Lux with IR
Field of view: Horizontal: 3 x 80.7°; vertical: 43.5°
Up to 30 m IR radius

PTZ Camera
1/2.8" progressive scan CMOS
Up to 1920 x 1080 @ 30 fps resolution
Min. illumination:
Color: 0.005 Lux @ (F1.6, AGC On)
B/W: 0.001 Lux @ (F1.6, AGC On)
0 Lux with IR
10x optical zoom, 8x digital zoom
Up to 50 m IR distance

DS-2PT3326IZ-DE3

Triple-Directional
PanoVu Mini Camera
with PTZ



Panoramic Camera
Three 1/2.8" progressive scan CMOS
3 ch's of 1920 x 1080 @ 30 fps resolution
Min. illumination:
Color: 0.05 Lux @ (F2.0, AGC On)
B/W: 0.01 Lux @ (F2.0, AGC On)
0 Lux with IR
Supports H.265 video compression
Field of view: Horizontal: 128.5° x 3

PTZ Camera
1/2.8" progressive scan CMOS
Up to 1920 x 1080 @ 30 fps resolution
Min. illumination:
Color: 0.05 Lux @ (F2.0, AGC On)
B/W: 0.01 Lux @ (F2.0, AGC On)
0 Lux with IR
Supports H.265 video compression
4x optical zoom, 8x digital zoom

DS-2PT3122IZ-DE3

Single-Directional
PanoVu Mini Camera
with PTZ



Panoramic Camera
1/2.8" progressive scan CMOS
Up to 1920 x 1080 @ 30 fps resolution
Min. illumination:
Color: 0.05 Lux @ (F2.0, AGC On)
B/W: 0.01 Lux @ (F2.0, AGC On)
0 Lux with IR
Supports H.265 video compression
Field of view: Horizontal: 128.5°

PTZ Camera
1/2.8" progressive scan CMOS
Up to 1920 x 1080 @ 30 fps resolution
Min. illumination:
Color: 0.05 Lux @ (F2.0, AGC On)
B/W: 0.01 Lux @ (F2.0, AGC On)
0 Lux with IR
Supports H.265 video compression
4x optical zoom, 8x digital zoom

**DS-2CD6D52G0-IHS(4mm)
DS-2CD6D82G0-IHS(4mm)**

Dual-Directional
PanoVu Camera



1/2.7" Progressive Scan CMOS
Dual lenses
Flexible lens options:
P: -90 to 90°
T: 0 to 60° (2.8 mm), 0 to 70° (4/6 mm)
R: 0 to 355°
H.264, H.264+, H.265, H.265+
DS-2CD6D52G0-IHS(S): 2560 x 1920 @ 30 fps
DS-2CD6D82G0-IHS(S): 3840 x 2160 @ 24 fps
120 dB WDR
Built-in micro SD/SDHC/SDXC card slot, up to 256 GB
IP67, IK10

Recommended Nvr

DS-9600NI-I8 Series NVR



H.264/H.264+/H.265/H.265+ video formats
16/32/64 channels of IP camera inputs
Decoding capacities: One channel @ 32 MP; two channels
@ 12 MP; 16 channels @ 1080p
8 SATA interfaces for HDD connection
HDD hot swapping with RAID 0/1/5/6/10

HUGE PANORAMAS, INCREDIBLE VIEWS

Hikvision Panovu Series Network Camera

Hikvision Europe
Dirk Storklaan 3
2132 PX Hoofddorp
The Netherlands
T +31 23 5542770
info.eu@hikvision.com

Hikvision Germany
Werner-Heisenberg Str. 2b
63263 Neu-Isenburg,
Germany
T +49 69 401507290
sales.dach@hikvision.com

Hikvision France
6 rue Paul Cézanne,
93360 Neuilly-Plaisance
France
T +33 (0)1 85330450
info.fr@hikvision.com

Hikvision Romania
Splaiul Independentei street
291-293, Riverside Tower,
12th floor, 6th district,
Bucharest, Romania
T +31235542770/988
marketing.ro@hikvision.com

Hikvision Poland
Business Garden, Budynek
B3 ul. Żwirki i Wigury 16B,
02-092 Warszawa
T +48 4600150
info.pl@hikvision.com

Hikvision Benelux
Neringenweg 44,
3001 Leuven, Belgium
T +31 23 5542770
info.bnl@hikvision.com

Hikvision Czech
BETA Building, Vyskocilova
1481/4, Prague 4
Czech Republic
T +42 29 6182640
info.cz@hikvision.com

Hikvision Hungary
Budapest, Reichl Kálmán u. 8,
1031, Hungary
T +36 1 323 7650
info.hu@hikvision.com

 @HikvisionEurope

 @HikvisionEurope

 HIKVISION Europe

HIKVISION
www.hikvision.com