



Title:	How to add a Device to the	ne iVMS 400	0 software		
Date:	9/13/2011	Version:	1.0	Pages	1
Product:	All HIKvision products				
Action Required:	Information Only				

- Start the iVMS-4000 by double clicking on the icon.
- Click the Setup tab
- Right click on the globe labeled "Monitor Area" located at the top left side of the screen and choose the "Add Device" option.
- Create a name for the device and put it in the Device Name field
- Input the device IP address or click the "Online Device" button and double click the desired device from the list.

Note: If the device IP address needs to be changed to match the IP range of your network, click the Online Device button, select the device you wish to change, and click the Modify button.

Once the IP is changed, be sure to type the password into the password field before clicking Save

	Device Type	IP Address	Port	Serial Nu	Serial Number
100	DS_2CD8	10.102.103.251	8000	DS-2CD8133F-E0120	DS-2CD8133F-E012010082
					V3.0build 100820
					Subnet Mask 255 . 255 . 0
					IP Address
					10 . 102 . 103 . 251
					Device Port
					8000
					00-40-48-2c-d5-d5
					Please input password
					Modify Cancel Save
					Restore DVR's default
					ОК

Once back at the "Modify Device Information" screen, input the username and password of the device you are adding.

By default, the username and password for Hikvision devices are: Username: admin Password: 12345

				1
Device Name	Demo DVR	Register Mode	Normal IP 🔹	
Device IP	173 . 200 . 91 . 70	Port	8000	
Username	admin	Password	*****	
Channel No.	16	Multicast	0.0.0.0	
DNS Address		Belongs to area	Monitor Area	
Serial Number	HK-RH5161620090909BB	RR010759156WCV	U	
Outra Destas				41
IS Address rial Number	HK-RH5161620090909BB	Belongs to area RR010759156WCV	Monitor Area	

- The "Channel Number" should reflect the number of Channels on the device you are adding (i.e. DS-9108HFI-S has 8 channels) or the number of channels you wish to preview.
- By default, the port number should be 8000
- Click "Ok"