

NVR Transition Series



New M-Series 8K Replaces the I-Series NVR

Series / Model:	I-Series NVRs				M-Series NVRs			
	DS-7608NI-I2/8P; DS-7616NI-I2/16P; DS-7716NI-I4/16P; DS-7732NI-I4/24P; DS-9616NI-I8; DS-9632NI-I8; DS-9664NI-I8; DS-9664NI-I16				DS-7608NI-M2/8P; DS-7616NI-M2/16P; DS-7716NI-M4/16P; DS-7732NI-M4/24P; DS-7716NI-M4/16P; DS-9632NI-M8; DS-9664NI-M8; DS-9664NI-M16			
Decoding Capacity	6-ch 1080P @ 30fps or 1-ch 32 MP @ 30fps				32-ch 1080p @ 30fps or 2-ch 32 MP @ 30fps			
Outputting Capacity	4K (3840x2160)				8K (7680x 4320) or Dual 4K resolution			
Recording Resolution	4-ch 32 MP video storage				8-ch 32 MP video storage			
HDD Capacity	Max. 10 TB				Max. 14 TB			
Alarm	16 in 8 out				4 in 1 out (only for 2 HDD slots) 16 in 9 out alarm port, 9th port supports CTRL 12V			
Input & Output Bandwidth	8-ch 80/256 Mbps	16-ch 160/256 Mbps	32-ch 256/256 Mbps	64-ch 320/256 Mbps	8-ch 80/256 Mbps	16-ch 160/256 Mbps	32-ch 256/256 Mbps	64-ch 320/256 Mbps

New K-Series NVR Featuring AcuSense

Series / Model:	Q Series	K Series with AcuSense
	DS-7604NI-Q1/4P; DS-7608NI-Q2/8P; DS-7616NI-Q2/16P	DS-7604NXI-K1/4P; DS-7608NXI-K2/8P; DS-7616NXI-K2/16P
Max. Recording Resolution	8 MP	12 MP
HDMI Output	4K	4K
Video Output Mode	HDMI/VGA simultaneous output	4-ch: simultaneous output 8/16-ch: independent output
Decoding Capacity	5-ch @ 1080p (30 fps)	Up to 12-ch @ 1080p (30 fps)
Remote Connection	4ch: 16 - 8/16ch: 64	128
Max Capacity Per HDD	8TB	10TB
Motion Detection 2.0	N/A	All channels
Facial Recognition	N/A	Yes