

How to disable live view output of NVR auxiliary port

Title:	How to disable live view output of NVR auxiliary port	v1.0	Date:	08/15/2020	
Product:	NVR			Page:	1 of 3

Preparation

For NVR models which have independent output interface, if main output and auxiliary output have the different live view configuration. Even if auxiliary output don't connect to screen, it will also waste some decoding ability of NVR.

How to disable live view output of NVR auxiliary port

1. Operation on GUI 4.0

Enter System - Live View - View, then you can see video output interface list.

ලිදි General		Video Output I	HDMI1/VG	GA1			-	- 2		
	>	Camer	Ca HDMI2/VC	6A2/Cha	nnel-Zero		1 03	⊗ 3	DA	\otimes
*		D1	IPCamera 22			115.5	_ 00		04	
Event	>	D2	IPPTZ		MILL					
C Live View	~	D3	IPCamera 03	5		× 6		\otimes'		\otimes
~~~		D4	IPCamera 04		D6		D7		D8	
General		D5	thermal							
View		D6	IPCamera 06	9		⊗ 10		⊗ 11		⊗ 1
Channel Zana		D7			D10		011		012	
Channel-Zero		D8	123		DIO		UII		UIZ	
(F) RS-232		D9	Camera 01	13		0 14		0 15		
Holiday		D10	IPCamera 10	10		× 14		× 15		× 1
		D11	IPCamera 11		D14		D15		D16	5
POS		D12	Camera 01	1000						
Hot Spare		-012	100	TH		III 25 32 36	164		ε	

As for 9664NI-I8, HDMI1/VGA1 and HDMI2/VGA2/Channel-Zero are independent. Choose HDMI2/VGA2/Channel-Zero, and click the icon to stop live view of all channels, then video output of HDMI2/VGA2/Channel-Zero interface will be empty.

Note: after stopped live view of all channels, different split-screen will be the same empty of this video output.

Title:	How to disable live view output of NVR auxiliary port	Version:	v1.0	Date:	08/15/2020
Product:	NVR			Page:	2 of 3

					-				
	Q	1		2		3		4	
Camer	Camera Name				+		+	+	
	IPGamera 22								
D2	IPPTZ	5		6		7		8	
D3	IPCamera 03	U ·							
D4	IPCamera 04		+	+		+			
D5	thermal	W						12	
D6	IPCamera 06	9		10				12	
D7			+		+		+	+	
D8	123								
D9	Camera 01	13		14		15		16	
and the second									
D10	IPCamera 10		+		+				

	Q			2		3		4	5	6
Camer	Camera Name		+		+		+	+	+	+
01	IPCamera 22	7		8		9		10	11	12
02	IPPTZ		+		+		+	+	+	+
03	IPCamera 03	12		14		45		10	47	
D4	IPCamera 04	15	+	14	+	15	+	16 +	17 +	18 +
D5	thermal									
D6	IPCamera 06	19		20		21		22	23	24
D7			+		+		+	+	+	+
D8	123	25		26		27		28	29	30
D9	Camera 01		+		+		+	+	+	+
D10	IPCamera 10	31		32		33		34	35	36
D11	IPCamera 11		+		+		+	+	+	+
D12	Camera 01									
04.2	100	1	BEBE		25 32	36			\$ G Q	■ P: 1/2 ≥
						>				
						`				

## 2. Operation on E-UI 4.0

Firstly, switch to Expert mode. Then enter Configuration - System – Live View. Choose the video output interface and click the icon to stop live view of all channels. After that, all live view of this output interface will be empty.

Title:	How to disable live view output of NVR auxiliary port	Version:	v1.0	Date:	08/15/2020
Product:	NVR			Page:	3 of 3

NVR		$\overline{\mathbf{O}}$	R	٥	×		88 ¢ 또 (
System	∽ General	View Channel-Zero		Color State			
General	Out	tput Interface HDMI	~				
Live View	Please	e enter keyword	0 1	• ²		3	4
User	Camera	No. I Camera Name		D1		•	
Network	> D1	thermal					
Camera							8
Event				•	*	•	*
Record			9	10		11	12
			13	14		15	16
							10
							Stop Live View of All
			• •				G R < 1/2 →
	Ap	ply					
⇔ Easy Mode							

Title:	How to disable live view output of NVR auxiliary port	Date:	08/15/2020		
Product:	NVR			Page:	4 of 3

