

## DS-VD22D-B/HW15 General Purpose Server



- Expand and optimize application performance.
- Automate systems management with OpenManage.
- Rely on Hikvision with built-in security.

### ▪ Specification

Model	DS-VD22D-B/HW15	
Hardware Specifications	CPU	Two Intel® Xeon® SP (4210 × 2)
	Hard Disk	1T 7.2K SATA × 2 (RAID_1)
	Device Dimensions	Form factor: Rack (2U) Chassis depth: 715.5 mm 715.5 × 482 × 86.8 mm (28.2 × 19.0 × 3.4 inch) With package: 960 × 610 × 295 mm (37.8 × 24.0 × 11.6 inch)
	Memory	64 GB DDR4 DIMM
	Storage Controller	PERC H350
	Power Supply	495 W (1 + 1)
	Bezel	security bezel
	Embedded Management	iDRAC9, Enterprise
	OpenManage™ Software	OpenManage Enterprise OpenManage Mobile OpenManage Essentials OpenManage Power Center

	Integrations and Connections	Integrations: Microsoft® System Center, VMware® vCenter™, BMC Software Connections: Nagios & Nagios XI, Oracle Enterprise Manager, HP Operations Manager, IBM Tivoli Netcool / OMNIBus, IBM Tivoli® Network Manager, CA Network and Systems Management
	Security	TPM 1.2 / 2.0 optional, Cryptographically signed firmware, Secure Boot, System Lockdown, Secure erase
	I/O & Ports	Network daughter card options: 4 × 1GE Front ports: Video, 2 × USB 2.0 Rear ports: Video, serial, 2 × USB 3.0 Video card: VGA × 1
	Supported Operating Systems	Not configured by default
<b>Physical and Environmental Parameters</b>	Working Temperature	+ 5 °C to +35 °C (41 °F to 95 °F )
	Working Humidity	8 % to 90 % (without condensation)
	Net Weight (without package)	26.5 kg (58.42 lb.)
	Gross Weight (with package)	35.1 kg (77.38 lb.)
	Storage Temperature	- 40 °C to +70 °C (- 40 °F to +158 °F )

▪ **Available Model**

- DS-VD22D-B/HW15

▪

**Accessory**

- Optional

<b>DS-VD22D-B/HW2 General Purpose Server</b>	<b>DS-VD22D-B/HW5 General Purpose Server</b>	<b>DS-VD22D-B/HW6 General Purpose Server</b>	<b>DS-VD22D-B/HW7 General Purpose Server</b>
			