

DS-VD22D-C/HW15 General Purpose Server



- Innovate at scale with challenging and emerging workloads
- Increase efficiency and accelerate operations with autonomous collaboration
- Built-in proactive resilience through a complete portfolio of solutions

▪ Specification

Hardware Specifications	
CPU	Xeon Scalable processors 4309Y×2
Hard Disk	2TB 7.2K SATA×2(RAID_1)
Device Dimensions	Form factor: Rack (2U) Chassis depth: 707.78 mm 707.78 × 482 × 86.8 mm (27.85 × 19.0 × 3.4 inch) With package: 930 × 667 × 327 mm (36.6 × 26.3 × 12.9 inch)
Memory	64 GB DDR4 DIMM
Storage Controller	SAS_H355
Power Supply	800 W (1 + 1)
Bezel	security bezel
Embedded Management	iDRAC9 iDRAC Service Module iDRAC Direct Quick Sync 2 wireless module
OpenManage™ Software	OpenManage Enterprise OpenManage Power Manager plugin OpenManage SupportAssist plugin OpenManage Update Manager plugin
Integrations and Connections	Integrations: BMC Truesight; Microsoft System Center; OpenManage Integrations; Red Hat Ansible Modules; VMware vCenter and vRealize Operations Manager Connections: IBM Tivoli Netcool/OMNibus; IBM Tivoli Network Manager IP Edition; Micro Focus Operations Manager; OpenManage Connections; Nagios Core; Nagios XI
Security	Cryptographically signed firmware Secure Boot Secure Erase Silicon Root of Trust System Lockdown (requires iDRAC9 Enterprise or Datacenter) TPM 1.2/2.0 FIPS, CC-TCG certified, TPM 2.0 China NationZ
I/O & Ports	Front Ports: 1 x iDRAC Direct (Micro-AB USB) port 1 x USB 2.0 1 x VGA 1 x DVD Rear Ports: 1 x USB 2.0 1 x Serial (optional) 1 x USB 3.0 6 x 1Gb Ethernet 1 x VGA
Supported Operating Systems	Not configured by default

Physical and Environmental Parameters

Net Weight (without package)	28.8 kg (63.49 lb.)
Gross Weight (with package)	37.2 kg (82.01 lb.)

▪ Available Model

DS-VD22D-C/HW15

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
www.hikvision.com



Follow us on social media to get the latest product and solution information.

