



IT CHANNEL PRODUCTS

2021

HIKVISION[®]

Providing choice and value to get the job done

Hikvision aims to develop advanced technologies that help people around the world to analyze information, anticipate problems, and make informed and intelligent decisions.

We continually explore ways to better perceive and understand the world through technology, and to bring new insights and new wisdom to customers, decision-makers, and practitioners.

We provide a wide range of products to allow IT providers to meet the needs of their customers. These are designed with value for money and easy installation in mind.

Our webcams can 'bridge any distance' between meeting attendees. Our monitors and digital signage products are delivering video and messages in high quality in a wide range of scenarios. Our HiWatch range makes professional security simple for homes and small businesses. And our Storage portfolio allows customers to keep their data for future use. We also provide switches and cabling to complete the system.

Whatever the needs of your customer, we can help you fulfill them.



Contents

• Hikvision Webcams	1
• Conference Flat Panel	5
• Digital Signage	9
• Super Narrow Bezel Monitors	11
• Hikvision Gigabit Switch	13
• HiWatch Kits	15
• Intelligent Storage	16
• Network Cable	23

Hikvision Webcams

Hikvision's brand new line of Webcams contains a wide variety of options to guarantee the perfect fit for any user in any scenario. Equipped with high edge definition, noise reduction, and USB plug & play, you can get it all – studio-quality imaging, crystal clear sound, and ease of use.



Horizontal /
Vertical



Supplemental
Light



Up to 4K



Wide-angle
Lens



USB



Auto Focus



Hi-Def Sound



Plug and
Play



Image Rendering to the Fullest



With up-to-4K definition on board, Hikvision webcams present clear and smooth video.

Sharp Auto Focus



Rapid focus on details to bring out every shining part of your product.

Never Miss a Word



HD sound pick-up with intelligent noise reduction ensures back-ground sounds won't interfere.

See What's Meant to Be Seen




The up-to-95° diagonal field of view covers a wide view and without distortion.

Look Your Best Every Moment



Built-in supplemental light, 5 levels of brightness, providing the best ambiance, even in dim conditions.


Flip Over as Needed



Switch image orientation simply with a side flip.

	Value Series			Pro Series			Live Series		
Model	DS-U02(2MP) DS-U04(2K)	DS-U02P(2MP) DS-U04P(2K)	DS-U12(2MP)	DS-UC2(2MP)	DS-UC4(2K)	DS-UC8(4K)	DS-UL2(2MP)	DS-UL4(2K)	DS-UL8(4K)
Product Comparison									
Auto Focus	-	√	-	√	√	√	√	√	√
Portrait Enhancement	-	-	-	√	√	√	√	√	√
FOV	Horizontal: 86°/80° Vertical: 55°/50° Diagonal: 95°/88°	Horizontal: 80° Vertical: 50° Diagonal: 88°	Horizontal: 80° Vertical: 50° Diagonal: 88°	Horizontal: 87° Vertical: 55° Diagonal: 95°	Horizontal: 80° Vertical: 50° Diagonal: 88°	Horizontal: 83° Vertical: 53° Diagonal: 91°	Horizontal: 87° Vertical: 55° Diagonal: 95°	Horizontal: 81° Vertical: 50° Diagonal: 90°	Horizontal: 83° Vertical: 53° Diagonal: 91°
Angle Adjustment	Pan: 360° Tilt: -15° to 15°	Pan: 360° Tilt: -15° to 15°	Pan: 0° Tilt: -15° to 15°	Pan: 0° to 360° Tilt: 0° to 35°	Pan: 0° to 360° Tilt: 0° to 35°	Pan: 0° to 360° Tilt: 0° to 35°	Pan: 0° Tilt: 0° to 35°	Pan: 0° Tilt: 0° to 35°	Pan: 0° Tilt: 0° to 35°
Audio In	1 built-in mic	1 built-in mic	1 built-in mic	2 built-in mics	2 built-in mics	2 built-in mics	2 built-in mics	2 built-in mics	2 built-in mics
Cable Length	1.5 m	1.5 m	1.5 m	2 m	2 m	2 m	2m	2 m	2 m
Video Output	USB 2.0	USB 2.0	USB 2.0	USB 2.0	USB 2.0	USB 3.0	USB 2.0	USB 2.0	USB 3.0
Housing Material	Plastic	Plastic	Plastic	Metal	Metal	Metal	Plastic	Plastic	Plastic
Packing List	Camera × 1 USB cable × 1 Quick start guide × 1	Camera × 1 USB cable × 1 Quick start guide × 1	Camera × 1 USB cable × 1 Quick start guide × 1	Camera × 1 USB cable × 1 Quick start guide × 1	Camera × 1 USB cable × 1 Quick start guide × 1	Camera × 1 USB cable × 1 Quick start guide × 1	Camera × 1 USB cable × 1 Quick start guide × 1 Bracket × 1 Tripod × 1	Camera × 1 USB cable × 1 Quick start guide × 1 Bracket × 1 Tripod × 1	Camera × 1 USB cable × 1 Quick start guide × 1 Bracket × 1 Tripod × 1
Warranty	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years	2 years

Video Conference Products



Speakerphone - Wired model

- 8-mic array, 5 m long distance pickup
- Built-in high fidelity speaker
Echo cancellation technology helps you hear clearer
- Upward mic and surrounding speaker design, perfect fitting the meeting scene
- AI noise reduction
Transient noise reduction + steady noise reduction
- Mic mute / volume up /volume down



iDS-UAC-S1V

Speakerphone - Wireless model

- 8-mic array, 5 m long distance pickup
- Built-in high fidelity speaker
Echo cancellation technology helps you hear clearer
- Upward mic and surrounding speaker design, perfect fitting the meeting scene
- AI noise reduction
Transient noise reduction + steady noise reduction
- Mic mute / volume up /volume down
- 3 connection modes: Bluetooth, USB wireless receiver, USB cable connection
- 10-hour rechargeable battery



iDS-UAC-S1

All in one – Wired model

- All-in-one design with camera, microphone and speaker, meeting high-quality audio and video conferencing demands
- 2 MP wide FOV camera without distortion, acceptable for all participants showing on the screen at the same time
- 4-mic array, 5 m long distance pickup
- Built-in high fidelity speaker
Echo cancellation technology helps you hear clearer
- AI noise reduction
Transient noise reduction + steady noise reduction
- Equipped with bluetooth remote controller, adjusting views and volume at any time

Wired Model




iDS-UAC-X12



DS-U102
2MP

Lens	3.1 mm to 15.5 mm vari-focal lens, 5× optical zoom
Auto Focus	✓
WDR	≥ 120 dB
FOV	Horizontal: 84.9° to 20.8° Vertical: 92.8° to 23.8° Diagonal: 94° to 23.8°
Angle Adjustment	Pan: -170° to 160° Tilt: -28° to 28°
Audio In	built-in mic
Cable Length	4.5 m
Video Output	USB 2.0
Housing Material	Metal
Packing List	Camera (including lens cover) × 1, Remote Control × 1, Power Adapter × 1, Cable × 1, Bracket × 1, Screws × 1, Quick Start Guide × 1
Warranty	2 years



Bracket



Camera



Remote Control



Cable



Adapter

Conference Flat Panel

All-in-one design

Value beyond price

- Simple installation and quick deployment
- Easy operation and convenient maintenance
- Elegant appearance and outstanding display

Wireless projection

Easier than ever

- Wireless projection and bi-directional control
- Multi-terminal simultaneous projection
- Duplicated displays for synchronized projection

Intelligent whiteboard

Free idea sharing

- Pen pickup detection, know what you think
- Multi-person writing and convenient material import
- Code scan sharing for easy meeting result saving

Remote conference

Communication without distance

- Compatible with mainstream remote conference software
- Rich remote conference peripherals available



Conference Flat Panel – Advanced Industrial Design



Optical Bonding Screen: writing without sense of extra space.



Linear Pen Slot: holding the pen magnetically when finish using.

Highlight Ink Screen Logo: delicate texture, business style.

Matte Powder Coating: matching the color of the whole device.



Elegant Appearance: 150 mesh ultra-fine sandblasting frame, comparable to the texture of a laptop.











High Color Gamut: $\geq 90\%$ color gamut outstanding display.

Newly Designed Pen: TPU nib material for fluent writing and fall-protection.

Pick-up Detection: Show prompts when the pen is picked up.




Bracket Upgrade: beautiful and elegant, easy to install and cost-effective.

	Local Collaboration				Remote Collaboration			
Model	DS-D5B55RB/A(55")	DS-D5B65RB/A(65")	DS-D5B75RB/A(75")	DS-D5B86RB/A(86")	DS-D5B55RB/B(55")	DS-D5B65RB/B(65")	DS-D5B75RB/B(75")	DS-D5B86RB/B(86")
Product Comparison								
Touch Type	Infrared touch screen				Infrared touch screen			
Glass	Smooth tempered glass being anti-glare and explosion-proof				Smooth tempered glass being anti-glare and explosion-proof			
Touch Point	20 point multi-touch				20 point multi-touch			
Backlight	DLED				DLED			
Resolution	3840 × 2160 @ 60 Hz				3840 × 2160 @ 60 Hz			
Color Depth	10 bit				10 bit			
Visual Angle	Horizontal 178°, vertical 178°				Horizontal 178°, vertical 178°			
Response Time	6 ms				6 ms			
Contrast Ratio	4500 : 1	1200 : 1			4500 : 1	1200 : 1		
Brightness	350 cd/m ²				350 cd/m ²			
Built-in Camera	-				√ 8 MP Built-in Camera			
Built-in Microphone	-				√ 6-array Microphone			

Conference Flat Panel – Accessories


USB Camera



- 8 MP CMOS, 3840 × 2160
- Low-distortion lens
- USB Type-C interface, USB 3.0 protocol
- Plug-and-play, no need driver software
- Support sharp autofocus


DS-UC8

Bracket



- Suitable for 86" model
- Silver gray, SPCC high quality steel plate
- Sheet metal spraying

DS-D5ABKY2-B




- Suitable for 55/65/75" model
- Silver gray, SPCC high quality steel plate
- Sheet metal spraying

DS-D5ABKY2-S


Note: wall-mounted bracket is included in the interactive display's package list by default.

Omnidirectional Microphone



- 360° mic coverage
- 256 ms acoustic echo cancellation
- Dynamic Noise Reduction (DNR)


DS-65VA300L



- Built-in 6 microphone arrays
- 5 meters 360° mice coverage
- Support Bluetooth, USB and AUX
- Support AEC (Automatic Echo Cancellation), AGC (Automatic Gain Control), ANC (Automatic Noise Cancellation) and VAD (Voice Activity Detection)


DS-D5A0W

OPS



- 6th-generation Intel® Core i5 7400 3.0 GHz
- Memory 8 GB, SSD 128 GB
- Intel Integrated Graphics, support H.265 and 4K resolution
- Interfaces: 6 x USB 3.0, 1 x HDMI, 1 x DP
- Support MSATA system disk quick start
- Standard Intel OPS interface
- Without Windows OS

DS-D5AS5/8S1L



- 8th-generation Intel® Core i5 9400 3.0 GHz
- Memory 8 GB, SSD 256 GB
- Intel Integrated Graphics 500, support H.265 and 4K resolution
- Interfaces: 4 x USB 3.0, 2 x USB2.0, 1 x HDMI, 1 x DP
- Support MSATA system disk quick start
- Built-in Win 10 OS

DS-D5AS5/8S2L

Diversified Advertisement Media Player Digital Signage

Up to 4K resolution to display extremely clear image and video.

HDMI & VGA input interfaces allow device to work as normal display content from different signals


Flexible installation for wall-mounted digital signage from either portrait or landscape mode



Wall-mounted Digital Signage			
Model	DS-D6032FN-B(31.5")	DS-D6043UN-B(43")	DS-D6055UN-B(55")
Product Comparison			
Backlight	ELED	DLED	
Resolution	1920 × 1080 @ 60 Hz	3840 × 2160 @ 60 Hz (4K)	
Brightness	350 bit	500 bit	
Visual Angle	Horizontal 178°, vertical 178°		
Resolution	3840 × 2160 @ 60 Hz		
Response Time	6.5ms	8ms	
Contrast Ratio	4000 : 1	1200 : 1	4000 : 1
Brightness	500 cd/m ²		
HDMI Input	HDMI Input × 2		
Built-In Storage	16 GB EMMC		
Built-In System	Android 8.1		


Asynchronous Display

To design programs in HikCentral FocSign, and release them to the digital signage to play by schedule.



Synchronized Display

To display HDMI/VGA input video content.



Super Narrow Bezel Monitors



1920 × 1080



HDMI, VGA interfaces



178° wide view angle
0 × 1080



24/7 operation



VESA mounting standard

Model	DS-D5022FN-C(21.5")	DS-D5024FN/EU(23.8")	DS-D5027FN/EU(27")
Product Comparison			
Optimal working resolution	1920 × 1080 @ 60Hz		
Active Display Area	476 × 268 mm	527.04 × 296.46 mm	598 × 336 mm
Brightness	250 cd/m ²	250 cd/m ²	300 cd/m ²
Contrast	3000: 1	3000: 1	1000: 1
Color	16.7 M	/	16.7 M
Response time	13 ms	16 ms	14 ms
Viewing Angle	Horizontal 178° Vertical 178°		
Interfaces	VGA input × 1 HDMI input × 1		
Wall-mounting Hole	75 × 75 mm	75 × 75 mm	100 × 100 mm
Accessories	AC power cable × 1, Base bracket × 1, User manual × 1, Quick start guide × 1, HDMI cable × 1	Power adapter × 1, Power cable × 1, Base bracket × 1, HDMI 1.5 m × 1, User Manual × 1	HDMI cable × 1, Power Cord × 1, Base bracket × 1, User Manual × 1
Warranty	2 years		

Hikvision Gigabit Switch

No configuration.

Just power up, connect the devices, and it works.

Suitable for a variety of scenarios



Plug and play



Self-adaptive
10/100/1000 M





Excellent heat
dissipation
Reliable fan-free design



PoE




6 KV surge
protection



	Desktop Switch	Non-PoE Switch	Smart Managed Switch		
Model	DS-3E0508D-E(8×1000 Mbps)	DS-3E0505-E(5×1000 Mbps)	DS-3E1105P-EI(5×100 Mbps)	DS-3E1508-EI(8×Gigabit)	DS-3E1516-EI(16×Gigabit)
Product Comparison			 ★	 ★	 ★
PoE PoE port PoE power budget	-	-	√ Ports 1 to 4 60 W	-	-
6 KV surge protection	-	-	√	-	-
Standard	IEEE 802.3, IEEE 802.3u, IEEE 802.3x, IEEE 802.3ab	IEEE 802.3, IEEE 802.3u, IEEE 802.3x	IEEE 802.3, IEEE 802.3u, IEEE 802.3x	IEEE 802.3, IEEE 802.3u, IEEE 802.3x, IEEE 802.3ab	IEEE 802.3, IEEE 802.3u, IEEE 802.3x, IEEE 802.3ab
Switching capacity	16 Gbps	10 Gbps	10 Gbps	16 Gbps	32 Gbps
Packet forwarding rate	11.904 Mpps	7.44 Mpps	7.44 Mpps	11.904 Mpps	23.808 Mpps
Shell	Plastic	Metal Fan-free design	Metal Fan-free design	Metal Fan-free design	Metal Fan-free design
Dimensions (L × H × D)	142 × 90 × 23 mm	103 × 25.6 × 61.1 mm	105 × 27.6 × 83.1 mm	170 × 27.6 × 93.1 mm	257 × 44.5 × 175.8 mm
Warranty	2 years	2 years	2 years	2 years	2 years

★ Smart Managed Function

 Visualized Topology Management

 Network Health Monitor

 Real-Time Alarm Push

 Video Control and Preview



HiWatch Kits

IP Kit 2 MP PoE Series

HWK-N4142TH-MH/P

HWK-N4142BH-MH/P



- Four 2 MP turret cameras with efficient H.265
- 1 TB pre-installed HDD
- One 4-ch PoE NVR with decoding up to 4-ch @ 1080p

- Four 2 MP turret cameras with efficient H.265
- 1 TB pre-installed HDD
- One 4-ch PoE NVR with decoding up to 4-ch @ 1080p

IP Kit 4 MP PoE Series

HWK-N4184TH-MH

HWK-N4184BH-MH



- Four 4 MP turret cameras with efficient H.265
- 1 TB pre-installed HDD
- One 8-ch PoE NVR with decoding up to 4-ch @ 1080p

- Four 4 MP bullet cameras with efficient H.265
- 1 TB pre-installed HDD
- One 8-ch PoE NVR with decoding up to 4-ch @ 1080p

Recommend Installation Indoor / Outdoor

Intelligent Storage

SSD

Memory

Flash cards

External series

NAS

Embedded Solutions




Accessories



CONSUMER CLASS SSD

	Consumer SATA SSD				Gaming PCIe SSD			
	2.5" SATA SSD			M.2 SATA SSD	PCIe SSD			
Model	C100	Minder(S)	E100	E100N	Minder(P)	E1000	E2000	E3000 (Low power consumption)
Product Comparison								
R/W speed	120 GB: 460/360 MB/s 240 GB: 530/400 MB/s 480 GB: 550/470 MB/s 960 GB: 550/480 MB/s 1920 GB 560/520 MB/	120 GB: 460/360 MB/s 240 GB: 530/400 MB/s 480 GB: 550/470 MB/s 960 GB: 550/480 MB/s	128 GB: 550/430 MB/s 256 GB: 550/450 MB/s 512 GB: 550/480 MB/s 1024 GB: 560/500 MB/s	128 GB: 550/440 MB/s 256 GB: 560/480 MB/s 512 GB: 560/500 MB/s 1024 GB: 560/510 MB/s	128 GB: 980/620 MB/s 256 GB: 2300/1200 MB/s 512 GB: 2500/2100 MB/s 1024 GB: 2500/2100 MB/s	128 GB: 980/620 MB/s 256 GB: 1950/1260 MB/s 512 GB: 2000/1610 MB/s 1024 GB: 2100/1800 MB/s	256 GB: 3100/1300 MB/s 512 GB: 3300/2100 MB/s 1024 GB: 3500/3000 MB/s 2048 GB: 3500/3000 MB/s	256 GB: 3230/1240 MB/s 512 GB: 3500/1800 MB/s 1024 GB: 3520/2900 MB/s
Warranty	3 years			3 years	3 years			5 years







INDUSTRIAL CLASS SSD

	Surveillance SSD		Industrial SSD		Data Center SSD
	2.5" SATA SSD		mSATA SSD	M.2 SATA SSD	2.5" SATA SSD
Model	V100	V210	S210M	S210N	D200
Product Comparison					
R/W speed	128 GB: 565/495 MB/s 256 GB: 560/530 MB/s 512 GB: 560/520 MB/s 1024 GB: 560/520 MB/s	128 GB: 525/475 MB/s 256 GB: 565/530 MB/s 512 GB: 550/530 MB/s 1024 GB: 560/525 MB/s	32 GB: 220/165 MB/s 64 GB: 445/290 MB/s 128 GB: 560/520 MB/s 256 GB: 560/510 MB/s 512 GB: 550/530 MB/s 1024 GB: 560/525 MB/s	32 GB: 220/175 MB/s 64 GB: 440/305 MB/s 128 GB: 560/510 MB/s 256 GB: 560/525 MB/s 512 GB: 550/525 MB/s 1024 GB: 560/525 MB/s	200 GB: 535/250 MB/s 480 GB: 535/410 MB/s 960 GB: 530/410 MB/s
Warranty	3 years		3 years		5 years

DRAM MEMORY



	Standard Memory		Performance Memory		RGB Gaming memory
Model	UDIMM Module U1	SODIMM Module S1	U10 Silver	U10 Midnight	DDR4 3200 U100
Product Comparison					
	4 GB/8 GB/16 GB	4 GB/8 GB/16 GB	8 GB/16 GB	8 GB/16 GB	8 GB/16 GB
Key features	DDR3 1600/ DDR4 2666/ DDR4 3200 High Quality IC Chips Plug and Play	DDR3 1600/ DDR4 2666/ DDR4 3200 High Quality IC Chips Plug and Play	Silver DDR4 3000/Midnight DDR4 3200 Self-designed model Aluminum heat spreader Intel XMP overclocking potential		XMP Supported, one click overclocking Dynamic RGB lighting Aluminum heat spreader Ultimate gaming experience
Warranty	Lifetime Warranty		Lifetime Warranty		Lifetime Warranty

MEMORY CARD

	Consumer Card	Surveillance Card				Gaming Card
	Class10 USH-I	Lifetime Warning / Health monitoring / R/W Lock			Dedicated to tachograph video surveillance	Specially designed for handheld console
Model	V100	HS-TF-L2	HS-TF-P1	HS-SD-P10	HS-TF-M1	HS - TF - G2
Product Comparison						
R/W speed	8/16/32/64/128/256 G R/W up to 92/50 MB/s Water/Shock/X-ray proof Temperature : 0 - 70	16/32/64/128/256 G R/W 95/15-55 MB/s Water/Shock/X-ray proof 0 - 70	32/64/128 GB R/W up to 100/85 MB/s Water/Shock/X-ray proof -25 - 85	32/64/128/256 G R/W 95/25-85 MB/s Water/Shock/X-ray proof -25 - 85	32/64/128 G R/W up to 100/85 MB/s Water/Shock/X-ray proof -25 ~ 85 P/E cycle times up to 3000	128/256 GB R/W 170/90 MB/s / 0 - 70 Smooth gaming experience
Warranty	7 years	2 years				Lifetime Warranty

ESSD & EHDD


Cost-effective External Storage

T200N	T100I	T30	T30 with Rubber
			

Lightweight & pocket-size
Take your files, games, music, movies and anything you want with you anywhere at anytime.

Capacity — ESSD from 128 GB to 1 TB; EHDD at 1 TB or 2 TB
Speed — ESSD T200N & T100I: up to 450MB/s; EHDD T30: up to 120MB/s

High-end External Storage


Elite 7 Series


All-metal body
dust-, shock- resistant
IPx7 waterproof
Great heat dissipation

Capacity — from 500 GB to 2 TB
Speed — up to 1060 MB/s

USB DRIVES



USB2.0

M200G	M200R
	
Camera look 16 GB Plastic	Roadster look 8 GB - 64 GB 7.4mm thick Anti-dropping

USB2.0/ 3.0

M200	M200S
	
Super Mini-size 8GB - 64GB All Metal	Twister look 8GB - 64GB Metal + Plastic

High-end External Storage

ENGIN


Cyberpunk look 128 GB - 1 TB Up to 540 MB/s All Metal

Home NAS


H100



H100



- 2-Bays supports up to 8 TB data storage
- With App 'Hikbox', access media anytime
- Multi-screen interaction
- Ultra low power, more energy
- Recommended for home, SOHO, and SMEs



Embedded Solutions

eMMC5.1(153 FBGA)



Industry eMMC
Samsung MLC, HS400
Capacity: 4/8/16 GB

R/W speed up to 160/110 MB/s
Hardware reset signal
Data removal commands
Multiple partitioning
Power off notification
Health report

Consumer eMMC
Samsung TLC, HS400
Capacity: 32/64/128 GB

R/W speed up to 230/150 MB/s
Enhanced reliable write
Background operations
Data removal commands
Power off notification
Health report

Accessories

FC20 (Portable PD 20 W fast charger Adapt to all USB-C PD devices)



UK

EU

US

- **High speed charging**
- **Broad compatibility**
PD2.0 PD3.0 QC2.0 QC3.0 FCP
BC1.2 APPLE 5V/2.4A
- **Safe & reliable**
Over-temperature & over-voltage & over-current & short-circuit protection
- **Compact**

Network Cable

99.95% Pure Copper

Higher conductivity with lower signal transmission attenuation



0.565 mm Wire Diameter

Transmission now more stable with reduced resistance




Precise Twisting Technology

Improved transmission data fluidity



CM/CMX Fire Resistance Ratings

Sheathing material resistant to fire, stretching, and aging




Sheath

Twisted Pair

Separator
(CAT6)

Copper Core

	CAT 6		CAT 5E	
Model	DS-1LN6-UU	DS-1LN6-UE-W	DS-1LN5E-S	DS-1LN5E-E/E
Product Comparison				
Material of Conductor	Solid Copper		Solid Copper	
Purity of Copper	99.95%		99.95%	
Diameter of Conductor	0.565 mm	0.53 mm	0.5 mm	0.5 mm
AWG Gauge	23 AWG	24 AWG	24 AWG	25 AWG
Separator	Yes		No	
Material of Sheath	PVC		PVC	
Color of Sheath	Orange	White	Gray	
Flame-retardant Rating	Eca		Eca	
Fluke Test	Pass		Pass	
Certifications	CPR, UL, CE-RoHS, RCM, REACH SVHC	CPR, UL, CE-RoHS, RCM	CPR, UL, CE-RoHS, RCM	
Length	305 meters		305 meters	
Warranty	5 years		5 years	

IT CHANNEL PRODUCTS

2021

Hikvision Europe

Dirk Storklaan 3
2132 PX Hoofddorp
The Netherlands
T +31 23 5542770
info.eu@hikvision.com

Hikvision France

6 rue Paul Cézanne,
93360 Neuilly-Plaisance
France
T +33 (0)1 85330450
info.fr@hikvision.com

Hikvision Poland

Business Garden, Budynek B3 ul.
Żwirki i Wigury 16B,
02-092 Warszawa
T +48 4600150
info.pl@hikvision.com

Hikvision Czech

BETA Building, Vyskocilova
1481/4, Prague 4
Czech Republic
T +42 29 6182640
info.cz@hikvision.com

Hikvision Germany

Werner-Heisenberg Str. 2b
63263 Neu-Isenburg,
Germany
T +49 69 401507290
sales.dach@hikvision.com

Hikvision Romania

Splaiul Independentei street 291-
293, Riverside Tower, 12th floor, 6th
district,
Bucharest, Romania
T +31235542770/988
marketing.ro@hikvision.com

Hikvision Benelux

Neringenweg 44,
3001 Leuven, Belgium
T +31 23 5542770
info.bnl@hikvision.com

Hikvision Hungary

Budapest, Reichl Kálmán u. 8,
1031, Hungary
T +36 1 323 7650
info.hu@hikvision.com



@HikvisionEurope



@HikvisionEurope



HIKVISION Europe

HIKVISION[®]

www.hikvision.com