

# MOBILE ANPR CAMERA Smart ANPR on the Move



AE-VC583I-ISF




### Flexible installation for a host of scenarios

Supporting **vertical** and **horizontal** installation, Hikvision's Mobile ANPR Camera can suit various vehicles and conditions with flexible applications for front or rear capture.

#### In vertical installations,

the Mobile ANPR Camera can cover 2 lanes with side capture, featuring a lens focal length of 8/12 mm with 5 MP resolution.




Lens	Instillation Angle	Horizontal Field Angle	Stop-line Distance
8mm	≤20°	40°	8m≤ L1 ≤20m
12mm	≤15°	26°	14m≤ L1 ≤32m

## Accurate recognition in environmentally-friendly ways

Built-in IR covers license plate recognition distances up to 30 m. Accuracy at night is supported by environmentally-friendly, mixed supplemental lighting.

#### In horizontal installations,

the Mobile ANPR Camera can offer front or rear capture over standard 3.5-3.75 m lanes.



Lens	Detection Distance	
8mm	L1 ≤22m	H1: 16m
12mm	L2 ≤33m	H2: 15.2m
16mm	L3 ≤44m	H3: 15.2m

### Sufficient and smart storage with fail-safe design

Hikvision's mobile ANPR camera features built-in eMMC storage up to 8 GB with image caching, supporting block lists for intelligent and safer operation.

Product Specification	AE-VC583I-IS/P(H)(RJ45)	AE-VC583I-IS/P(H)(M12)	AE-VC583I-IS/P[V](RJ45)	Vertical AE-VC583I-IS/P(V)(M12)	
Lens & Resolution	8 mm, 5 MP	8/12/16 mm, 5 MP	8/12/16 mm, 5 MP	8/12/16 mm, 5 MP	
Connector	RJ45	M12	RJ45	M12	
IP	IP68 & IP69K				
Sensor	1/2.7" Progressive Scan CMOS				
Power Supply	9 - 36 VDC, PoE (802.3 af, 36-57 V)				



Headquarters

No.555 Qianmo Road, Binjiang District, Hangzhou 310051, China T +86-571-8807-5998 overseasbusiness@hikvision.com

