

## DS-K1101 Pro 1101 Series Card Reader



- M1/ EM card reader
- PC+ABS material shell with PMMA panel design
- Built-in audible beeper
- RS-485 and Wiegand interface
- IP64

## ▪ Specification

Authentication	
Card reading frequency	13.56MHz
General	
Power supply	12V DC, ≤ 500 mA
Power consumption	≤ 2 W
Working temperature	-20 °C to 65 °C (-4 °F to 149 °F)
Working humidity	10% to 90% (no condensing)
Dimensions	132.0 mm × 92.3 mm × 20.5 mm (5.20" × 3.63" × 0.81")
Installation	壁装吗? Applied for 120 Gang Box Only
Weight	≤ 0.14 kg (0.3 lb)
Keypad	DS-K1101M: No keypad DS-K1101MK: 12 keys (0 to 9, *, #)
Buzzer	support
Function	
ID settings	via DIP Switch

## ▪ Available Model

DS-K1101

### Headquarters

No.555 Qianmo Road, Binjiang District,  
Hangzhou 310051, China  
T +86-571-8807-5998  
www.hikvision.com



Follow us on social media to get the latest product and solution information.



Hikvision



HikvisionHQ



HikvisionHQ



Hikvision\_Global



Hikvision  
Corporate Channel



hikvisionhq