

## DS-2CE56D0T-VFIRE 2 MP Indoor PoC Manual Varifocal Dome Camera



- 2 MP varifocal PoC dome camera
- 2.8 mm to 12 mm varifocal lens
- Up to 30 m IR distance for bright night imaging
- Transmits both HD video and power over the same coaxial cable

## ▪ Specification










Camera	
Image Sensor	2 MP progressive scan CMOS
Max. Resolution	1920 (H) × 1080 (V)
Min. Illumination	0.01 Lux@(F1.4, GC ON), 0 Lux with IR
Shutter Time	PAL: 1/25 s to 1/50, 000 s NTSC: 1/30 s to 1/50, 000 s
Day & Night	IR cut filter
Angle Adjustment	Pan: 0° to 340°, Tilt: 0° to 75°, Rotation: 0° to 355°
Signal System	PAL/NTSC
Lens	
Lens Type	2.8 mm to 12 mm
Focal Length & FOV	105.2 ° to 32.8 °
Lens Mount	Φ14
Image	
Image Settings	Brightness, Sharpness, DNR, Mirror
Frame Rate	PAL: 1080p@25fps NTSC: 1080p@30fps
Day/Night Mode	Smart/color/BW(Black and White)
Wide Dynamic Range (WDR)	DWDR
Image Enhancement	BLC
AGC	Low/middle/high
Interface	
Video Output	1 HD analog output
General	
Material	Plastic
Dimension	Ø 136 mm × 102 mm (Ø 5.35" × 4.02")
Weight	600 g (1.32 lb.)
Operating Condition	-40 °C to 60 °C (-40 °F to 140°F), humidity 90% or less (non-condensation)
Language	English
Power Supply	12 VDC ± 15%/PoC.af
Consumption	Max. 4 W
IR Range	Up to 30 m

## ▪ Available Model

DS-2CE56DOT-VFIRE(2.8-12mm)

▪ **Accessory**

▪ **Optional**

DS-1275ZJ-SUS(Grey)#UK	DS-1250ZJ Rain Shade	DS-1253ZJ-L Rain Shade	DS-1276ZJ-SUS Corner Mount	DS-1249ZJ
				
DS-1275ZJ-SUS Vertical Pole Mount	DS-1271ZJ-130 Pendant Mount	DS-1273ZJ-130 Wall mount	DS-1273ZJ-130B Wall mount	
				

**Headquarters**

No.555 Qianmo Road, Binjiang District,  
Hangzhou 310051, China  
T +86-571-8807-5998  
www.hikvision.com



Follow us on social media to get the latest product and solution information.

