

## ISD-SC6550D-4CVL

### Dual View X-ray intelligent Security Inspection System

ISD-SC6550D-4CVL dual-source dual-view X-ray intelligent security inspection system integrates the functions of intelligent recognition, face recognition, behavior analysis and speed change, etc, which can better solve problems such as missed inspection caused by low concentration of security operators and excessive security pressure during rush hours. The products are applicable to government agencies, scenic spots, courts, procuratorates, prisons, embassies, factories, schools, hospitals, gymnasiums, exhibition halls, entertainment venues and other scenes, and can be used for security check of briefcases, postal parcels, express parcels, carry-on luggage and small parcels.



- Advanced material properties identification technology can effectively identify the equivalent of atomic number of the item(such as metal and organics) and give a different color
- Intelligent recognition technology is a deep learning recognition algorithm with full independent intellectual property rights, which realizes the integration of intelligent recognition algorithm and X-ray imaging software, and achieves better recognition effect
- Radiation leakage reaches environmental level
- speed can be changed according to the scene
- Double lead curtain design effectively reduce the radiation lead shade place
- Supports access to Hik-Central, and implement the data upload
- Data storage supports local storage, view and playback of the images and alarm information
- Event tracing can organically combine X-ray image with passenger video information to realize human package tracing
- Supports login with face and fingerprint authentication



## ▪ Specification





Model		ISD-SC6550D-4CVL
Size	Tunnel Size	650 mm(W) × 500 mm(H)
	Dimension	2454 mm × 1419 mm × 1376mm (L x W x H)
	Operation Desk Size	1200 mm × 700 mm × 1142mm (L x W x H)
Performance	Line Resolution	Bottom Angle of View: 36AWG Side Angle of View: 38AWG
	Penetration Steel panel	30mm standard, 34mm typical
	Spatial Resolution	Bottom Angle of View:1.0mm(Horizontal and vertical) Side Angle of View: 1.0mm(Horizontal and vertical)
	X-Ray Generator	160kV 1.2mA(Adjustable)
	X-Ray Cooling/Work Period	Oil Cooling/Continuous
	Film Security	Standard of ASA/ISO1600
Radiation	Leakage	< 1μGy/h, 50mm away from the device sheet
Conveyor	Conveyor Height	678mm
	Speed	0.2m/s, 0.3m/s, 0.4m/s adjustable
Monitoring System	Sensor Type	1/2.7" Progressive Scan CMOS
	Camera	4 ch
	Video Compression Standard	H.265 /H.264 / MJPEG
	Max. Image Size	1920× 1080
	Frame Rate	50Hz: 25fps (1920× 1080, 1536× 864, 1280 × 720)
	Storage Time	≥30 days
Intelligent Function	Prohibited Goods	41 classes in 15 major types
	Login Method	Face/ Fingerprint/ Password
Operation Desk	Screen Size	21.5", Double Screen,1920×1080
	Camera Image Size	1 ch, 1920 x 1080
General	Consumption	< 1 KVA
	Power	220VAC(±10%) 50±3Hz
	Operating Humidity	10% to 90%(No Condensation)
	Operating Temperature	0°C to 45°C
	Weight	Net:800 kg(With rack and operating table gross weight 1000kg)

\* Stated performance as measured by HIKVISION Imaging Standard Test Piece

## ▪ Available Model

ISD-SC6550D-4CVL	Main machine	X-Ray Intelligent Security Check Machine, 2 monitors, mouse included.
	Exit table/ carrier	0.6 m entrance Flat baggage carrier included 1.2 m exit Flat baggage carrier included

▪ Dimension



Distributed by

**HIKVISION****Headquarters**

No.555 Qianmo Road, Binjiang District,  
Hangzhou 310051, China  
T +86-571-8807-5998  
overseasbusiness@hikvision.com

**Hikvision USA**  
T +1-909-895-0400  
sales.usa@hikvision.com

**Hikvision Australia**  
T +61-2-8599-4233  
salesau@hikvision.com

**Hikvision India**  
T +91-22-28469900  
sales@pramahikvision.com

**Hikvision Canada**  
T +1-866-200-6690  
sales.canada@hikvision.com

**Hikvision Thailand**  
T +662-275-9949  
sales.thailand@hikvision.com

**Hikvision Europe**  
T +31-23-5542770  
sales.eu@hikvision.com

**Hikvision Italy**  
T +39-0438-6902  
info.it@hikvision.com

**Hikvision Brazil**  
T +55 11 3318-0050  
Latam.support@hikvision.com

**Hikvision Turkey**  
T +90 [216]521 7070- 7074  
sales.tr@hikvision.com

**Hikvision Malaysia**  
T +601-7652-2413  
sales.my@hikvision.com

**Hikvision UK & Ireland**  
T +01628-902140  
sales.uk@hikvision.com

**Hikvision South Africa**  
Tel: +27 [10] 0351172  
sale.africa@hikvision.com

**Hikvision France**  
T +33[0]1-85-330-450  
info.fr@hikvision.com

**Hikvision Kazakhstan**  
T +7-727-9730667  
nikia.panfilov@hikvision.ru

**Hikvision Vietnam**  
T +84-974270888  
sales.vt@hikvision.com

**Hikvision UAE**  
T +971-4-4432090  
salesme@hikvision.com

**Hikvision Singapore**  
T +65-6684-4718  
sg@hikvision.com

**Hikvision Spain**  
T +34-91-737-16-55  
info.es@hikvision.com

**Hikvision Tashkent**  
T +99-87-1238-9438  
uzb@hikvision.ru

**Hikvision Hong Kong**  
T +852-2151-1761  
info.hk@hikvision.com

**Hikvision Russia**  
T +7-495-669-67-99  
saleru@hikvision.com

**Hikvision Korea**  
T +82-[0]31-731-8817  
sales.korea@hikvision.com

**Hikvision Poland**  
T +48-22-460-01-50  
info.pl@hikvision.com

**Hikvision Indonesia**  
T +62-21-2933759  
Sales.Indonesia@hikvision.com

**Hikvision Colombia**  
sales.colombia@hikvision.com