

DS-2CD2212-I5-C 1.3MP EXIR Bullet Network Camera



Key features

- Up to 1.3 megapixel (1280 x 960) resolution
- HD real-time video
- WDR & 3D DNR
- EXIR illuminators: up to 50m
- IP66
- PoE
- ONVIF / Open SDK
- Bracket included
- Support people counting and facial recognition application by Hikvision Software license
- Dual Stream
- Motion Detection - 5 levels supported
- Watermark
- Support
- Webservice

DS-2CD2212-I5-C 1.3MP EXIR Bullet Network Camera

Camera	Image Sensor: 1/3" Progressive Scan CMOS Signal System: PAL/NTSC Min. Illumination: 0.01Lux @ (F1.2, AGC ON) ,0 Lux with IR Shutter time: 1/25(1/30) s to 1/100,000 s Lens: 12mm@ F2.0, Angle of view: 22° (4mm, 6mm optional) Lens Mount: M12 Day& Night: IR cut filter with auto switch Digital noise reduction: 3D DNR
Compression Standard	Video Compression: H.264/M-JPEG/MPEG4 Bit Rate: 32 Kbps ~ 16 Mbps Dual Stream: Yes
Image	Max. Image Resolution: 1280x960 Frame Rate: 50 Hz: 25 fps (1280 × 960), 25 fps (1280 x 720) 60 Hz: 30 fps (1280 × 960), 30 fps (1280 x 720) Image Settings: Saturation, brightness, contrast adjustable through client software or web browser Backlight compensation: Yes, zone optional BLC: Yes, zone configurable
Network	Network Storage: NAS Alarm Trigger: Motion detection, Tampering alarm Protocols: TCP/ IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP, PPPoE,NTP,UPnP,SMTP,SNMP,IGMP,802.1X,QoS,IPv6,Bonjour(SIP optional) Security: User authentication, watermark System Compatibility: ONVIF, PSIA, CGI
Interface	Communication Interface: 1 RJ45 10M / 100M ethernet interface
General	Operating Conditions: -30 °C ~ 60 °C (-22 °F ~ 140 °F) Humidity 95% or less (non-condensing) Power Supply: 12 VDC ± 10%, PoE (802.3af/at) Power Consumption: Max. 7 W (Max. 9 W with IR cut filter on) Weather Proof: IP66 IR Range: Up to 50m Dimensions: 105×104.8×263.1mm (4.13" × 4.13" × 10.38") Weight: 700g (1.5 lbs)

DS-2CD2212-I5-C 1.3MP EXIR Bullet Network Camera

Dimensions

