



The second secon

As Simple as That

Ultimate Visual Experience without Distortion

- Apply to standard widescreen monitors with a 16:9 aspect ratio
- No distortion during the video preview or playback







- Other 5 MP (16 : 9) camera 2880 × 1620

- Hikvision 3K camera with ColorVu 2960 × 1665

More Visual Information with High Resolution

• More detailed information can be found in a high-quality, crisp image

Ultra Clear Imaging Even in Darkness

• Ensure clear, colorful imaging in low-light environments



Image taken by DF3T cameras 2 MP







3K Products Showcase





KF3T(-E)

DS-2CE10KF3T(-E) DS-2CE12KF3T(-E) DS-2CE72KF3T(-E)

- 24/7 color imaging with F1.0 aperture
- 0.0003 lux
- Warm light, WL 20/40m
- **130 dB WDR**, 3D DNR
- PoC (-E)







KF3T-PIRXO

DS-2CE12KF3T-PIRXO DS-2CE72KF3T-PIRXO

- 24/7 color imaging with F1.0 aperture
- 0.0003 lux
- Live guard
- Audio customization
- PIR detection
- 130 dB WDR, 3D DNR

Recommended DVRs DVRs with AcuSense

iDS-7204HUHI-M1/**P(C)**

iDS-7208HUHI-M2/**P (C)**

iDS-7216HUHI-M2/**P(C)**





3K @ 12 fps

iDS-7204HUHI-M1(2)/**S (C)** iDS-7208HUHI-M1(2)/S (C)

iDS-7216HUHI-M2/**S (E)**

iDS-7204HUHI-M1(2)/FA (C) iDS-7208HUHI-M1(2)/FA

3K @ 20 fps

iDS-7204HTHI-M1(2)/S (C) iDS-7208HTHI-M2/**\$**

Hikvision Europe

Dirk Storklaan 3 2132 PX Hoofddorp The Netherlands T+31 23 5542770 info.eu@hikvision.com www.hikvision.com







Deep-learning based motion detection on all channels Up to 4-ch deep-learning based perimeter protection



Audio over Coax



Wi-Fi Dongle Connection



Facial Recognition (1-ch) * /FA models

- Face matched / mismatched
- \bullet 500 face images at most stored in the chip with high stability
- Up to 16 face picture libraries



PoC * /P models



Connected with Hik-Connect

- Receive human/vehicle alarms on your mobile phone
- Arm and disarm easily via Hik-Connect app



