

MOBILE ANPR CAMERA

Smart ANPR on the Move





AE-VC583I-ISF



Intelligent ANPR algorithm with high accuracy built in



5 MP sensor with 2560 x 1920p offers high quality video security



Flexible installation and detection coverage suits most vehicles



Environmental protection with 650 nm and 730 nm mixed supplemental lighting




Flexible installation for a host of scenarios

Supporting **vertical** and **horizontal** installation, Hikvision's Mobile ANPR Camera can suit various vehicles and conditions with flexible applications for front or rear capture.

In vertical installations,


the Mobile ANPR Camera can cover 2 lanes with side capture, featuring a lens focal length of 8/12 mm with 5 MP resolution.



Lens	Instillation Angle	Horizontal Field Angle	Stop-line Distance
8mm	≤20°	40°	8m≤ L1 ≤20m
12mm	≤15°	26°	14m≤ L1 ≤32m

In horizontal installations,

the Mobile ANPR Camera can offer front or rear capture over standard 3.5-3.75 m lanes.



Lens	Detection Dis	Detection Distance	
8mm	L1 ≤22m	H1: 16m	
12mm	L2 ≤33m	H2: 15.2m	
16mm	L3 ≤44m	H3: 15.2m	

Accurate recognition in environmentally-friendly ways

Built-in IR covers license plate recognition distances up to 30 m. Accuracy at night is supported by environmentally-friendly, mixed supplemental lighting.

Sufficient and smart storage with fail-safe design

Hikvision's mobile ANPR camera features built-in eMMC storage up to 8 GB with image caching, supporting block lists for intelligent and safer operation.



Hikvision Europe

Dirk Storklaan 3 2132 PX Hoofddorp The Netherlands T+31 23 5542770 info.eu@hikvision.com





