
















QUICK GUIDE FOR ELECTRICIANS

HD Security System for Home and Business

| | Product Model | Key Parameters | Recommended Position | Tips |
|--|-------------------------------|--|-------------------------|--|
| PoE Package     | 2 MP PoE Bullet Camera | DS-2CD1023G0E-I 2 MP IR Fixed Network Bullet Camera; Night vision, Digital WDR | ● Outdoor ● Entrance | For outdoor areas, bullet cameras are easier to see and will deter potential intruders. Dome cameras can be installed indoors as they match easily with interior designs and have large fields of view. |
| | 2 MP PoE Turret Camera | DS-2CD1323G0E-I 2 MP IR Fixed Network Turret Camera; Night vision, Digital WDR | ● Indoor ● Entrance | |
| | 2 MP PoE Dome Camera | DS-2CD1123G0E-I 2 MP IR Fixed Network Dome Camera; Night vision, Digital WDR | ● Indoor | |
| | Up to 8 channel NVR | DS-7604NI-KI/4P(B) DS-7608NI-KI/8P(B) H.265+ video compression 1-ch @ 6 MP / 4-ch @ 1080p decoding capability | | |
| Wi-Fi Package    | IP KIT-WiFi Series | NK42W0H-1T(WD)(D)/EU Four 2 MP bullet Wi-Fi cameras with efficient H.265 One network cable and one HDMI cable 1 TB pre-installed HDD One 4-ch Wi-Fi NVR with decoding up to 4-ch @ 1080p | ● Indoor | Wi-Fi cameras transmit video to the NVR within a limited distance, and thus are recommended mainly for indoor use. |
| | IPC-Wireless Series | DS-2CV2Q21FD-IW(2.8mm)(W)/FUS Wifi, 2MP@30fps, PT, Built-in microphone and speaker | | |
| | IPC-Wireless Series | DS-2CV2U32G1-IDW(1.68mm)(W)/FUS Wifi, 180° Wide Angle, 3MP@20fps, Built-in microphone and speaker | | |
| Turbo HD Package      | Analog HD TVI 4in1 | DS-2CE16D0T-ITF(2.8mm)(C) 2MP, 30m IR, EXIR, 4 in 1 | ● Outdoor ● Entrance | Hikvision's ColorVu technology helps cameras see clearly in color in the dark. Cameras featuring Wide Dynamic Range (WDR) are suited for scenes with bright sunshine outside and dim lights inside, such as entrances. True WDR cameras reveal even more detail. |
| | Analog HD TVI 4in1 | DS-2CE56D0T-IT3F(2.8mm)(C) 2MP, 4in1 | ● Indoor ● Entrance | |
| | Analog HD TVI 4in1 | DS-2CE76D0T-ITMF(2.8mm)(C) 2MP, 4in1, IP67, 30M IR | ● Indoor ● Entrance | |
| | DVR71 Audio | DS-7104HQHI-K1(S) H265 Pro+, 5in1, 4ch 4MP Lite@15fps/ch, 1 SATA, Plastic enclosure, Audio input | | |
| | QE Series Monitor | DS-D5022QE-B EU Standard 21.5" 1080P, HDMI/VGA input, view angle: 170°/160°, 250 cd/m², plastic casing, ERP level A, VESA, base bracket included, 7*24h | | |
| 1-TB HDD | | | | |

Installation Position

-  Indoor
-  Entrance
-  Outdoor




Real security , real convenient

| | Product Model | Key Parameters | Recommended Position |
|------------|------------------------|--|----------------------|
| IP Kit | DS-KIS603-P | 2 MP high resolution WDR,BLC, Wide View H:129 ° V: 75° Standard POE/DC 12V Remote Configuration via Web 2.4 GHz Wi-Fi for both indoor station & door station IP 65 Mifare Card Reading 1 Relay for door lock control | ● Entrance |
| | DS-KIS702(Europe BV) | 2 MP high resolution WDR,BLC, Wide View H:180 ° V: 96° Two -wire deployment 2.4 GHz Wi-Fi for indoor station IP 65 Metal outdoor panel Nametag customization Easy to extend Receives Video Call And Unlocks On Mobile App 2 Relay for door lock control | ● Entrance |
| 2-Wire Kit | DS-KIS703-P(Europe BV) | 2 MP high resolution Two -wire deployment only one power adpater, no need distributor 2.4 GHz Wi-Fi for indoor station IP 65 Receives Video Call And Unlocks On Mobile App 2 Relay for door lock control | ● Entrance |
| | DS-KIS101-P | 2-Wire plug & play, easy, cost-efficient 7-inch TFT screen with 1024*600 resolution 2MP HD colorful camera View in color, even in darkness IP65 water resistant, preventing from water ingress IK7 vandal resistant 2 lock relays, power supply for one electric lock (Up to 12V 1A) | ● Entrance |
| | DS-KIS203 | Hands-free video intercom communication Supports monitoring the door station and the external analog camera Convenient installation and easy operation Remote unlocking | ● Entrance |

Installation Position

-  Indoor
-  Entrance
-  Outdoor




Real security , real convenient

| | Product Model | Key Parameters | Recommended Position |
|-------------------|----------------|---|----------------------|
| Indoor Station | DS-KH6320-WTE1 | 7-inch colorful touch screen with resolution 1024 × 600 Standard PoE Remote unlocking via the client software or the mobile client Views live videos of door stations and linked cameras Supports wireless network | ● Indoor |
| | DS-KH6320-WTE2 | Two-pin wire for power supply and network access 7-inch colorful touch screen with resolution 1024 × 600 Remote unlocking via the client software or the mobile APP Views live videos of door stations and linked cameras Supports wireless network | ● Indoor |
| | DS-KH1200 | 2-Wire plug & play, easy, cost-efficient Receive video call and unlock via indoor station 7-inch TFT screen with 1024*600 resolution | ● Indoor |
| Door Station | DS-KV6113-WPE1 | Support Wifi Support web configuration Nice industry design, IP65 Internal Mifare card reader 2MP HD Camera with IR supplement Standard PoE/ 12 VDC | ● Entrance |
| | DS-KD8003-IME2 | Two-pin wire for power supply and network access Fisheye camera with IR supplement light Access control function Nametag customization Easy to and extend | ● Entrance |
| | DS-KV1101-ME2 | 2-Wire plug & play, easy, cost-efficient 2MP HD colorful camera View in color, even in darkness IP65 water resistant, IK7 vandal resistant 2 lock relays, power supply for one electric lock (Up to 12V 1A) | ● Entrance |
| Power Distributor | DS-KAD706 | 1 RJ-45 Interface, 6 Two-Wire Interface to connect device 1 In interface & 1 out interface Din rail mounting, 24VDC | ● Indoor |

Installation Position

-  Indoor
-  Entrance
-  Outdoor



Intrusion and Video, Refocused

AX PRO Wireless Alarm Kit



64 zone wireless control panel Kit



96 zone wireless control panel Kit

| Product Model | Key Parameters | Recommended Position |
|-------------------|---|----------------------|
| DS-PWA64-Kit-WE | 64 zones Control Panel x1 supports up to 64 inputs and outputs communication channel: Wi-fi, LAN, and GPRS Jamming detection PIRCAM and repeater supported PIR Motion Sensor x1 15m detection range, 30kg Pet immunity Magnet Contact x1 opening status detect Wired terminal for connect third party sensors Keyfob x1 | ● Indoor |
| DS-PWA96-Kit-WE | 96 zones Control Panel x1 supports up to 96 inputs and outputs communication channel: Wi-fi, LAN, and 2 x 3/4G Jamming detection PIRCAM and repeater supported PIR Motion Sensor x1 15m detection range, 30kg Pet immunity Magnet Contact x1 opening status detect Wired terminal for connect third party sensors Keyfob x1 | ● Indoor |
| DS-PDPC12P-EG2-WE | 12m detection range 30kg pet immunity function | ● Indoor |
| DS-PDMCS-EG2-WE | opening status detect | ● Indoor |
| DS-PS1-E-WE | 3 level sound adjustable, up to 110dB Indicates armed/disarmed mode with a built-in LED IP54 | ● Outdoor |
| DS-PS1-I-WE | 3 level sound adjustable, up to 110dB Indicates armed/disarmed mode with a built-in LED | ● Indoor |
| DS-PD-SMK-S-WE | 10 years battery life | ● Indoor |

Optional Peripherals



PIRCAM



Slim Magnet Contact



External Siren



Internal Siren



Smoke Sensor

Installation Position




Indoor



Entrance



Outdoor



Switch & Network Cable



4 PORTS POE Switch

| Product Model | Key Parameters | Recommended Position |
|-----------------|--|----------------------|
| DS-3E0105P-E(B) | 4 * 10/100M RJ45 PoE ports, 1*10/100M RJ45 uplink port, 802.3af/at, PoE power budget 60W, max. 250m transmission | ● Indoor |
| DS-3E0310P-E/M | 8 10/100M RJ45 PoE ports, 2 Gigabit RJ45 uplink ports, 802.3af/at, PoE power budget 60W, max. 300m transmission | ● Indoor |
| DS-3E0505-E | Unmanaged, 5 Gigabit RJ45 ports, Desktop Steel Case | ● Indoor |
| DS-1LN5E-E/E | UTP CAT 5E, 305 meters, Core diameter: 0.45mm, Pure copper, gray, CPR Eca level | ● Indoor |



8 PORTS POE Switch



5 Gigabit RJ45 ports



Cat 5 Network Cable

Installation Position




Indoor



Entrance



Outdoor



See the world in a new way



Thermography Camera

| Product Model | Key Parameters | Recommended Position | Tips |
|-----------------|---|----------------------|--|
| DS-2TP21-6AVF/W | 160 × 120 resolution (thermal), and 8 MP resolution (optical) DDE, 3D DNR, and adaptive AGC 640 × 480 resolution 3.5" LCD touch display Up to 5 hours continuous running | Handheld | Indoor & Outdoor use: Electrical & Building inspection. Identify abnormal temperature in electrical cabinet. Tools who can help to see default on building insulation. Saving energy. With the manual focus you will always get the sharpest picture you need. The TP21 also include bispctrum len (thermal + visible) and thus fusion mode. The advantage of both technology. |



Thermography Camera

| | | | |
|---------------|---|----------|--|
| DS-2TP31-3AUF | 160 × 120 resolution 320 × 240 resolution 2.4" LCD display Built-in rechargeable Li-ion battery Up to 8 hours continuous running | Handheld | Indoor & Outdoor use: Most Affordable thermal camera in the market. Key advantages are the ease of use and a high quality picture. The fastest tools to identify electrical default. |
|---------------|---|----------|--|

QUICK GUIDE FOR ELECTRICIANS

Hikvision Europe

Dirk Storklaan 3
2132 PX Hoofddorp
The Netherlands
T +31 23 5542770
info.eu@hikvision.com

Hikvision France

6 rue Paul Cézanne,
93360 Neuilly-Plaisance
France
T +33 (0)1 85330450
info.fr@hikvision.com

Hikvision Poland

The Park, Office Building A
Krakowiaków 50
02-255 Warsaw, Poland
T +48 22 4600150
info.pl@hikvision.com

Hikvision Czech

BETA Building, Vyskocilova
1481/4, Prague 4
Czech Republic
T +42 29 6182640
info.cz@hikvision.com

Hikvision Germany

Werner-Heisenberg Str. 2b
63263 Neu-Isenburg,
Germany
T +49 69 401507290
sales.dach@hikvision.com

Hikvision Romania

Splaiul Independentei street
291-293, Riverside Tower, 12th
floor, 6th district,
Bucharest, Romania
T +31235542770/988
marketing.ro@hikvision.com

Hikvision Belgium

Neringenweg 44,
3001 Leuven, Belgium
T +31 23 5542770
info.bnl@hikvision.com

Hikvision Hungary

Budapest, Reichl Kálmán u. 8,
1031, Hungary
T +36 1 323 7650
info.hu@hikvision.com

