

DS-D4237FI-CAF



- For video wall composition with superior luminance uniformity
- High brightness provides vivid images in a range of lighting conditions
- Superior contrast ratio
- Broadcast grey processing gives more image details
- Superior brightness and color uniformity maintains smooth and complete image quality
- Ultra high refresh rate
- Nanosecond response time
- Long service life
- Wide viewing angle
- High aperture ratio and wide color gamut coverage
- Low heating and superior cooling system ensures high reliability and environmental protection







▪ Specification

Cabinet	
Pixel Configuration	SMD 3-in-1 LED
Pixel Pitch Category	P3.75
Pixel Pitch	3.75 mm
Modules Component	2 x 2
Dimensions (W × H × D)	480 mm x 540mm x 54 mm (18.90" × 21.26" × 2.12")
Resolution	128 x 144
Area	0.2592 m ²
Weight	6.95kg (14.33lb)
Pixel Density	71111 dots/m ²
Lamp Board Housing	no housing
Cabinet Material	Die-cast aluminum
Maintenance Method	Front maintenance for all components
Cabinet Flatness	≤0.2 mm
Protection Level	Front protection level IP5X
Display	
White Balance Brightness	600 cd/m ²
Color Temperature	3000 K to 10000 K adjustable
Viewing Angle	Horizontal 160°, vertical 160°
Contrast Ratio	≥ 5000:1
Color Uniformity	≤ ± 0.003Cx, Cy
Brightness Uniformity	≥ 97%
Processing Performance	
Driving Method	Constant current driving
Frame Frequency	60 Hz
Refresh Rate	3840 Hz
Grey Level	16 bit
Display Color	281 trillion
Power	
Power Supply	110~220 VAC ± 15%
Max. Consumption	≤ 570 W/m ²
Average Consumption	≤ 170 W/m ²
Working Environment	
Working Temperature	-10-45 °C
Working Humidity	10%~90%RH
Storage Humidity	10%~90%RH
Storage Temperature	-20~60 °C
General	
Gross Weight	40 Kg (88.2 lb)
Package Dimension (W × H × D)	598mm × 467mm × 763mm (23.54" × 18.38" × 30.04") 4in1
Lifespan	Lamp 100,000 hours

▪ Available Model

DS-D4237FI-CAF, 二代480*540/箱体,海康系统,

▪ Accessory**▪ Optional**

DS-D42C08-H LED Controll Card	DS-D42C16-H LED Control Card
	
	



Distributed by

**HIKVISION®****Headquarters**

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
overseasbusiness@hikvision.com

Hikvision USA
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Australia
T +61-2-8599-4233
salesau@hikvision.com

Hikvision India
T +91-22-28469900
sales@pramahikvision.com

Hikvision Canada
T +1-866-200-6690
sales.canada@hikvision.com

Hikvision Thailand
T +662-275-9949
sales.thailand@hikvision.com

Hikvision Europe
T +31-23-5542770
sales.eu@hikvision.com

Hikvision Italy
T +39-0438-6902
info.it@hikvision.com

Hikvision Brazil
T +55 11 3318-0050
Latam.support@hikvision.com

Hikvision Turkey
T +90 [216]521 7070- 7074
sales.tr@hikvision.com

Hikvision Malaysia
T +601-7652-2413
sales.my@hikvision.com

Hikvision UK & Ireland
T +01628-902140
sales.uk@hikvision.com

Hikvision South Africa
Tel: +27 (10) 0351172
sale.africa@hikvision.com

Hikvision France
T +33(0)1-85-330-450
info.fr@hikvision.com

Hikvision Kazakhstan
T +7-727-9730667
nikia.panfilov@hikvision.ru

Hikvision Vietnam
T +84-974270888
sales.vt@hikvision.com

Hikvision UAE
T +971-4-4432090
salesme@hikvision.com

Hikvision Singapore
T +65-6684-4718
sg@hikvision.com

Hikvision Spain
T +34-91-737-16-55
info.es@hikvision.com

Hikvision Tashkent
T +99-87-1238-9438
uzb@hikvision.ru

Hikvision Hong Kong
T +852-2151-1761
info.hk@hikvision.com

Hikvision Russia
T +7-495-669-67-99
saleru@hikvision.com

Hikvision Korea
T +82-(0)31-731-8817
sales.korea@hikvision.com

Hikvision Poland
T +48-22-460-01-50
info.pl@hikvision.com

Hikvision Indonesia
T +62-21-2933759
Sales.Indonesia@hikvision.com

Hikvision Colombia
sales.colombia@hikvision.com