

DS-IE1032-03U/BA(A7)



- Behavior Analysis Server can detect the specific behaviors of individuals and groups in the perimeter, street, densely populated areas, indoor and other places, and provide professional video intelligent analysis applications.
- Real-time detection and alarming of events such as line crossing, area intrusion, region entrance/exiting, loitering, parking, unattended baggage or object removal.
- Real-time detection and alarming of people density, real-time people counting statistics and people counting statistics.
- Real-time detection and alarming of events such as getting up, key person getting up, climbing, absence or sleep on duty, abnormal number of people, overstaying, sudden change of sound intensity, regional overstaying, physical conflict, standing up, sitting, people counting or uniform detection.
- Real-time detection and alarming of events such as fast moving, physical conflict, people gathering, falling down or unattended baggage detection.
- AI open platform algorithm detection: Real-time detection and alarm are performed on the object detection, single tag classification, multi tags classification, multi attributes classification, and mix (1 for detection and 3 for classification) algorithm events trained by the open platform.

▪ Specification


Model		DS-IE1032-03U/BA(A7)
Product Performance	Algorithm Type	Indoor, Perimeter, Trend, Street
	Protocol Type	ISAPI
	Cluster Capacity	5
	Virtual Machine Storage	100,000 alarm messages & images
	Data Type	Behavior (Video)
	Video Analysis Capacity	64 channels (up to 8 MP, 1080 p is recommend)
	AI	Data Type
Picture Resolution Requirement		32 × 32 to 4096 × 4096 Picture format: JPEG (JPG), TIF, BMP, PNG, gif (static); Picture size: no more than 10 MB.
Supported Algorithm Type		Object detection, single tag classification, multiple tags classification, multiple attributes classification, mix.
Video Frame Rate Requirement		H.264 video stream, H.265 video stream (HIKVISION), Resolution: 2 MP-8 MP (4096 × 2160); Frame rate: 12/s to 30/s; Stream packaging format supported by video importing: ps, ts, mp4, avi, mbf, asf, h.264, h.265 (HIKVISION), svac, hik es, Dahua es, Tiandi platform es; Video size: no more than 100 GB in total, and no more than 10 GB per video.
Picture Analysis Performance		Performance specification (2 MP resolution with less than 10 targets in the scene): Object detection, single tag classification, multiple tags classification, multiple attributes classification, mix (1 for detection, 3 for classification) and 256 pictures per second.
Video Analysis Performance		Performance specification (2 MP to 8 MP (4096 × 2160): resolution-insensitive; tracking 64 targets in scene at the same time and outputting one target per second Object detection, single tag classification, multiple tags classification, multiple attributes classification, mix (1 for detection, 3 for classification) and 64 channels video analysis.
Usage		AIMMS 1.6.0
Hardware Specifications	Picture rotation analysis	Performance specification (2 MP resolution with less than 10 targets in the scene): Object detection, single tag classification, multiple tags classification, multiple attributes classification, mix (1 for detection, 3 for classification). Support up to 16 tasks of scheduled capture analysis (each capture task can link to 16 channels rotation analysis, capture interval can be 1 to 3600 seconds).
	CPU	Hygon 3185 (8 Cores, 16 Threads, 3 GHz)
	Memory	16 GB DDR4 RDIMM
	HDD Interface	M.2

	HDD Capacity	240 GB SSD × 2
	Network Interface	1000 M network interface × 4
	USB 3.0 (External)	6
	VGA Interface	1
Physical and Environmental Parameters	Rated Power Consumption	550 W × 2
	Package Dimensions	830 mm (W) × 830 mm (D) × 222 mm (H)
	Gross Weight (With Package)	21 kg

▪ Available Model

DS-IE1032-03U/BA(A7)

▪ Dimension



Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
www.hikvision.com



Follow us on social media to get the latest product and solution information.

