

HikCentral-E-Industrial-HW



- Expand and optimize application performance
- Automate systems management with OpenManage
- Rely on Hikvision with built-in security
- Support HikCentral Enterprise Industrial





Specification

Model		HikCentral-E-Industrial-HW
Product	Platform	HildControl Enterprise Industrial
Description	Version	HikCentral Enterprise Industrial
Hardware Specification	CPU	Two Intel® Xeon®SP (4208 × 2)
	Memory	64 GB DDR4 DIMM
	Hard Disk	1 TB 7.2 K SATA × 2 (RAID 1) + 1 TB 7.2 K SATA × 2 (RAID 1)
		Form factor: Rack (2U) Chassis depth: 715.5 mm
	Device	715.5 × 482 × 86.8 mm (28.2 × 19.0 × 3.4 inch)
	Dimensions	With package: 960 × 610 × 295 mm (37.8 × 24.0× 11.6 inch)
	Storage Controller	PERC H330
	Power Supply	495 W (1+1)
	Bezel	Security bezel
	Embedded Management	iDRAC9, Enterprise
	OpenManage ™ Software	OpenManage Enterprise OpenManage Mobile
		OpenManage Essentials OpenManage Power Center
	Integrations	Integrations: Microsoft® System Center, VMware® vCenter™, BMC Software Connections: Nagios & Nagios XI, Oracle Enterprise Manager, HP Operations Manager, IBM
	and Connections	Tivoli Netcool/OMNIbus,IBM Tivoli® Network Manager,CA Network and Systems Management
	Security	TPM 1.2/2.0 optional, cryptographically signed firmware, Secure Boot, System Lockdown, Secure Erase
	I/O & Ports	Network daughter card options: 4 × 1GE
		Front ports: Video, 2 × USB 2.0
		Rear ports: Video, serial, 2 × USB 3.0
		Video card: VGA × 1
	Supported	
	Operating Systems	Not configured by default
Physical and Environment al Parameter	Working Temperature	+5 °C to +35 °C (41 °F to 95 °F)
	Working Humidity	8 % to 90 % (without condensation)
	Storing Temperature	-40 °C to +70 °C (-40 °F to 158 °F)
	Net Weight (Without Package)	26.5 kg (58.4 lb.)



Gross Weight	
(With	35.1 kg (77.4 lb.)
Package)	

Available Model

HikCentral-E-Industrial-HW(O-STD),



Distributed by

HIKVISION°

Headquarters

No.555 Qianmo Road, Binjiang District, Hangzhou 310051, China T +86-571-8807-5998 overseasbusiness@hikvision.com

Hikvision USA T+1-909-895-0400 sales.usa@hikvision.com

Hikvision Australia T+61-2-8599-4233 salesau@hikvision.com

Hikvision India T+91-22-28469900 sales@pramahikvision.com

Hikvision Canada T+1-866-200-6690 sales.canada@hikvision.com

Hikvision Thailand T+662-275-9949 sales.thailand@hikvision.com Hikvision Europe T +31-23-5542770 sales.eu@hikvision.com

Hikvision Italy T +39-0438-6902 info.it@hikvision.com

Hikvision Brazil T +55 11 3318-0050 Latam.support@hikvision.com

Hikvision Turkey T +90 (216)521 7070- 7074 sales.tr@hikvision.com

Hikvision Malaysia T+601-7652-2413 sales.my@hikvision.com Hikvision UK & Ireland T +01628-902140 sales.uk@hikvision.com

Hikvision South Africa Tel: +27 (10) 0351172 sale.africa@hikvision.com

Hikvision France T +33(0)1-85-330-450 info.fr@hikvision.com

Hikvision Kazakhstan T +7-727-9730667 nikia.panfilov@hikvision.ru

Hikvision Vietnam T +84-974270888 sales.vt@hikvision.com Hikvision UAE T +971-4-4432090 salesme@hikvision.com

Hikvision Singapore T +65-6684-4718 sg@hikvision.com

Hikvision Spain T +34-91-737-16-55 info.es@hikvision.com

Hikvision Tashkent T +99-87-1238-9438 uzb@hikvision.ru

Hikvision Hong Kong T +852-2151-1761 info.hk@hikvision.com **Hikvision Russia** T +7-495-669-67-99 saleru@hikvision.com

Hikvision Korea T +82-{0}31-731-8817 sales.korea@hikvision.com

Hikvision Poland T +48-22-460-01-50 info.pl@hikvision.com

Hikvision Indonesia T+62-21-2933759 Sales.Indonesia@hikvision.com

Hikvision Colombia sales.colombia@hikvision.com