

DS-D4225FO-BGF Outdoor Fixed LED Displays



- Widely applied in outdoor permanent advertising scenes
- Thin and light cabinet with the die-casting aluminum design
- IP 65 rating for both the front and back panels
- Free of air conditioners with multiple ventilation modes working together inside the cabinets
- front maintenance
- Standing, wall mount, and lifting
- Customizable as stadium LED screens



▪ Specification

Cabinet	
Pixel Configuration	SMD 3-IN-1 LED
Pixel Pitch Category	P2.5
Pixel Pitch	2.5 mm
Lamp Dimensions	1.4 × 1.5 mm
Modules Component	2 × 2
Dimensions (W × H × D)	500 mm × 500 mm × 85.1 mm (19.7" × 19.7" × 3.35")
Resolution	200 × 200
Area	0.25 m ²
Weight	8.25 Kg (18.2 lb)
Pixel Density	160000 dots/m ²
Lamp Board Housing	With housing
Cabinet Material	aluminum
Maintenance Method	Front maintenance
Cabinet Flatness	0.2 mm
Protection Level	IP65 both front and back
Key Material	
Lamp Encapsulation	Nationstar 1415
Driver IC	ICN2053
Control System	DS-D42C04-N
Display	
White Balance Brightness	5000 cd/m ²
Color Temperature	2000 K to 9300 K adjustable
Viewing Angle	Horizontal 140°, vertical 140°
Contrast Ratio	≥ 5000:1
Color Uniformity	≤ ± 0.003Cx, Cy
Brightness Uniformity	≥ 97%
Processing Performance	
Driving Method	Constant current driving
Frame Frequency	60 Hz
Refresh Rate	Up to 3840 Hz
Grey Level	Up to 16 bit
Display Color	281 trillion
Power	
Power Supply	110~220 VAC ± 15%
Max. Consumption	≤ 750 W/m ²
Average Consumption	≤ 250 W/m ²
Working Environment	
Working Temperature	-10~55 °C
Working Humidity	10%~80%RH
Storage Humidity	10%~85%RH
Storage Temperature	-20~60 °C

General

Gross Weight	100 Kg (220 lb) /8 in 1
Package Dimension (W × H × D)	1260 mm × 610 mm × 750 mm (49.6" × 24.0" ×29.53")
Lifespan	Lamp 100,000 hours

▪ Available Model

DS-D4225FO-BGF, 户外2.5mm, 500*500mm/箱体, 5%备件,

▪ Accessory**▪ Optional****DS-D42C04-N**



Distributed by

**HIKVISION®****Headquarters**

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
overseasbusiness@hikvision.com

Hikvision USA
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Australia
T +61-2-8599-4233
salesau@hikvision.com

Hikvision India
T +91-22-28469900
sales@pramahikvision.com

Hikvision Canada
T +1-866-200-6690
sales.canada@hikvision.com

Hikvision Thailand
T +662-275-9949
sales.thailand@hikvision.com

Hikvision Europe
T +31-23-5542770
sales.eu@hikvision.com

Hikvision Italy
T +39-0438-6902
info.it@hikvision.com

Hikvision Brazil
T +55 11 3318-0050
Latam.support@hikvision.com

Hikvision Turkey
T +90 (216)521 7070- 7074
sales.tr@hikvision.com

Hikvision Malaysia
T +601-7652-2413
sales.my@hikvision.com

Hikvision UK & Ireland
T +01628-902140
sales.uk@hikvision.com

Hikvision South Africa
Tel: +27 (10) 0351172
sale.africa@hikvision.com

Hikvision France
T +33(0)1-85-330-450
info.fr@hikvision.com

Hikvision Kazakhstan
T +7-727-9730667
nikia.panfilov@hikvision.ru

Hikvision Vietnam
T +84-974270888
sales.vt@hikvision.com

Hikvision UAE
T +971-4-4432090
salesme@hikvision.com

Hikvision Singapore
T +65-6684-4718
sg@hikvision.com

Hikvision Spain
T +34-91-737-16-55
info.es@hikvision.com

Hikvision Tashkent
T +99-87-1238-9438
uzb@hikvision.ru

Hikvision Hong Kong
T +852-2151-1761
info.hk@hikvision.com

Hikvision Russia
T +7-495-669-67-99
saleru@hikvision.com

Hikvision Korea
T +82-(0)31-731-8817
sales.korea@hikvision.com

Hikvision Poland
T +48-22-460-01-50
info.pl@hikvision.com

Hikvision Indonesia
T +62-21-2933759
Sales.Indonesia@hikvision.com

Hikvision Colombia
sales.colombia@hikvision.com