

## DS-PEA1-21 Panic Alarm Station

DS-PEA1 series panic alarm station is designed with 2 MP HD camera, 2MP HD IR camera and dual network ports. It supports two-way audio. It helps to realize alarm aid the first time and provides more efficient service for building social stability. It is mainly applied to classroom, corridor, laboratory, dormitory, office, hospital, ward and so on.

9	HIKH	rsitil V	0	DN
	-			
	60			
		9		

## Key Features

- One-touch emergency calling
- High quality imaging with 2 MP built-in camera
- Real-time security via sound and voice detection
- Supports broadcasting
- Supports dual net ports
- Built-in SD slot supports MicroSD / SDHC / SDXC up to 128 GB
- Supports siren and audio expansion





<ul> <li>Specification</li> <li>Software features</li> </ul>			
Wired network	10 M/100 M Self-adaptive Ethernet port		
Hardware features			
Tamper-Proof	tamper alarm		
Netowrk interface	1RJ45,10 M/100 M/1000 M self adaptive		
	1-ch Built-in Omnidirectional Microphone, Pickup Distance: 5 m		
Audio interface	1-ch 3.5 mm Audio Interface for External Audio Input		
PSTN	1		
Bus	RS-485 1, Half-duplex		
SD card	Standard Micro SD card Slot, Supports Micro SD/SDHC/SDXC Card, Max. 128G		
Video			
Frame rate	25fps		
	Horizontal: 128°		
Field angle	Vertical: 75°		
5	Diagonal: 147°		
Day/night switch mode	IR Cut Filter		
Electrical characteristics			
Power supply	12VDC		
Operation temperature	-40 °C to +60 °C (-40 °F to 140 °F)		
Power consumption	≤ 24 W		
Operation humidity	10% to 90%		
General			
Dimension(WxHxD)	218 mm × 128 mm × 58 mm (8.58" × 5.04" × 2.28")		
Installation method	Wall Mounting		
Audio			
Sound pressure	110dB, Sound Can be Configured Separately		
	1-ch Built-in Omnidirectional Microphone, Pickup Distance: 5 m		
Audio input	1-ch 3.5 mm Audio Interface for External Audio Input		
	1-ch 3 W Build-in Loudspeaker		
Audio output	1-ch 3.5 mm Audio Interface for External Audio Output		
Intercom	1-ch Built-in Omnidirectional Microphone, Pickup Distance: 5 m		
Audio compression code rate	16Kbps,64Kbps		
Device management			
Alarm input	2		
Camera	2 MP HD IR Camera		
Alarm output	2		
Report method			
Protocol	TCP/IP, RTSP, HIK-SIP,ONVIF		



## • Available Model DS-PEA1-21, DS-PEA-SG

Distributed by

 $\square$ 

**HIKVISION**<sup>®</sup>

## Headquarters

No.555 Qianmo Road, Binjiang District, Hangzhou 310051, China T +86-571-8807-5998 overseasbusiness@hikvision.com

Hikvision USA T +1-909-895-0400 sales.usa@hikvision.com

Hikvision Australia T +61-2-8599-4233 salesau@hikvision.com

Hikvision India T +91-22-28469900 sales@pramahikvision.com

Hikvision Canada T +1-866-200-6690 sales.canada@hikvision.com

Hikvision Thailand T +662-275-9949 sales.thailand@hikvision.com Hikvision Europe T +31-23-5542770 sales.eu@hikvision.com

Hikvision Italy T +39-0438-6902 info.it@hikvision.com

Hikvision Brazil T +55 11 3318-0050 Latam.support@hikvision.com

Hikvision Turkey T +90 (216)521 7070- 7074 sales.tr@hikvision.com

Hikvision Malaysia T +601-7652-2413 sales.my@hikvision.com Hikvision UK & Ireland T +01628-902140 sales.uk@hikvision.com

Hikvision South Africa Tel: +27 (10) 0351172 sale.africa@hikvision.com

Hikvision France T +33(0)1-85-330-450 info.fr@hikvision.com

Hikvision Kazakhstan T +7-727-9730667 nikia.panfilov@hikvision.ru

Hikvision Vietnam T +84-974270888 sales.vt@hikvision.com Hikvision UAE T +971-4-4432090 salesme@hikvision.com

Hikvision Singapore T +65-6684-4718 sg@hikvision.com

Hikvision Spain T +34-91-737-16-55

info.es@hikvision.com Hikvision Tashkent T +99-87-1238-9438 uzb@hikvision.ru

Hikvision Hong Kong T +852-2151-1761 info.hk@hikvision.com Hikvision Russia T +7-495-669-67-99 saleru@hikvision.com

Hikvision Korea T +82-(0)31-731-8817 sales.korea@hikvision.com

Hikvision Poland T +48-22-460-01-50 info.pl@hikvision.com

Hikvision Indonesia T +62-21-2933759 Sales.Indonesia@hikvision.com

Hikvision Colombia sales.colombia@hikvision.com

© Hikvision Digital Technology Co., Ltd. 2020 | Data subject to change without notice |