



WAREHOUSE PROTECTION



HeatPro Thermal Camera Solutions for Warehouse Industry Scenarios

Security from within and without is a major concern for warehouse managers and employees. From preventing break-ins to detecting fire risks, what are the best options for reacting immediately to prevent damage and loss? Now, Hikvision's HeatPro series of advanced security products offers a professional solution to keep any warehouse safe and secure.

Common Industry Concerns



STORAGE & PACKAGING AREAS

Requirements:

- Protecting goods from risk of fire
- Visualized monitoring in storage areas
- Exterior protections




DISPATCH CENTERS

Requirements:

- Protecting goods from risk of fire
- Visualized tracking of goods
- Employee safety

HEATPRO SERIES ADVANCED FEATURES



24 HOUR BI-SPECTRUM LIVE VIEW

- 4 MP HD Optical channels
- Thermal channel with target colouration
- On-screen, real-time temperature information



TEMPERATURE & FIRE DETECTION


- Monitoring temperature anomalies and alarm triggering
- Multiple configurable temperature anomaly rules



ACCURATE PERIMETER DEFENSE

- Detecting intrusions & line crossing events
- Reduced false alarms with human/vehicle classification
- Automated strobe light and audible alerts


MULTI-STAGE FIRE DETECTION SOLUTIONS



APPLICATION SCENARIOS



PARKING AREAS
Human/vehicle classification for perimeter protection



EXTERNAL SURROUNDINGS
Automated strobe light and audio alerts



Perimeter Defense
Thermal HeatPro cameras cover large areas and detect intrusions & line-crossing events.





STORAGE AREAS
Temperature anomaly detection



Real-Time Fire Detection
Thermal HeatPro series cameras large FOV provides wide coverage throughout the warehouse.

FLEXIBLE SOLUTIONS




Fundamental Protections

Connected to an NVR, HeatPro cameras provide multiple powerful security protections in small warehouses.


Large-Scale Deployment

HeatPro cameras can be deployed on a large scale for more complex projects – such as chain stores and industrial parks – with centralized management.

VCA PERFORMANCE



Recommended human detection distance



0.5m (1.6ft)

Temperature measurement distance
0.25 sq.m. (2.69 sq. ft.)

0.5m (1.6ft)

MODEL SELECTION

HeatPro



TD1228(T) Turret Camera
TD2628(T) Bullet Camera

Models	FOV (H x V)	Key Features
DS-2TD1228-2/QA	90.0° × 65.4°	Resolution: 256 x 192 Perimeter Protection: Line crossing / Intrusion / Region entrance / Region exiting Fire Prevention: temperature measurement range -20°C~150°C with an accuracy of ±8°C Updated Algorithm: better performance of false alarm filtering
DS-2TD1228-3/QA	50.0° × 37.3°	
DS-2TD2628-3/QA	50.0° × 37.3°	
DS-2TD2628-7/QA	24.9° × 18.7°	
DS-2TD2628-10/QA	18.0° × 13.5°	
DS-2TD1228T-2/QA	90.0° × 65.4°	Resolution: 256 x 192 Perimeter Protection: Line crossing / Intrusion / Region entrance / Region exiting Fire Prevention: temperature measurement range -20°C~550°C with higher accuracy of ±2°C Updated Algorithm: better performance of false alarm filtering
DS-2TD1228T-3/QA	50.0° × 37.3°	
DS-2TD2628T-3/QA	50.0° × 37.3°	
DS-2TD2628T-7/QA	24.9° × 18.7°	



TECHNICAL SUPPORT

Hikvision Canada Toll-free: +1 855-655-9888

Email: techsupport.ca@hikvision.com

OFFICES

Hikvision Canada Inc. (Montreal)

8555 Rte Transcanadienne, Suite 200

Saint-Laurent, QC H4S 1Z6

Hikvision Canada Inc. (Toronto)

2355 Skymark Ave., Suite 300

Mississauga, ON L4W 4Y6

Hikvision Canada Inc. (Vancouver)

4400 Dominion St., Suite 400

Burnaby, BC V5G 4L7

Email: sales.canada@hikvision.com