

LED POSTER DISPLAY

HIKVISION



EASY SEAMLESS SPLICING TO FORM A LARGE SCREEN

SUPERIOR IMAGE/VIDEO QUALITY & EYE-CATCHING BRIGHTNESS

SUPER THIN AT 2.68IN, SUPER LIGHT AT 29-32KG

SUPPORTS FLEXIBLE MOUNTING SOLUTIONS



*Floor stands sold separately

LEARN MORE



UNEVEN SPLICING CAPABILITY



10 PIECE LED WALL MOUNTING SOLUTIONS

FLEXIBLE DEPLOYMENT

Support a max. of 10 pieces of self-splicing with HDMI cables

CONVENIENT ADVERTISING

Manage advertising programs with HikCentral FocSign for scheduled release, multiple templates, etc.

LED POSTER DISPLAY

HIKVISION®



HOIST MOUNTING

Model	DS-D4212MI-070H(B) P1.2 Ultra Slim LED poster	DS-D4215MI-070H(B) P1.5 Ultra Slim LED poster	DS-D4218MI-070H(B) P1.8 Ultra Slim LED poster	
Image				
Cabinet	Pixel Configuration	SMD Triad LED	SMD Triad LED	SMD Triad LED
	Pixel Pitch Category	P1.2	P1.5	P1.8
	Pixel Pitch	1.25 mm	1.5625 mm	1.875 mm
	Modules Component	Cabinet x 5, single cabinet (2 x 4)	Cabinet x 5, single cabinet (2 x 4)	Cabinet x 5, single cabinet (2 x 4)
	Dimensions (W x H x D)	613 x 1695.5 x 68.1 mm (24.1 x 66.8 x 2.7 inch)	613 x 1695.5 x 68.1 mm (24.1 x 66.8 x 2.7 inch)	613 x 1695.5 x 68.1 mm (24.1 x 66.8 x 2.7 inch)
	Resolution	480 x 1350	384 x 1080	320 x 900
	Area	1.0125 m ²	1.0125 m ²	1.0125 m ²
	Weight	32.5 kg (71.65 lb.)	29 kg (64.0 lb.)	29 kg (64.0 lb.)
	Pixel Density	64000 dots/m ²	409600 dots/m ²	284444 dots/m ²
	Lamp Board Housing	Without housing, glue potting	Without housing, glue potting	Without housing, glue potting
Cabinet Material	Aluminum alloy	Aluminum alloy	Aluminum alloy	
Maintenance Method	Front maintenance for cabinet, and rear maintenance for system backpack	Front maintenance for cabinet, and rear maintenance for system backpack	Front maintenance for cabinet, and rear maintenance for system backpack	
Display	White Balance Brightness	600 cd/m ²	600 cd/m ²	600 cd/m ²
	Colour Temperature	3000 to 10000 K adjustable	3000 to 10000 K adjustable	3000 to 10000 K adjustable
	Viewing Angle	Horizontal 160°, vertical 160°	Horizontal 160°, vertical 160°	Horizontal 160°, vertical 160°
	Contrast Ratio	≥ 3000:1	≥ 3000:1	≥ 3000:1
	Colour Uniformity	± 0.003 Cx, Cy	± 0.003 Cx, Cy	± 0.003 Cx, Cy
Brightness Uniformity	≥ 97%	≥ 97%	≥ 97%	

ALL-IN-ONE DESIGN

- Built-in Digital Signage player and storage allows remote management with Focsign software
- Built-in LED controller
- Ultra fine Pixel Pitch at P1.2, P1.5, and P1.8

- Patent pending Hikvision GOB (Glue On Board) Craft Surface Colloid Layer for better protection (waterproof, moisture proof, anti-corrosion, dust-proof, anti-static, anti-oxidation)



Build-in LED Controller



Central Advertisement Management



Self Splicing



GOB Technology



Flexible Deployment