

NETWORK SWITCHES

Switches Made Simple

Smart managed switches are developed by Hikvision, featuring easy management and maintenance. You can easily deploy, monitor and expand your security system anytime and anywhere with our software platforms. You can view the network topology, monitor the health of the network and receive device alarms in real time, which greatly reduces the cost of network operation and maintenance.



300-Meter Transmission

300-Meter Transmission
With the Extended Mode on, the transmission distance can be increased to 300 meters. Even when the transmission distance reaches 300 meters, the video is still smooth and stable.



VIP Port Transmission Priority

VIP ports enjoy higher priority and more stable transmission when the switch is overloaded. It is recommended to connect cameras in critical areas to VIP ports.



PoE Watchdog

The PoE watchdog can detect the status of connected devices and restart offline cameras automatically, saving manpower and maintenance costs.



Easy Port Isolation

The port isolation function can virtually isolate the ports from each other, preventing: data from leaking among ports and a broadcasting storm in case of mistaken connection.



Higher PoE Power Budget

Hikvision PoE switches support IEEE 802.3 af/at/bt PoE standard, and can flexibly match with front-end devices according to their power standard.



6 KV Surge Protection

Hikvision switches are designed with surge protection to protect cameras installed outdoors that are vulnerable to lightning strikes.


Smart

and simple operation



Solid

and reliable performance



Secure

network at all times



Gigabit PoE

Model	DS-3E0505P-E	DS-3E0510P-E	DS-3E0518P-E	DS-3E0526P-E
				
Management	Unmanaged			
Ports	4 Gigabit PoE ports 1 Gigabit RJ45 uplink port	8 Gigabit PoE ports 1 Gigabit RJ45 uplink port 1 Gigabit SFP uplink port	16 Gigabit PoE ports 1 Gigabit RJ45 uplink port 1 Gigabit SFP uplink port	24 Gigabit PoE ports 1 Gigabit RJ45 uplink port 1 Gigabit SFP uplink port
PoE Standard	802.3 af/at			
PoE Budget	60 W	110 W	230 W	370 W
Package Forwarding Rate	7.44 Mpps	14.88 Mpps	26.784 Mpps	38.688 Mpps
Switching Capacity	10 Gbps	20 Gbps	36 Gbps	52 Gbps
Operating Temperature	-10 to 55 °C (14 to 131 °F)			
Dimensions	105 × 27.6 × 83.1 mm	217.6 × 27.8 × 108.55 mm	440 × 44 × 220.8 mm	440 × 44 × 220.8 mm

Gigabit Hi-PoE

Model	DS-3E0505HP-E	DS-3E0510HP-E	DS-3E0520HP-E	DS-3E0528HP-E	DS-3E1508-EI	DS-3E1516-EI	DS-3E1524-EI
							
Management	Unmanaged				Smart Managed		
Ports	3 × Gigabit PoE ports, 1 × Gigabit Hi-PoE port, and 1 × Gigabit RJ45 port	6 × Gigabit PoE ports, 2 × Gigabit Hi-PoE ports, 1 × Gigabit RJ45 port, and 1 × Gigabit fiber optical port	12 × Gigabit PoE ports, 4 × Gigabit Hi-PoE ports, 2 × Gigabit RJ45 ports, and 2 × Gigabit fiber optical ports	20 × Gigabit PoE ports, 4 × Gigabit Hi-PoE ports, 2 × Gigabit RJ45 ports, and 2 × Gigabit fiber optical ports	8 × 1 Gigabit RJ45 port	16 × Gigabit RJ45 ports	24 × Gigabit RJ45 ports
PoE Standard	802.3 af/at/bt	802.3 af/at	802.3 af/at	802.3 af/at	/		
PoE Budget	60 W	110 W	225 W	370 W	/		
Package Forwarding Rate	7.44 Mpps	14.88 Mpps	26.76 Mpps	41.664 Mpps	11.904 Mpps	23.808 Mpps	35.712 Mpps
Switching Capacity	10 Gbps	20 Gbps	40 Gbps	56 Gbps	16 Gbps	32 Gbps	48 Gbps
Operating Temperature	-10 °C to 40 °C (14 °F to 104 °F)	-10 °C to 40 °C (14 °F to 104 °F)	-10 °C to 55 °C (14 °F to 131 °F)	-10 °C to 55 °C (14 °F to 131 °F)	-10 °C to 55 °C (14 °F to 131 °F)	0 °C to 55 °C (32 °F to 131 °F)	0 °C to 55 °C (32 °F to 131 °F)
Dimensions	121 × 88.1 × 27.6 mm	217.6 × 108.55 × 27.8 mm	440 × 220.8 × 44 mm	440 × 220.8 × 44 mm	170 × 27.60 × 93.10 mm	257 × 44.50 × 175.80 mm	335 × 44.50 × 175.80 mm

Smart EI Non-PoE

Smart EI PoE

Model	DS-3E1105P-EI	DS-3E1309P-EI	DS-3E1318P-EI	DS-3E1326P-EI
				
Management	Smart Managed			
Ports	4 10/100 M RJ45 PoE ports 1 10/100M RJ45 port	8 10/100 M RJ45 PoE ports 1 Gigabit RJ45 port	16 10/100 M RJ45 PoE ports 2 Gigabit combo ports	24 10/100 M RJ45 PoE ports 2 Gigabit combo ports
Software Features	Smart managed on HCP/HPC/iVMS-4200, support link aggregation, LLDP			
PoE Standard	802.3 af/at			
PoE Budget	60 W	110 W	230 W	370 W
Package Forwarding Rate	7.44 Mpps	2.6784 Mpps	5.3568 Mpps	6.5472 Mpps
Switching Capacity	1Gbps	3.6 Gbps	7.2 Gbps	8.8 Gbps
Operating Temperature	0 to 40 °C (32 to 104 °F)		-10 to 55 °C (14 to 131 °F)	
Dimensions	105 × 27.6 × 83.1 mm	170 × 27.6 × 93.1 mm	440 × 44 × 220.8 mm	440 × 44 × 221 mm

Smart SI PoE

Model	DS-3E1510P-SI	DS-3E1518P-SI	DS-3E1526P-SI	DS-3E1552P-SI
				
Management	Smart Managed			
Ports	8 Gigabit PoE ports 2 Gigabit SFP ports	16 Gigabit PoE ports 2 Gigabit SFP ports	24 Gigabit PoE ports 2 Gigabit SFP ports	48 × 1 Gigabit PoE port, 2 × 1 Gigabit fiber optical port, 2 × 1 Gigabit RJ45 port
Software Features	Smart managed on HCP/HPC/iVMS-4200, support link aggregation, LLDP, port mirroring, storm control, PoE watchdog, port rate limiting, port isolation, SNMP, STP/RSTP, VLAN, QoS			
PoE Standard	802.3 af/at			
PoE Budget	110 W	225 W	370 W	470 W
Package Forwarding Rate	14.88 Mpps	26.784 Mpps	52 Gbps	77.376 Mpps
Switching Capacity	20 Gbps	36 Gbps	52 Mbpps	104 Gbps
Operating Temperature	-10 °C to 55 °C (14 °F to 131 °F)			0 °C to 45 °C (32 °F to 113 °F)
Dimensions	217.6 × 108.55 × 27.8 mm	440 × 220.8 × 44 mm	440 × 221 × 44 mm	440 × 44 × 323.80 mm

SUPPORT
 HIKVISION Canada: +1-866-200-6690
 e-mail: techsupport.ca@hikvision.com

HIKVISION Canada Inc. (Toronto)
 2335 Skyhawk Ave., Suite 300
 Mississauga, ON L4W 4Y6

Toll Free: +1 866-200-6690
 Phone: +1 909-895-0400
 e-mail: sales.canada@hikvision.com

Contact with us:





www.hikvision.ca