



**iVMS-5200 Mobile Surveillance V1.1.4
Software Requirements & Hardware Performance**

© 2020 Hangzhou Hikvision Digital Technology Co., Ltd. All rights reserved.

This Document (hereinafter referred to be “the Document”) is the property of Hangzhou Hikvision Digital Technology Co., Ltd. or its affiliates (hereinafter referred to as “Hikvision”), and it cannot be reproduced, changed, translated, or distributed, partially or wholly, by any means, without the prior written permission of Hikvision. Unless otherwise expressly stated herein, Hikvision does not make any warranties, guarantees or representations, express or implied, regarding to the Document, any information contained herein.

About this Document

Pictures, charts, images and all other information hereinafter are for description and explanation only. The information contained in the Document is subject to change, without notice, due to updates or other reasons.

Please use this Document with the guidance and assistance of professionals trained in supporting the Product.

LEGAL DISCLAIMER

TO THE MAXIMUM EXTENT PERMITTED BY APPLICABLE LAW, THE DOCUMENT IS PROVIDED "AS IS" AND “WITH ALL FAULTS AND ERRORS”. HIKVISION MAKES NO REPRESENTATIONS OR WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO, WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT. IN NO EVENT WILL HIKVISION BE LIABLE FOR ANY SPECIAL, CONSEQUENTIAL, INCIDENTAL, OR INDIRECT DAMAGES INCLUDING, AMONG OTHERS, DAMAGES FOR LOSS OF BUSINESS PROFITS, BUSINESS INTERRUPTION, OR LOSS OF DATA, CORRUPTION OF SYSTEMS, OR LOSS OF DOCUMENTATION, WHETHER BASED ON BREACH OF CONTRACT, TORT (INCLUDING NEGLIGENCE), OR OTHERWISE, IN CONNECTION WITH THE USE OF THE DOCUMENT, EVEN IF HIKVISION HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES OR LOSS.

1. Software Requirements

<p>OS for Mobile Surveillance Servers</p>	<p>Microsoft Windows 7 (64-bit) Microsoft Windows 8 (64-bit) Microsoft Windows 8.1 (64-bit) Microsoft Windows 10 (64-bit) Microsoft Windows Server 2008 R2 (64-bit) Microsoft Windows Server 2012 (64-bit)</p>
<p>OS for Mobile Surveillance Control Client</p>	<p>Microsoft Windows 7 (32-bit & 64-bit) Microsoft Windows 8 (32-bit & 64-bit) Microsoft Windows 8.1 (32-bit & 64-bit) Microsoft Windows 10 (64-bit) Microsoft Windows Server 2012 (32-bit & 64-bit)</p>
<p>Database</p>	<p>PostgreSQL V 9.3.9 (64-bit)</p>
<p>Browsers</p>	<p>Internet Explorer 9/10/11 or above (32-bit) Chrome 35/36/37/38/39/40/41/42/43/44 (32-bit) Firefox 32/33/34/35/36/37/38/39/40 (32-bit)</p>
<p>Virtualization (CMS)</p>	<p>VMware ESXI 6.x Microsoft Hype-V with Windows Server 2012 R2</p>
<p>Failover Cluster</p>	<p>Microsoft Windows Server 2008 R2 (64-bit) Microsoft Windows Server 2012 (64-bit) RoseReplicationPlus_5.1.0_175-x64</p>

2. Client Performance

Low-end

CPU: Intel® Xeon® i3-1450 v2 @3.50GHz 3.50GHz

RAM: 4GB DDR3 ECC

NIC: 1000 M

Graphics Card: Intel® HD Graphics 4400

Hard Disk Type: 1T SATA3 7200RPM Hard Drives

Mid-end

CPU: Intel® Xeon® i5-4460 v2 @3.20GHz 3.20GHz

RAM: 8GB DDR3 ECC

NIC: 1000 M

Graphics Card: NVIDIA® GeForce® GT730

Hard Disk Type: 1T SATA3 7200RPM Hard Drives

High-end

CPU: Intel® Xeon® E5-2650 v2 @2.60GHz 2.60GHz

RAM: 16G DDR3 ECC

NIC: 1000 M

Graphics Card: NVIDIA® GeForce® GTX960

Hard Disk Type: 1T SATA3 7200RPM Hard Drives

3. Server Performance

SMS Performance

SMS	
CPU: Intel® Xeon®E3-1230 v2 @3.30GHz 3.30GHz	
RAM: 8G	
Network: GbE network interface card	
Hard Disk Type: SATA-II 7200 RPM Enterprise Class Hard Drives	
Hard Drive Capacity: 10G for SMS log files	
Performance	300 Camera*2Mbps/s input and 300 Camera*2Mbps/s output

CMS Performance

Server 1	
CPU: Intel® Xeon®E3-1220V5	
OS: Windows Server 2012 R2 Standard	
RAM: 16GB UDIMM, 2400MT/s, ECC*1	
NIC: 1000 M	
Hard Disk Type: 1TB SATA3.5 Enterprise Class Hard Drives	
Performance	Up to 2000 sets of MVR Up to 200 pieces of GPS data can be handled in one second. 50 pieces of alarm can be handled in one second. GPS data can be saved for 3 months. Alarm logs can be saved for 6 months. GPS data of 24 hours will react in 8s.
Server 2	
CPU: Intel® Xeon®E5-2620 V4 8-core 2.1GHz	
OS: Windows Server 2012 R2 Standard	
RAM: 16GB RDIMM, 2400MT/s, ECC*2	
NIC: 1000 M	
Hard Disk Type: 1TB SATA3.5 Enterprise Class Hard Drives	
Performance	Up to 5000 sets of MVR Up to 500 pieces of GPS data can be handled in one second. 100 pieces of alarm can be handled in one second. GPS data can be saved for 3 months.

	Alarm logs can be saved for 6 months.
--	---------------------------------------

	GPS data of 24 hours will react in 8s.
--	--

Note : The GPS Upload Interval is recommended to set as 10s.



See Far, Go Further