

How to Configure the Second Lock on Door Station

Title:	How to configure the second lock on door station	Version:	v1.0	Date:	2020/11/24
Product:	Video Intercom			Page:	1 of 3

Preparation

1. This guide takes									
Туре	Model	Version							
Indoor station	DS-KH8520-WTE1	V2.2.3_2000713							
Door station	DS-KV8413-WME1(B)	V2.2.3_200805							

As examples to introduce configure the second lock on door station

2. Software: iVMS-4200 Version 3.4.0.9

How to Configure the Second Lock on Door Station

1. Add Devices on iVMS-4200

1) Search for online devices and add the door station on iVMS-4200, enter username and password, and then confirm that the device is online.



Title:	How to configure the second lock on door station	Version:	v1.0	Date:	2020/11/24
Product:	Video Intercom			Page:	2 of 3

2. Add Indoor Station to Door Station

1) Then go to **Device Management** → **Add**, set the **Device Type** as Indoor Station, fill in the necessary info of the device.

Note: The **password** is the device's password, if the device is inactive, set a new password in this page. The **registration password** is the password that must be configured for the activated device. When the door station adds an activated indoor station, the registration password of the indoor station must be known. The inactive indoor station can be directly assigned by door station. The **Port** is 8000.

			Device Management Config				1.	dmin 🕕 Help	E+Logout
Device List									
+ Add 🕼 Import 🕼 Expo	rt 📋 Delete 📿 Synchron	nize				Status All	Device Type Indoo	Station	2
No.	IP Address	Serial No.	Add Davice	Current Verring Elear Me	Poom No.	User Name	Network Status	Operation	
			Add Device		^				
			Device Type	Indoor Station					
			User Nam	admin					
			Passwore		•				
			Registration Passwore		0				
			Serial No	226732706	•				
			Floor No	1]				
			Room No	1	•				
			IP Address	10.9.96.153	•				
			IPv4 Subnet Masl	k 255.255.255.0	•				
			IPv4 Default Gateway	/ 10.9.96.254	•				
			Por	8000	•				
					OK Canad				
					Cancel				
			020	20 Hilovision Digital Technology Co., Ltd. Al	Rights Reserved.				

2) After we complete the device info, wait 5 to 10 minutes, you will see the page as shown below and the devices will be online

Н	KVI	SION		Live View	User	Number Settings	Device Management	Configuration					👤 admin	i) Help	E Logout
	D	evice List													
	+ Add	i 🕻 Import	t 🗋 Export	📋 Delete	🖉 Synchronize						Status All	Device Type	door Station		•
		No.		IP Address		Serial No.	Model	Current Version	Floor No.	Room No.	User Name	Network Status	Oper	ation	
		1		10.9.96.152		226732706	DS-KH8520-WTE1	V2.1.10 build 200713 🛕	1	1	admin	💙 Online	Ľ	© 💼	

3. Configure the Second lock on the Door Station

 Choose Configuration→Intercom→I/O Setting, Set the I/O Output No. Output2, enable it, and select Electric Lock as its value.

HIKVISION			wice Management Con	figuration		🚨 admin	Help	E+Logout
📮 Local	Device ID Settings Session Set	ttings Time Paramete	rs Ringbacktone Setti	ngs Press Button to Call	I/O Settings			
🗄 System 🗸 🗸								
Metwork ✓	I/O Input No.	Input1	~					
i⊟ Video/Audio	Input	Door Status	~					
🖾 Image	I/O Output No.	Output2	~					
🖹 Event 🗸 🗸	Output	Electric Lock	~					
📋 Schedule 🗸 🗸								
Intercom		Save						
Access Control								

Title:	How to configure the second lock on door station	v1.0	Date:	2020/11/24
Product:	Video Intercom	Page:	3 of 3	

2) When call the indoor station by door station, the user interface will be shown as below, you should notice there are two unlock options in the screen.



