

## DS-D5B75RB/EP 75-inch 4K Interactive Display



The Hikvision Interactive Flat Panel is a kind of newly developed intelligent teaching assistance product which integrates with the latest technologies of touch control, HD display, video processing, network communication, interactive control, sound control. It can be widely applied to the classroom, online teaching, training center, etc.

- UHD 4K display with resolution of 3840 × 2160.
- Anti-glare and anti-blocking design to ensure smooth interaction.
- Dual systems of Android and Windows (optional with OPS slot) saving cost and easy to use, video conference software are recommended to run under Windows system.
- Quick response, at most 50-point touch control and smooth writing experience.
- Built-in network switch chip saves a network switch.
- Multi-button design in front, convenient for classroom use.
- All-in-one design with tempered glass and intelligent temperature control, making it environmental-friendly and safety-guaranteed.
- Built-in Android 14 system, EDLA Certified

## ▪ Specification

Product Model	
Product Model	DS-D5B75RB/EP
Display	
Screen Size	75 inch
Backlight	DLED
Pixel Pitch	0.143 (H) × 0.429 (V) mm
Resolution	3840 × 2160 @60 Hz
Brightness	450 cd/m <sup>2</sup> (Max.) 400 cd/m <sup>2</sup> (Typ.)
Color Depth	10 bit
Display Color	1.07 G
Response Time	5 ms
Panel Type	VA
Contrast Ratio	5000:1 (Static) 30,000:1 (Dynamic)
Color Gamut	72% NTSC (CIE1931) (Typ.)
Refresh Rate	60 Hz
Viewing Angle	178° (H)/178° (V)
Aspect Ratio	16:9
Surface Hardness	9H (Pencil) 7 (Mohs)
Surface Glass	Tempered laminated 4mm Anti-Glare & Anti-Fingerprint Glass
Surface Haze	25% Haze
Glass Bonding Method	Zero Bonding
Display Area	1650.24 (H) × 928.26 (V)
Working Duration	7 × 16 H
Transmittance	88% ± 3
Lifespan	50,000 hours
Touch	
Type	Infrared Touch Screen
Touch Point	50 (Android), 20 (Windows), 1 (Mac OS)
Touch Response Time	≤ 2 ms
Minimum Touch Object	≥ 1.5 mm (≥ 90% touching area)
Touch Precision	± 0.5 mm (≥ 90% touching area)
Touch Resolution	32768 × 32768
Built-in System	
Operation System	Android 14.0 EDLA
Memory	8 GB
Built-in Storage	128 GB
Processor	Quad-core Cortex-A72 × 4 (2.2 GHz) and quad-core Cortex-A53 × 4 (1.8 GHz)
GPU	Mali-G52 MC3
HDCP Version	2.3 & 2.0 & 1.4
Internal Function	
Loudspeaker	Built-in 2 × 20 W + 25 W loudspeaker;


Bluetooth	Built-in BLE (Bluetooth Low Energy) module supports Bluetooth 5.4
NFC	Support card reader 13.56 MHz, (ISO 14443A/ ISO 14443B)
Light Sensor	Yes, Support automatic light adjustment
<b>Software</b>	
Whiteboard	Support multi touch Support split to 2/3 whiteboard function Support Triangle/Ruler/Protractor/European Triangular Ruler Support Insert 2D/3D Shapes (hexagon/Circle...)
WPS	View Word/PPT/Excel/PDF
Wondercast	Support screen share from Android/IOS/Windows to screen share Support screen share via different network
Device Optimizer	Support clear device files
File Browser	Support manage files in local storage & USB disk
Chrome Browser	Support internet access
Media Player	Support play Video & Audio
Upgrade	Support upgrade via OTA & USB disk
Central Management System	Support working with Hikcentral Forsign for remote management with multiple screens simultaneously from remote location, change hardware settings, downloading APK and installing on screens, and software upgrading.
System Language	Simplified Chinese, German, Italian, Arabic, Portuguese, Dutch, French, Indonesian, Thai, Vietnamese, Japanese, Spanish, English, Czech, Danish, Hungarian, Polish, Turkish, Russian, Romanian, Slovak, Korean, Uzbek, Bulgarian, Greek, Swedish, Norwegian, Finnish, Croatian, Slovenian, Serbian, Hebrew, Ukrainian, Traditional Chinese (Hong Kong), Traditional Chinese (Taiwan)
<b>Interface</b>	
Video & Audio Input	HDMI 2.0 × 3 (Front x 1; Rear x 2; Support HDCP2.3 & 2.2 & 1.4; HDMI1 Support CEC&ARC protocol) VGA × 1 (Rear) Audio (3.5mm) x1 (rear)
Video & audio output	HDMI 2.0 × 1 (Rear) Audio × 1 (Rear) SPDIF × 1 (Rear)
Control interface	TOUCH-USB 3.0 × 1 (Front × 1) TOUCH-USB 2.0 × 2 (Rear × 2) RS232 × 1 (Rear)
Network Interface	LAN (RJ45, 1000 Mbps) × 2 (Rear) Wi-Fi AP & Station, 2.4 G/5 G Wi-Fi 6, IEEE 802.11 a/b/g/n/ac/ax 2 × 2 MIMO (2.4 GHz and 5 GHz) authentication protocols WEP, WPA, WPA2, PSK and 802.1X EAP Support IPV4 & IPV6 network access

Data Transmission Interface	USB 3.0 × 3 (Front × 2; Rear × 1) USB 2.0 × 2 (Rear × 2) Type-C × 1 (Front × 1: Support USB 3.0, 65 W charging functions; support DP IN 1.4) Type-C × 1 (Rear × 1: Support USB 2.0, 65 W charging functions; support DP IN 1.4)
OPS Interface	1 Slot
<b>Power</b>	
Power Supply	100 to 240 VAC, 50/60 Hz
Standby Consumption	≤ 0.5 W
Average Consumption	< 189 W
<b>Working Environment</b>	
Working Temperature	0 °C to 40 °C (32 °F to 104 °F)
Working Humidity	10%~90% RH
<b>General</b>	
VESA	800 mm × 400 mm (4 × M8-25 mm)
Accessory	Wall mount bracket, hook, user manual, touch writing pen x2, packing list, power cable, remote control, screen cleaning cloth.
Package Dimensions (W × H × D)	1907 × 1160 × 223 mm
Net Weight	45.1 ± 0.5 kg
Gross Weight	62.4 ± 0.5 kg
Product Dimensions (With Wall Attachment)	1709.8 × 1017.3 × 110.4 mm
Product Dimensions (Without Wall Attachment)	1709.8 × 1017.3 × 83.2 mm
Certifications	CE/CB/Energy Star


## ▪ Physical Interface


Interface	Description	Interface	Description
1.SPDI	SPDI interface	2.Line OUT	Audio output interface
3.Line IN	Audio input interface	4.VGA IN	Video devices connection interface
5.TYPE-C	Type-C interface with DP input	6.TOUCH-USB 2	Peripheral touch interface
7.HDMI IN 2	HDMI 2 input interface	8.TOUCH-USB	Peripheral touch interface
9.HDMI IN 1	HDMI 1 input interface	10.USB	USB 2.0 interface
11.MULTI-USB 2	Multi-functional USB 3.0 interface	12.MULTI-USB 1	Multi-functional USB 3.0 interface
13.HDMI OUT	HDMI output interface	14.RS 232	RS 232 Control interface
15.LAN 1	LAN 1 interface	16. LAN 2	LAN 2 interface
A.USB	USB 3.0 interface	B.USB	USB 3.0 interface
C.TOUCH-USB	Peripheral touch interface	D.HDMI IN	HDMI input interface
E.TYPE-C	Type-C interface with DP input	F.	Light sensor
G.	Remote-control unit	H.	Power Key
J.	Volume -	K.	Volume +

L.	Android host menu	M.	Return
N.	Control menu	P.	PC shutdown
R.	NFC area		



## ▪ Installation







- **Available Model**

DS-D5B75RB/EP(EDLA)

- **Dimension**

If the equipment is installed embedded in the wall, reserve at least 50mm from each side.





## ▪ Accessory

## ▪ Optional

iDS-UVC-X28	DS-D5AC12T7-16S5	DS-D5AC12T5-8S2	DS-D5SC3B-W	DS-D5ABKY2-M
				
DS-D5SC3B-B	DS-D5ABKY2-S	DS-UVC-X12		
				



# See Far, Go Further



[www.hikvision.com](http://www.hikvision.com)  
[support@hikvision.com](mailto:support@hikvision.com)

