


A solid red horizontal banner with rounded ends on the right side, containing the product model number. The text is white and bold.

LED-D41Q25CA-1PH



- Supports seamless image stitching in any direction, size and shape and displays stitched images uniformly and consistently without black lines
- Uses the ultra-high refresh rate to display delicate and smooth video images
- Uses the broadcast grayscale processing to show more image details
- High brightness and high contrast

▪ Specification

Model		LED-D41Q25CA-1PH
Product Model	Product Model	LED-D41Q25CA-1PH
Module	Pixel Configuration	SMD
	Pixel Pitch	2.5 mm
	Lamp Bead Dimensions	2121
	Dimensions of Module	320 × 160
	Module Resolution	128 × 64
	Pixel Density	160000
	Signal Source Interface	HUB75E
Display	White Balance Brightness	500 nits
	Color Temperature	3000K to 10000K adjustable
	Viewing Angle	160° (H)/160° (V)
	Brightness Uniformity	≥ 97%
	Color Uniformity	Within ± 0.003 Cx, Cy
	Contrast Ratio	3000:1
	Refresh Rate	3840 Hz
Processing Performance	Scanning Amount	32
Power	Max. Consumption	≤ 980 W/m ²
	Average Consumption	< 400 W/m ²
	Input Voltage	4.5 VDC to 5 VDC
Working Environment	Working Temperature	-10 °C to 40 °C (14 °F to 104 °F)
	Working Humidity	10% RH to 80% RH (without condensation)
	Storage Temperature	-20 °C to 60 °C (-4 °F to 140 °F)
	Storage Humidity	10% RH to 85% RH (without condensation)
General	Package Dimensions (W × H × D)	673 mm × 453 mm × 390 mm (26.5 inch × 17.83 inch × 15.35 inch) (40 cabinets in 1 box)
	Packing List	Several high magnetic brackets Several LED lamp beads and IC components Several signal cables and power cables
	Gross Weight	0.61 kg (1.34 lb.)
	Net Weight	0.48 kg (1.06 lb.)
Cabinet	Cabinet Width(mm)	960
	Cabinet Height(mm)	960
	Cabinet Resolution(W)	384
	Cabinet Resolution(H)	384
	Module Quantity	3x6=18pcs
	Material	Iron
	Cabinet Weight	20kg/m ²

▪ Available Model

LED-D41Q25CA-1PH

▪ Dimension

