

DS-MDT501/4&64/gle Keyboard Handheld Terminal



- A 1MP global shutter sensor and lighting system to ensure excellent image quality.
- Laser aiming projects a crosshair pattern for easy targeting of objects.
- Self-developed high-performance barcode recognition technology can efficiently read barcodes of various formats.
- Supports various one-dimensional codes, including Code 11, Code 39, Code 93, Code 128, EAN-8, EAN-13, UPC-A, UPC-E, ITF-25, Codabar, Matrix 25, IND 25, PDF417, China Post, MSI-Plessey, etc.
- Supports various two-dimensional codes, including DM (ECC200), QR, MicroQR, Aztec, Hanxin, etc.
- Supports continuous and single scanning modes.
- Scanning interval: 10 to 2000 ms.
- Supports duplicate filtering timeout.
- Support NFC protocol: ISO15693, ISO14443A, ISO14443B.
- Image Sensor: Front camera: 5 MP; Rear camera: 13 MP.

▪ Specification


Camera	
Image Sensor	Front camera: 5 MP; Fix-focus Rear camera: 13 MP; Auto-focus
Flashing Light	Supported
Screen	
Screen Size	4.0"
Screen Type	IPS; Capacitive touch panel; multi-touch
Resolution	800 × 480 pixel
Storage	
CPU	8 cores, 2.0 GHz
RAM	4 GB
ROM	64 GB
Extended Storage	1 TF Card, supports up to 512 GB
Wireless Network	
Cellular Network	2G: B2/B3/B5/B8 3G: WCDMA: B1/B2/B5/B8 CDMA&EVDO: BCO, TD-SCDMA B34/B39 4G: FDD-LTE: B1/B3/B5/B7/B8/B20, TDD-LTE: B34/B38/B39/B40/B41
Wi-Fi Protocol	802.11 a/b/g/n/ac
Wi-Fi Frequency Band	2.4 GHz, 5 GHz
Bluetooth	BT 5.0
Positioning Mode	GPS, BeiDou, Glonass
NFC	Supported
Interface	
Button	Side Keys Volume+, Volume-, Left Scan Key, Right Scan Key, PTT Button
Keypad	37 Physical keyboard + 5 Side keys
SIM Card	2 (Nano-SIM)
Charging Interface	Type C
General	
Operating System	Android 11.0
Dimensions	210.4 × 75.8 × 38.9 mm
Weight	413 g
Power	Input: AC 100 to 240 V, 50 to 60 Hz Output: DC 5V, 2A
Client	MDM
Vibration Motor	Supported
Light Sensor	Supported
MIC	Supported
Drop Specifications	1.5 m
Operating Condition	Operating Temp: -15 °C to 55 °C Humidity: 95% or less (non-condensing)
Storage Condition	-40 °C to 60 °C
Sealing	IP68

Battery	
Battery Type	Replaceable Li-ion battery; Built-in hot-swappable battery (50 mAh)
Capacity	5200 mAh
Battery Duration	Standby Time: 350 H
Scanning Engine	
Model	Hikvision
Sensor	CMOS, Global shutter
Barcode Type	1D: Code 11, Code 39, Code 93, Code 128, EAN-8, EAN-13, UPC-A, UPC-E, ITF-25, Codabar, Matrix 25, IND 25, PDF417, China Post, MSI-Plessey, etc. 2D: DM (ECC200), QR, MicroQR, Aztec, Hanxin
Decode Ranges	Code39 (5 mil): 170 to 280 mm Code39 (20 mil): 80 to 1000 mm Code39 (100 mil): xx to 3700 mm DM (10 mil): 165 to 310 mm DM (167 mil): xx to 3100 mm Code128 (5 mil): 170 to 280 mm Code 128 (15 mil): 100 to 800 mm
Minimum reading accuracy	5 mil
Accessories	
Standard Accessories	USB cable × 1, power adapter × 1, wriststrap × 1

▪ Available Model

DS-MDT501/4&64/GLE

▪ Dimension



▪ Accessory

▪ Optional

DS-MH1421-501	DS-MH1330-501

See Far, Go Further



www.hikvision.com
support@hikvision.com



© Hangzhou Hikvision Digital Technology Co., Ltd. Unless otherwise agreed, Hikvision makes no warranties, express or implied. We reserve the right to introduce modifications without notice.

HIKVISION®