

DS-1600KI(C)
Network Keyboard



- High-performance, full-featured network keyboard
- Built-in Android system provides powerful control functions
- User friendly touch screen makes operation easy
- Flexible configuration via network
- Supports various cameras, NVRs and DVRs
- Supports uploading captured pictures and recorded videos to storage device
- Supports Preset Position, Auto Scan, Auto Pan, Auto Tour & Pattern Control

▪ Specification

System	
System Processor	Dual-core Processor
Operating System	Android 6.0
Interface	
USB Interface	2 x USB 3.0, 1 x USB 2.0
Serial Interface	Network, RS-232, RS-422, RS-485
Alarm In/Out	4/4
Network Interface	2 x 10M/100M/1000M adaptive Ethernet port; WiFi: Supported
General	
Working Temperature	-10 to +55° C (14 to 131° F)
Working Humidity	10% to 90%
Net Weight	1.7 kg (3.75 lb)
Dimensions (W × H × D)	404 mm × 163 mm × 180 mm (15.91" × 6.42" × 7.09")
Power Consumption	≤15 W
Power Supply	12 VDC/PoE
Display	10.1" TFT LCD touchscreen, Resolution: 1280 × 800
Joystick	4-axis joystick
Video	
Video Output Interface Type	1 ×HDMI, 1 ×DVI
Audio	
Audio Input Interfaces	1-ch, 3.5 mm connector (2.0 Vp-p, >1 KΩ)
Audio Output Interfaces	1-ch, 3.5 mm connector (2.0 Vp-p, 600 Ω)
Video Decoding	
Video Decoding Format	H.264, H.264+, H.265, H.265+, MPEG4
Video Decoding Capability	4 channels of 4K@25fps, 8 channels of 4MP@25fps, 16 channels of 1,080P@30fps
Certification	
Obtained Certification	CE-EMC/CE-LVD/ROHS/CB/UL/FCC-SDoC/RCM/BIS

▪ Available Model

DS-1600KI/ZAO Hikvision

DS-1600KI(C)

DS-1600KI(C)/美分

See Far, Go Further



www.hikvision.com
support@hikvision.com



© Hangzhou Hikvision Digital Technology Co., Ltd. Unless otherwise agreed, Hikvision makes no warranties, express or implied. We reserve the right to introduce modifications without notice.

HIKVISION®