

DS-VP41D-C/HW5X02 Tower Workstation



- Integrated graphics with great decoding capabilities
- Four-screen independent output for efficient management
- Pre-installed operating system and configured with keyboard and mouse, plug and play
- Operates in extreme temperatures and high humidity
- Customized dust filters for effective protection against windborne sand and dust

▪ Specification

Hardware Specifications	
CPU	i5-12500, 3.00 GHz, 18 MB Cache, 6 Cores, 12 Threads
Memory	Standard Config: 2 × 8GB UDIMM, 3200MT/s Scalability: 4 × 32GB UDIMM
Hard Disks	Standard Config: 1 × 512GB M.2 SSD Scalability: 1 × 4TB 3.5inch SATA HDD
Supported Operating Systems	Win11 IOT pre-installed
Graphic Card	UHD Graphics 770 (integrated in CPU), NVIDIA RTX A400 (4GB)
PCIe Slots	1*PCIe 4.0 x16 Slot 1*PCIe 4.0 x4 Slot
Ports	
Type-C	1
USB 3.0	1 (Front) +3 (Rear)
USB 2.0	2 (Front) +2 (Rear)
Universal Audio Port	1
Ethernet Port	1 x LAN 10/100/1000
VGA	/ (HDMI port can be used as VGA port)
HDMI	1
DP	3 (DP port can be used as HDMI port)
General	
Net Weight	5.63 kg (12.42 lb)
Gross Weight	6.72 kg (14.81 lb)
Dimension (W × H × D)	92.60 mm × 290.00 mm × 292.80 mm (3.65" × 11.42" × 11.53")
Package Dimensions (W × H × D)	394.00 mm × 264.00 mm × 487.00 mm (15.51" × 10.39" × 19.17")
Operating Temperature	5 °C to 45 °C (41 °F to 113 °F)
Storage Temperature	-40 °C to 70 °C (-40 °F to 158 °F)
Operating Humidity	20% to 80% (no condensation)
Storage Humidity	5% to 95% (no condensation)
Power Supply	300 W PSU, 92% Energy efficiency, 80 Plus Platinum
Form Factor	Tower / SFF

▪ Available Model

DS-VP41D-C/HW5X02

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
www.hikvision.com



Follow us on social media to get the latest product and solution information.



Hikvision



HikvisionHQ



HikvisionHQ



Hikvision_Global



Hikvision
Corporate Channel



hikvisionhq