

**DS-VP41D-C/HW7
Tower Workstation**

- Graphics with great decoding capabilities
- Four-screen independent output for efficient management
- Pre-installed operating system and configured with keyboard and mouse, plug and play
- Operates in extreme temperatures and high humidity
- Customized dust filters for effective protection against windborne sand and dust

▪ Specification

Hardware Specifications	
CPU	i7-14700, 2.10 GHz, 33 MB Cache, 20 Cores, 28 Threads
Memory	Standard Config: 2 × 32GB DDR5 DIMM/ 4 × 16GB DDR5 DIMM , 4400MT/s Scalability: 4 × 32GB DIMM
Hard Disks	Standard Config: 1 × 512GB M.2 NVMe SSD Scalability: 1 × 4TB 3.5inch SATA HDD
Supported Operating Systems	Windows 10 IoT/ Windows 10 Professional pre-installed
Graphic Card	NVIDIA GeForce RTX 2060
PCIe Slots	1*PCIe 4.0 x16 Slot 1*PCIe 4.0 x4 Slot
Ports	
Type-C	1
USB 3.0	1 (Front) +3 (Rear)
USB 2.0	2 (Front) +2 (Rear)
Audio Port	1 Universal Audio port, 1 Audio line-out
Network Interface	1 x LAN 10/100/1000, Wi-Fi 6E
VGA	/ (HDMI port can be used as VGA port)
HDMI	1
DP	3 (DP port can be used as HDMI port)
General	
Operating Temperature	5 °C to 45 °C (41 °F to 113 °F)
Storage Temperature	-40 °C to 70 °C (-40 °F to 158 °F)
Operating Humidity	20% to 80% (no condensation)
Storage Humidity	5% to 95% (no condensation)
Power Supply	300 W PSU, 92% Energy efficiency, 80 Plus Platinum
Form Factor	Tower
Accessories	Keyboard and Mouse
Safety	EN 62368-1:2014 +A11:2017, EN 62311:2008
EMC	CE-EMC: EN 55032:2015 +A11:2020, EN 55035:2017 +A11:2020
Environment	CE-RoHS: EN IEC 63000:2018

▪ Available Model

DS-VP41D-C/HW7

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
www.hikvision.com



Follow us on social media to get the latest product and solution information.



Hikvision



HikvisionHQ



HikvisionHQ



Hikvision_Global



Hikvision
Corporate Channel



hikvisionhq