

DS-D41Q15CA-1PH(PS)

P1.53, 320 mm × 160 mm, Indoor LED



- Supports seamless image stitching in any direction, size and shape and displays stitched images uniformly and consistently without black lines
- Supports 2K HD and 4K UHD video formats
- Utilizes MOB optical film for enhanced durability and clarity, applied with a high thermal conductivity double-sided adhesive for optimal heat dissipation and secure bonding.
- Material: Aluminum Die-Cast for strength and thermal efficiency
- Uses the ultra-high refresh rate to display delicate and smooth video images
- Operational Life: Rated for up to 100,000 hours of continuous operation
- Uses the broadcast grayscale processing to show more image details
- High brightness and high contrast


▪ Specification

Model		DS-D41Q15CA-1PH(PS)
Product Model	Product Model	DS-D41Q15CA-1PH(PS)
Module	Pixel Configuration	SMD
	Pixel Pitch	1.538 mm
	Lamp Bead Dimensions	1212
	Dimensions of Module	320 mm × 160 mm
	Module Resolution	208 × 104
	Pixel Density	422500
	Signal Source Interface	HUB320
Display	White Balance Brightness	450-550 nits
	Color Temperature	3000K to 10000K adjustable
	Viewing Angle	160° (H)/160° (V)
	Brightness Uniformity	≥ 97%
	Color Uniformity	≤ ± 0.003Cx, Cy
	Contrast Ratio	10000:1
	Refresh Rate	3840 Hz
Processing Performance	Scanning Amount	52
	Grey Level(Color Depth)	Up to 16 bit
Power	Max. Consumption	≤ 600 W/m ²
	Average Consumption	< 290 W/m ²
	Input Voltage	DC: 4.5 V to 5 V
General	Package Dimensions (W × H × D)	673 (W) mm × 248 (H) mm × 390 (D) mm (26.50" × 9.76" × 15.35") (20 cabinets in 1 box)
	Packing List	Several high magnetic brackets Several LED lamp beads and IC components Several signal cables and power cables
	Gross Weight	0.55 kg (1.21 lb)
	Net Weight	0.48 kg (1.06 lb)
Working Environment	Working Temperature	-10 °C to 40 °C (14 °F to 104 °F)
	Working Humidity	10% RH to 80% RH (without condensation)
	Storage Temperature	-20 °C to 60 °C (-4 °F to 140 °F)
	Storage Humidity	10% RH to 85% RH (without condensation)

▪ Available Model

DS-D41Q15CA-1PH(PS)

▪ Dimension



Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
www.hikvision.com



Follow us on social media to get the latest product and solution information.



Hikvision



HikvisionHQ



HikvisionHQ



Hikvision_Global



Hikvision
Corporate Channel



hikvisionhq