

DS-VBD1HH-UH/H/PAK



- Innovate at scale with challenging and emerging workloads
- Increase efficiency and accelerate operations with autonomous collaboration
- Built-in proactive resilience through a complete portfolio of solutions



Specification

Hardware Specifications	
CPU	Xeon Scalable processors 5418Y (24 core 2.0GHz) ×2
Hard Disk	960G SSD×2 (RAID1) /1.6T NVME U.2 SSD×4/8T 7.2K SATA HDD×6 (RAID10)
Device Dimensions	Form factor: Rack (2U)
	Height: 86.8 mm (3.41 inches)
	Width :482 mm (18.97 inches)
	Depth:
	707.78 mm (27.85 inches) without bezel
	721.62 mm (28.4 inches) – with bezel
	For reference only
Memory	64GB DDR5×8 RDIMM
Storage Controller	SAS_H755 8G RAID card
Power Supply	750 W (1 + 1)
Bezel	security bezel
Embedded Management	iDRAC9
	iDRAC Direct
	iDRAC RESTful API with Redfish
	iDRAC Service Module
	Quick Sync 2 wireless module
OpenManage™ Software	OpenManage Enterprise
	OpenManage Power Manager plugin
	OpenManage SupportAssist plugin
	OpenManage Update Manager plugin
Integrations and Connections	Integrations: BMC Truesight; Microsoft System Center; OpenManage Integrations; Red
	Hat Ansible Modules; VMware vCenter and vRealize Operations Manager
	Connections: IBM Tivoli Netcool/OMNIbus; IBM Tivoli Network Manager IP Edition;
	Micro Focus Operations Manager; OpenManage Connections; Nagios Core; Nagios XI
Security	Cryptographically signed firmware
	Data at Rest Encryption (SEDs with local or external key mgmt)
	Secure Boot
	Secure Erase
	Secured Component Verification (Hardware integrity check)
	Silicon Root of Trust
	System Lockdown (requires iDRAC9 Enterprise or Datacenter)
	TPM 2.0 FIPS, CC-TCG certified, TPM 2.0 China NationZ
I/O & Ports	Front Ports: 1 x iDRAC Direct (Micro-AB USB) port, 1 x USB 2.0, 1 x VGA Internal Ports:
	1 x USB 3.0 (optional)
	Rear Ports: 1 x Dedicated iDRAC Ethernet port, 1 x USB 2.0, 1 x USB 3.0, 1 x VGA, 1 x
	Serial (optional)
Companies de Onsensition - Content	Network ports: 10GbE×2+1GbE×2
Supported Operating Systems Physical and Environmental Baras	Not configured by default
Physical and Environmental Parar	
Net Weight (without package)	28.6 kg (63.00 lb.)



Gross Weight (with package) 37.2 kg (82.01 lb.) For reference only

Available Model

DS-VD22D-D/HW63



Headquarters
No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
www.hikvision.com

Follow us on social media to get the latest product and solution information.





ff HikvisionHQ



HikvisionHQ



Hikvision_Global



Hikvision Corporate Channel

