

DS-96000NI-I24 SERIES NVR



Características y funciones

Profesional y confiable

- Nuevo diseño de GUI lógico y visualizado.
- Adopts hardware and software integrated professionals, and pioneer design of dual SOS to ensure system reliability during execution.
- Supports redundant power supply to improve system stability.
- Admits hot-swapping of HDDs with RAID0, RAID1, RAID5, RAID 6 and RAID10 configurations.
- Normal mode or hot spare mode is configurable to constitute a hot swap system.

Entrada y transmisión de vídeo

- Can connect up to 128/256 IP cameras.
- Supports live viewing, storage and playback of connected cameras with a resolution of up to 12 megapixels.
- H.265+ compression reduces storage space by up to 75%.
- 4 auto-adapting network interfaces (10M/100M/1000M).
- Supports stream over TLS (improved SDK and RTP via HTTPS).
- Can connect to third-party network cameras such as ACTI, Arecont, AXIS, Bosch, Brickcom, Canon, ONVIF, PANASONIC, Pelco, SAMSUNG, SANYO, SONY, Vivotek and ZAVIO.

Salida HD

- HDMI 1/VGA simultaneous output as the main output and HDMI 2 as auxiliary output.
- HDMI and VGA1 simultaneous outputs by default. Configurable asynchronous outputs.
- Video output with a resolution of up to 4K (4096x2160).
- Supports decoding up to 20 channels at 1080p resolution.

Almacenamiento HD

- Up to 24 SATA and 1 eSATA interfaces for HDD connection.
- 10 TB capacity per hard disk.
- Hard disk status monitoring.
- Supports disk quota and group modes; different capacity can be assigned to different channels.
- Normal/importance/personalized video reproduction.

Varias aplicaciones


- Supports centralized management of IP cameras, including configuration, import/export information, real-time display, bidirectional audio, updates, etc.
- Connects to intelligent IP cameras from Hikvision and performs recording, playback and backup of VCA alarms.
- Supports VCA detection alarm.
- Facial search for VCA detection, behavior analysis, person counting and heat map.
- Initial registration with a key.
- Instantaneous reproduction of the assigned channel during multi-channel display mode.
- Intelligent search for the selected area in the video; intelligent reproduction to improve reproduction efficiency.



Especificaciones

Modelo		DS-96128NI-I24	DS-96256NI-I24
Entrada de vídeo y audio	Entrada de vídeo IP	128-ch	256-ch
	Entrada/salida Banda	576 Mbps/512 Mbps	768 Mbps/768 Mbps
	Entrada/salida ancho de banda (modo RAID)	576 Mbps/512 Mbps	768 Mbps/768 Mbps
	Ancho de banda de salida TLS	128 Mbps o 64 Mbps (cuando RAID está habilitado)	
	Protocolo	HIKVISION, ACTi, ARECONT, AXIS, BOSCH, BRICKCOM, CANON, HUNT, ONVIF (Versión 2.5), PANASONIC, PELCO, RTSP, SAMSUNG, SONY, VIVOTEK, ZAVIO	
Salida de vídeo y audio	Salida HDMI	Dos salidas HDMI independientes de resolución 4K. Resolución: 4K (4096 × 2160), 4K (3840 × 2160)/30Hz, 2K (2560 × 1440)/60Hz, 1080p (1920 × 1080)/60Hz, UXGA (1600 × 1200)/60Hz, SXGA (1280 × 1024)/60Hz, 720p (1280 × 720)/60Hz, XGA (1024 × 768)/60Hz	
	Salida VGA	1-ch. Resolución: 1080p (1920 × 1080)/60Hz, UXGA (1600 × 1200)/60Hz, SXGA (1280 × 1024)/60Hz, 720p (1280 × 720)/60Hz, XGA (1024 × 768)/60Hz	
	Salida LCD (opcional)	Una pantalla LCD de 7 pulgadas	
	Salida de audio	1-ch. RCA (2,0 Vp-p, 1 Ko)	
Decodificación de vídeo y audio	Formato de decodificación	H.265, H.265+, H.264, H.264+, MPEG4, MJPEG (solo para cámara IP Hikvision)	
	Resolución de vídeo	12 MP/8 MP/7 MP/6 MP/5 MP/4 MP/3 MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF	
	Reproducción sincrónica	Hasta 16 canales	
	Capacidad	3-ch@12 MP (30fps), 5-ch@8 MP (30fps), 6-ch@6 MP (30fps), 10-ch@4 MP (30fps), 20-ch@1080p (30 fps)	
Hdd	Interfaz	24 interfaces SATA compatibles con hot-plug	
	Capacidad	Hasta 10 TB por cada disco duro	
	Extensión de almacenamiento	1 interfaz × eSATA, interfaz mini SAS de 2 × (opcional)	
Raid	Tipo RAID	RAID0, RAID1, RAID5, RAID 6 y RAID10	
Red Administración	Protocolo	IPv4, IPv6, HTTPS, UPnP, SNMP, NTP, SADP, SMTP, NFS, iSCSI, PPPoE, DDNS	
	Interfaz de red	4, interfaz Ethernet autoadaptable RJ45 10M/100M/1000M	
Interfaz externa	Entrada de audio bidireccional	1-ch, RCA (2.0 Vp-p, 1 Ko)	
	Puerto serie	RS-232; RS-485; Teclado	
	Interfaz USB	Panel frontal: 1 × USB 2.0; Panel trasero: 2 × USB 3.0	
	Entrada/salida de alarma	16/8	
	Placa de extensión (opcional)	Una placa de extensión es compatible con cuatro interfaces ópticas 10M/100M/1000M (1.25 Gbps SFP módulo), ocho interfaces RS-485 e interfaz de alarma de 32 entradas de alarma y 16 salidas de alarma.	
General	Fuente de alimentación	100 a 240 VCA, 550W	
	Ventilador	Ventilador redundante de doble rodamiento de bolas; Velocidad ajustable; Hot-plug	
	Consumo (sin disco duro)	≤ 140W	
	Temperatura de trabajo	De 0 °C a + 50 °C (de 32 a 122 °F)	
	Humedad de trabajo	10% a 90%	
	Dimensión (W × D × H)	447 × 528 × 172 mm (17,6 × 20,8 × 6,8 pulgadas)	
	Peso (sin disco duro)	≤ 23 kg (50,7 lb))	

Interfaces físicas



No.	Nombre	No.	Nombre
1	Salida de vídeo HDMI 1/2	8	Botón de reinicio
2	Entrada de audio	9	Interfaz RS-232
3	Salida de audio		Entrada de alarma
4	USB 3.0		Salida de alarma
5	Lan		Interfaz RS-485
6	Interfaz eSATA		Interfaz de teclado
7	Salida de vídeo VGA	11	Tierra
8	Interfaz Mini SAS (Opcional)	12	Fuentes de alimentación

Modelos disponibles

DS-96128NI-I24; DS-96256NI-I24

Distributed by



Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
overseasbusiness@hikvision.com

Hikvision USA
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Italy
T +39-0438-6902
info.it@hikvision.com

Hikvision Singapore
T +65-6684-4718
sg@hikvision.com

Hikvision Europe
T +31-23-5542770
saleseuro@hikvision.com

Hikvision France
T +33(0)1-85-330-444
info.fr@hikvision.com

Hikvision Oceania
T +61-2-8599-4233
salesau@hikvision.com

Hikvision Middle East
T +971-4-8816086
salesme@hikvision.com

Hikvision Spain
T +34-91-737-16-55
info.es@hikvision.com

Hikvision Hong Kong
T +852-2151-1761

Hikvision Russia
T +7-495-669-67-99
saleru@hikvision.com

Hikvision Poland
T +48-22-460-01-50
poland@hikvision.com

Hikvision Canada
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision India
T +91-22-28469900
sales@pramahikvision.com

Hikvision UK
T +44-1628-9021-4
support.uk@hikvision.com