Explora nuevas posibilidades con la tecnología Colorvu

C+X
Incluso más que ColorVu

Ve en color, incluso en la oscuridad

Cámaras IP

NEW 4K

DS-2CD238762P-LSU/SL
Panoramic Turret Network Camera
- 0.0005 lux @ F1.0
- 2 x 1/1.8'' CMOS sensor
- 4 mm dual lens
- Colorful imaging 24/7
- Human/vehicle classification
- Strobe light and audio alarm
- H.265+/H.265
- IP67
- 130 dB WDR
- Built-in microphone and speaker
- Alarm I/O 1/1, audio I/O 1/1

NEW 4K

DS-2CD2T8762P-LSU/SL
Panoramic Bullet Network Camera
- 0.0005 lux @ F1.0
- 2 x 1/1.8'' CMOS sensor
- 4 mm dual lens
- Colorful imaging 24/7
- Human/vehicle classification
- Strobe light and audio alarm
- H.265+/H.265
- IP67
- 130 dB WDR
- Built-in microphone and speaker
- Alarm I/O 1/1, audio I/O 1/1

NEW 6 MP

DS-2CD2367G2P-LSU/SL
Panoramic Turret Network Camera
- 0.0005 lux @ F1.0
- 2 x 1/2.5'' CMOS sensor
- 2.8 mm dual lens
- Colorful imaging 24/7
- Human/vehicle classification
- Strobe light and audio alarm
- H.265+/H.265
- IP67
- 130 dB WDR
- Built-in microphone and speaker
- Alarm I/O 1/1, audio I/O 1/1
- *To be released in 2022Q3

NEW 6 MP

DS-2CD2T67G2P-LSU/SL
Panoramic Bullet Network Camera
- 0.0005 lux @ F1.0
- 2 x 1/2.5'' CMOS sensor
- 2.8 mm dual lens
- Colorful imaging 24/7
- Human/vehicle classification
- Strobe light and audio alarm
- H.265+/H.265
- IP67
- 130 dB WDR
- Built-in microphone and speaker
- Alarm I/O 1/1, audio I/O 1/1
- *To be released in 2022Q3

NEW 4 MP

DS-2CD234762P-LSU/SL
Panoramic Turret Network Camera
- 0.0005 lux @ F1.0
- 2 x 1/2.5'' CMOS sensor
- 2.8 mm dual lens
- Colorful imaging 24/7
- Human/vehicle classification
- Strobe light and audio alarm
- H.265+/H.265
- IP67
- 130 dB WDR
- Built-in microphone and speaker
- Alarm I/O 1/1, audio I/O 1/1
- *To be released in 2022Q3

NEW 4 MP

DS-2CD2T47G2P-LSU/SL
Panoramic Bullet Network Camera
- 0.0005 lux @ F1.0
- 2 x 1/2.5'' CMOS sensor
- 2.8 mm dual lens
- Colorful imaging 24/7
- Human/vehicle classification
- Strobe light and audio alarm
- H.265+/H.265
- IP67
- 130 dB WDR
- Built-in microphone and speaker
- Alarm I/O 1/1, audio I/O 1/1
- *To be released in 2022Q3

NEW 4 MP

DS-2CD2647G2T-LZS
Bullet Network Camera
- 0.0005 lux @ F1.0
- 1/1.8'' CMOS sensor
- 2.8 - 12 mm motorized vari focal lens
- Colorful imaging 24/7
- Human/vehicle classification
- H.265+/H.265
- IP67, IK10
- 130 dB WDR
- Alarm I/O 1/1, audio I/O 1/1
- *To be released in 2022Q3

NEW 4 MP

DS-2CD2747G2T-LZS
Dome Network Camera
- 0.0005 lux @ F1.0
- 1/1.8'' CMOS sensor
- 2.8 - 12 mm motorized vari focal lens
- Colorful imaging 24/7
- Human/vehicle classification
- H.265+/H.265
- IP67, IK10
- 130 dB WDR
- Alarm I/O 1/1, audio I/O 1/1
- *To be released in 2022Q3

HOT 4 MP

DS-2DE3A400BW-DE(F1)(T5)
Fixed Network PT Camera
- 0.0005 lux @ F1.0
- 1/1.8'' CMOS sensor
- 4 mm fixed lens
- Pan: 350°, tilt: 0° to 90°
- Colorful imaging 24/7
- Human/vehicle classification
- Strobe light and audio alarm
- H.265+/H.265
- IP66
- 120 dB WDR

HOT 4K

DS-2CD2087G2-L(U)
Bullet Network Camera
- 0.0005 lux @ F1.0
- 1/1.2'' CMOS sensor
- 2.8, 4 or 6 mm fixed lens
- Colorful imaging 24/7
- Human/vehicle classification
- H.265+/H.265
- IP67
- 130 dB WDR
- -U: built-in microphone

HOT 4K

DS-2CD2387G2-L(U)
Turret Network Camera
- 0.0005 lux @ F1.0
- 1/1.2'' CMOS sensor
- 2.8 or 4 mm fixed lens
- Colorful imaging 24/7
- Human/vehicle classification
- H.265+/H.265
- IP67
- 130 dB WDR
- -U: built-in microphone

HOT 4K

DS-2CD2T87G2-L
Bullet Network Camera
- 0.0005 lux @ F1.0
- 1/1.2'' CMOS sensor
- 2.8, 4 or 6 mm fixed lens
- Colorful imaging 24/7
- Human/vehicle classification
- H.265+/H.265
- IP67
- 130 dB WDR

HOT 4K

DS-2CD2387G2-LSU/SL
Turret Network Camera
- 0.0005 lux @ F1.0
- 1/1.2'' CMOS sensor
- 2.8 or 4 mm fixed lens
- Colorful imaging 24/7
- Human/vehicle classification
- Strobe light and audio alarm
- H.265+/H.265
- IP67
- 130 dB WDR
- Built-in microphone and speaker
- Alarm I/O 1/1, audio I/O 1/1

HOT 4K

DS-2CD2T87G2-LSU/SL
Bullet Network Camera
- 0.0005 lux @ F1.0
- 1/1.2'' CMOS sensor
- 2.8, 4 or 6 mm fixed lens
- Colorful imaging 24/7
- Human/vehicle classification
- Strobe light and audio alarm
- H.265+/H.265
- IP67
- 130 dB WDR
- Built-in microphone and speaker
- Alarm I/O 1/1, audio I/O 1/1

4 MP

DS-2CD2047G2-L(U)
Bullet Network Camera
- 0.0005 lux @ F1.0
- 1/1.8'' CMOS sensor
- 2.8, 4 or 6 mm fixed lens
- Colorful imaging 24/7
- Human/vehicle classification
- H.265+/H.265
- IP67
- 130 dB WDR
- -U: built-in microphone

HOT 4 MP

DS-2CD2147G2-L(SU)
4 MP Dome Network Camera
- 0.0005 lux @ F1.0
- 1/1.8'' CMOS sensor
- 2.8 or 4 mm fixed lens
- Colorful imaging 24/7
- Human/vehicle classification
- H.265+/H.265
- IP67, IK10
- 130 dB WDR
- -SU: built-in microphone, alarm I/O 1/1, audio I/O 1/1

HOT 4 MP

DS-2CD2347G2-L(U)
4 MP Turret Network Camera
- 0.0005 lux @ F1.0
- 1/1.8'' CMOS sensor
- 2.8 or 4 mm fixed lens
- Colorful imaging 24/7
- Human/vehicle classification
- H.265+/H.265
- IP67
- 130 dB WDR
- -U: built-in microphone

4 MP

DS-2CD2547G2-LS
4 MP Mini Dome Network Camera
- 0.0005 lux @ F1.0
- 1/1.8'' CMOS sensor
- 2.8 or 4 mm fixed lens
- Colorful imaging 24/7
- Human/vehicle classification
- H.265+/H.265
- IP67, IK08
- 130 dB WDR
- Built-in microphone, alarm I/O 1/1, audio I/O 1/1

4 MP

DS-2CD2T47G2-L
4 MP Bullet Network Camera
- 0.0005 lux @ F1.0
- 1/1.8'' CMOS sensor
- 2.8, 4 or 6 mm fixed lens
- Colorful imaging 24/7
- Human/vehicle classification
- H.265+/H.265
- IP67
- 130 dB WDR

HOT 4 MP

DS-2CD2047G2-LU/SL
Bullet Network Camera
- 0.0005 lux @ F1.0
- 1/1.8'' CMOS sensor
- 2.8, 4 or 6 mm fixed lens
- Colorful imaging 24/7
- Human/vehicle classification
- Strobe light and audio alarm
- H.265+/H.265
- IP67
- 130 dB WDR
- Built-in microphone and speaker

HOT 4 MP

DS-2CD2347G2-LSU/SL
Turret Network Camera
- 0.0005 lux @ F1.0
- 1/1.8'' CMOS sensor
- 2.8 or 4 mm fixed lens
- Colorful imaging 24/7
- Human/vehicle classification
- Strobe light and audio alarm
- H.265+/H.265
- IP67
- 130 dB WDR
- Built-in microphone and speaker
- Alarm I/O 1/1, audio I/O 1/1

HOT 4 MP

DS-2CD2T47G2-LSU/SL
Bullet Network Camera
- 0.0005 lux @ F1.0
- 1/1.8'' CMOS sensor
- 2.8, 4 or 6 mm fixed lens
- Colorful imaging 24/7
- Human/vehicle classification
- Strobe light and audio alarm
- H.265+/H.265
- IP67
- 130 dB WDR
- Built-in microphone and speaker
- Alarm I/O 1/1, audio I/O 1/1

2 MP

DS-2CD2027G2-L(U)
Bullet Network Camera
- 0.0005 lux @ F1.0
- 1/2.8'' CMOS sensor
- 2.8, 4 or 6 mm fixed lens
- Colorful imaging 24/7
- Human/vehicle classification
- H.265+/H.265
- IP67
- 120 dB WDR
- -U: built-in microphone

2 MP

DS-2CD2127G2(-SU)
Dome Network Camera
- 0.0005 lux @ F1.0
- 1/2.8'' CMOS sensor
- 2.8 or 4 mm fixed lens
- Colorful imaging 24/7, with dim environmental light requirement
- Human/vehicle classification
- H.265+/H.265
- IP67, IK10
- 120 dB WDR
- -SU: built-in microphone, alarm I/O 1/1, audio I/O 1/1

2 MP

DS-2CD2327G2-L(U)
Turret Network Camera
- 0.0005 lux @ F1.0
- 1/2.8'' CMOS sensor
- 2.8 or 4 mm fixed lens
- Colorful imaging 24/7
- Human/vehicle classification
- H.265+/H.265
- IP67
- 120 dB WDR
- -U: built-in microphone

2 MP

DS-2CD2527G2-LS
Dome Network Camera
- 0.0005 lux @ F1.0
- 1/2.8'' CMOS sensor
- 2.8 or 4 mm fixed lens
- Colorful imaging 24/7
- Human/vehicle classification
- H.265+/H.265
- IK08 ; IP67
- 120 dB WDR
- Built-in microphone, alarm I/O 1/1,audio I/O 1/1

2 MP

DS-2CD2T27G2-L
Bullet Network Camera
- 0.0005 lux @ F1.0
- 1/2.8'' CMOS sensor
- 2.8, 4 or 6 mm fixed lens
- Colorful imaging 24/7
- Human/vehicle classification
- H.265+/H.265
- IP67
- 120 dB WDR

Cámaras Turbo HD

HOT 4K

DS-2CE10UF3T-E
PoC Fixed Mini Bullet Camera
- 0.0005 lux @ F1.0
- 2.8/3.6 mm
- 130 dB true WDR, 3D DNR technology
- 20 m lighting distance
- IP67
- Metal
- PoC

HOT 4K

DS-2CE12UF3T-E
PoC Fixed Bullet Camera
- 0.0005 lux @ F1.0
- 2.8/3.6 mm
- 130 dB true WDR, 3D DNR technology
- 40 m lighting distance
- IP67
- Metal
- PoC

HOT 4K

DS-2CE72UF3T-E
PoC Fixed Turret Camera
- 0.0005 lux @ F1.0
- 2.8/3.6 mm
- 130 dB true WDR, 3D DNR technology
- 40 m lighting distance
- IP67
- PoC

HOT 3K

DS-2CE10KF3T
Fixed Mini Bullet Camera
- 0.0003 lux @ F1.0
- 2.8 / 3.6 mm
- 130 dB true WDR, 3D DNR technology
- 20 m lighting distance
- IP67
- Metal

HOT 3K

DS-2CE12KF3T
Fixed Bullet Camera
- 0.0003 lux @ F1.0
- 2.8 / 3.6 mm
- 130 dB true WDR, 3D DNR technology
- 40 m lighting distance
- IP67
- Metal

HOT 3K

DS-2CE72KF3T
Fixed Turret Camera
- 0.0003 lux @ F1.0
- 2.8 / 3.6 mm
- 130 dB true WDR, 3D DNR technology
- 40 m lighting distance
- IP67

HOT 3K

DS-2CE10KF3T-E
Fixed Mini Bullet Camera
- 0.0003 lux @ F1.0
- 2.8/3.6 mm
- 130 dB true WDR, 3D DNR technology
- 20 m lighting distance
- IP67
- Metal
- Power over Coaxial cable (-E)

HOT 3K

DS-2CE12KF3T-E
Fixed Bullet Camera
- 0.0003 lux @ F1.0
- 2.8/3.6 mm
- 130 dB true WDR, 3D DNR technology
- 40 m lighting distance
- IP67
- Metal
- Power over Coaxial cable (-E)

HOT 3K

DS-2CE72KF3T-E
Fixed Turret Camera
- 0.0003 lux @ F1.0
- 2.8/3.6 mm
- 130 dB true WDR, 3D DNR technology
- 40 m lighting distance
- IP67
- Power over Coaxial cable (-E)

HOT 3K

DS-2CE10KF0T-FS
Audio Fixed Mini Bullet Camera
- 0.001 lux @ F1.0
- 2.8 / 3.6 mm
- DWDR, 2D DNR technology
- 20 m lighting distance
- Audio over Coaxial cable
- IP67
- Metal

HOT 3K

DS-2CE10KF0T-PFS
Audio Fixed Mini Bullet Camera
- 0.001 lux @ F1.0
- 2.8 / 3.6 mm
- DWDR, 2D DNR technology
- 20 m lighting distance
- Audio over Coaxial cable
- IP67
- Plastic

HOT 3K

DS-2CE12KF0T-FS
Audio Fixed Bullet Camera
- 0.001 lux @ F1.0
- 2.8 / 3.6 mm
- DWDR, 2D DNR technology
- 40 m lighting distance
- Audio over Coaxial cable
- IP67
- Metal

HOT 3K

DS-2CE70KF0T-MFS
Audio Fixed Turret Camera
- 0.001 lux @ F1.0
- 2.8 / 3.6 mm
- DWDR, 2D DNR technology
- 20 m lighting distance
- Audio over Coaxial cable
- IP67
- Metal

HOT 3K

DS-2CE70KF0T-PFS
Indoor Audio Fixed Turret Camera
- 0.001 lux @ F1.0
- 2.8 / 3.6 mm
- DWDR, 2D DNR technology
- 20 m lighting distance
- Audio over Coaxial cable
- Plastic

HOT 3K

DS-2CE72KF0T-FS
Audio Fixed Turret Camera
- 0.001 lux @ F1.0
- 2.8 / 3.6 mm
- DWDR, 2D DNR technology
- 40 m lighting distance
- Audio over Coaxial cable
- IP67

5 MP

DS-2CE10HFT-F
DS-2CE10HFT-E
Fixed Mini Bullet Camera
- 0.0005 lux @ F1.0
- 3.6/6 mm
- 130 dB true WDR, 3D DNR technology
- 20 m lighting distance
- IP67
- Power over Coaxial cable (-E)
- Metal

5 MP

DS-2CE12HFT-F
DS-2CE12HFT-E
Fixed Bullet Camera
- 0.0005 lux @ F1.0
- 3.6/6 mm
- 130 dB true WDR, 3D DNR technology
- 40 m lighting distance
- IP67
- Power over Coaxial cable (-E)

5 MP

DS-2CE72HFT-F
DS-2CE72HFT-E
Fixed Turret Camera
- 0.0005 lux @ F1.0
- 3.6/6 mm
- 130 dB true WDR, 3D DNR technology
- 20 m lighting distance
- IP67
- Power over Coaxial cable (-E)

5 MP

DS-2CE10HFT-E
PoC Fixed Mini Bullet Camera
- 0.0005 lux @ F1.0
- 2.8/3.6 mm
- 130 dB true WDR, 3D DNR technology
- 20 m lighting distance
- Power over Coaxial cable
- IP67

5 MP

DS-2CE12HFT-E
PoC Fixed Bullet Camera
- 0.0005 lux @ F1.0
- 2.8/3.6 mm
- 130 dB true WDR, 3D DNR technology
- 40 m lighting distance
- Power over Coaxial cable
- IP67

5 MP

DS-2CE72HFT-E
PoC Fixed Turret Camera
- 0.0005 lux @ F1.0
- 2.8/3.6 mm
- 130 dB true WDR, 3D DNR technology
- 20 m lighting distance
- Power over Coaxial cable
- IP67

2 MP

DS-2CE72DF8T-F
Fixed Turret Camera
- 0.0003 lux @ F1.0
- 130 dB true WDR, 3D DNR technology
- 40 m lighting distance
- IP68
- Main body: Metal; Enclosure: Plastic
- 2.8mm / 3.6mm

2 MP

DS-2CE12DF8T-F(SLN)
Fixed Bullet Camera
- 0.0003 lux @ F1.0
- 2.8/3.6 mm
- 130 dB true WDR, 3D DNR technology
- 40 m lighting distance
- Built-in mic, up to 12 m audio collection
- Dual noise reduction (with DVR)
- Line in port
- IP67
- Metal

2 MP

DS-2CE10DF8T-F(SLN)
Fixed Mini Bullet Camera
- 0.0003 lux @ F1.0
- 2.8/3.6 mm
- 130 dB true WDR, 3D DNR technology
- 20 m lighting distance
- Built-in mic, up to 12 m audio collection
- Dual noise reduction (with DVR)
- Line in port
- IP67
- Metal

2 MP

DS-2CE10DF8T-PF(SLN)
Fixed Mini Bullet Camera
- 0.0003 lux @ F1.0
- 2.8/3.6 mm
- 130 dB true WDR, 3D DNR technology
- 20 m lighting distance
- Built-in mic, up to 12 m audio collection
- Dual noise reduction (with DVR)
- Line in port
- IP67
- Plastic

2 MP

DS-2CE72DF8T-F(SLN)
Fixed Turret Camera
- 0.0003 lux @ F1.0
- 2.8/3.6 mm
- 130 dB true WDR, 3D DNR technology
- 40 m lighting distance
- Built-in mic, up to 12 m audio collection
- Dual noise reduction (with DVR)
- Line in port
- IP67

2 MP

DS-2CE70DF8T-MF(SLN)
Fixed Turret Camera
- 0.0003 lux @ F1.0
- 2.8/3.6 mm
- 130 dB true WDR, 3D DNR technology
- 20 m lighting distance
- Built-in mic, up to 12 m audio collection
- Dual noise reduction (with DVR)
- Line in port
- IP67
- Full metal

2 MP

DS-2CE70DF8T-PF(SLN)
Indoor Fixed Turret Camera
- 0.0003 lux @ F1.0
- 2.8/3.6 mm
- 130 dB true WDR, 3D DNR technology
- 20 m lighting distance
- Built-in mic, up to 12 m audio collection
- Dual noise reduction (with DVR)
- Line in port
- Plastic

2 MP

DS-2CE19DF8T-AZE
PoC Motorized Varifocal Bullet Camera
- Fixed 0.0003 lux @ F1.0
- 2.8 – 12 mm motorized lens
- Up to 40 m lighting distance (high/low beam headlights)
- Auto focus
- IP68
- PoC/AC/DC triple power supply

2 MP

DS-2CE59DF8T-AVPZE
Vandal PoC Motorized Varifocal Dome Camera
- Fixed 0.0003 lux @ F1.0
- 2.8 – 12 mm motorized lens
- Up to 40 m lighting distance (high/low beam headlights)
- Auto focus
- IP68, IK10
- PoC/AC/DC triple power supply
- Bubble with light-sheild
- Built-in junction box

2 MP

DS-2CE79DF8T-AZE
PoC Motorized Varifocal Turret Camera
- Fixed 0.0003 lux @ F1.0
- 2.8 – 12 mm motorized lens
- Up to 40 m lighting distance (high/low beam headlights)
- Auto focus
- IP68
- PoC/AC/DC triple power supply

2 MP

DS-2CE12DF3T-F(S)
Fixed Bullet Camera
- 0.0005 lux @ F1.0
- 2.8/3.6 mm
- 130 dB true WDR, 3D DNR technology
- 40 m lighting distance
- Built-in mic, up to 12 m audio collection
- Dual noise reduction (with DVR)
- IP67
- Metal

2 MP

DS-2CE10DF3T-F(S)
Fixed Mini Bullet Camera
- 0.0005 lux @ F1.0
- 2.8/3.6 mm
- 130 dB true WDR, 3D DNR technology
- 20 m lighting distance
- Built-in mic, up to 12 m audio collection
- Dual noise reduction (with DVR)
- IP67
- Metal

2 MP

DS-2CE10DF3T-PF(S)
Fixed Mini Bullet Camera
- 0.0005 lux @ F1.0
- 2.8/3.6 mm
- 130 dB true WDR, 3D DNR technology
- 20 m lighting distance
- Built-in mic, up to 12 m audio collection
- Dual noise reduction (with DVR)
- IP67
- Plastic

2 MP

DS-2CE72DF3T-F(S)
Fixed Turret Camera
- 0.0005 lux @ F1.0
- 2.8/3.6 mm
- 130 dB true WDR, 3D DNR technology
- 40 m lighting distance
- Built-in mic, up to 12 m audio collection
- Dual noise reduction (with DVR)
- IP67

2 MP

DS-2CE70DF3T-MF(S)
Fixed Turret Camera
- 0.0005 lux @ F1.0
- 2.8/3.6 mm
- 130 dB true WDR, 3D DNR technology
- 20 m lighting distance
- Built-in mic, up to 12 m audio collection
- Dual noise reduction (with DVR)
- IP67
- Full metal

2 MP

DS-2CE70DF3T-PF(S)
Indoor Fixed Turret Camera
- 0.0005 lux @ F1.0
- 2.8/3.6 mm
- 130 dB true WDR, 3D DNR technology
- 20 m lighting distance
- Built-in mic, up to 12 m audio collection
- Dual noise reduction (with DVR)
- Plastic

NEW 2 MP

DS-2CE70DF3T-PFS
Indoor Audio Fixed PT Camera
- 0.0005 lux @ F1.0
- 2.8/3.6 mm
- 20 m lighting distance
- Built-in mic, audio over coaxial
- Pan: 0° to 350°, tilt: 0° to 75°
- PT rotation through DVR or Hik-connect
- Plastic

2 MP

DS-2CE10DF0T-F
Fixed Mini Bullet Camera
- 0.001 lux @ F1.0
- DWDR, 3D DNR technology
- 20 m lighting distance
- IP67
- Metal
- 2.8mm / 3.6mm

2 MP

DS-2CE10DF0T-PF
Fixed Mini Bullet Camera
- 0.001 lux @ F1.0
- DWDR, 3D DNR technology
- 20 m lighting distance
- IP67
- Plastic
- 2.8mm / 3.6mm

2 MP

DS-2CE12DF0T-F
Fixed Bullet Camera
- 0.001 lux @ F1.0
- DWDR, 3D DNR technology
- 40 m lighting distance
- IP67
- Metal
- 2.8mm / 3.6mm

2 MP

DS-2CE70DF0T-MF
Fixed Turret Camera
- 0.001 lux @ F1.0
- DWDR, 3D DNR technology
- 20 m lighting distance
- IP67
- Metal
- 2.8mm / 3.6mm

2 MP

DS-2CE70DF0T-PF
Indoor Fixed Turret Camera
- 0.001 lux @ F1.0
- DWDR, 3D DNR technology
- 20 m lighting distance
- IP67
- Plastic
- 2.8mm / 3.6mm

2 MP

DS-2CE72DF0T-F
Fixed Turret Camera
- 0.001 lux @ F1.0
- DWDR, 3D DNR technology
- 40 m lighting distance
- IP67
- Main body: Metal; Enclosure: Plastic
- 2.8mm / 3.6mm

NEW 4K

DS-2CE12UF3T-PIRX0
Live Guard Fixed Bullet Camera
- 0.0005 lux @ F1.0
- 3 + 1 Voice Broadcasts
- 3 built-in voice broadcasts
- 1 voice broadcast customization by Hik-Connect
- Audio over Coaxial
- Built-in dual mic, dual noise reduction (with DVR)
- 40 m lighting distance
- Active strobe light and audio alarm to warn intruders off
- IP67

NEW 4K

DS-2CE72UF3T-PIRX0
Live Guard Fixed Turret Camera
- 0.0005 lux @ F1.0
- 3 + 1 Voice Broadcasts
- 3 built-in voice broadcasts
- 1 voice broadcast customization by Hik-Connect
- Audio over Coaxial
- Built-in dual mic, dual noise reduction (with DVR)
- 20 m lighting distance
- Active strobe light and audio alarm to warn intruders off
- IP67

NEW 3K

DS-2CE12KF3T-PIRX0
Live Guard Fixed Bullet Camera
- 0.0005 lux @ F1.0
- 3 + 1 Voice Broadcasts
- 3 built-in voice broadcasts
- 1 voice broadcast customization by Hik-Connect
- Audio over Coaxial
- Built-in dual mic, dual noise reduction (with DVR)
- 40 m lighting distance
- Active strobe light and audio alarm to warn intruders off
- IP67

NEW 3K

DS-2CE72KF3T-PIRX0
Live Guard Fixed Turret Camera
- 0.0005 lux @ F1.0
- 3 + 1 Voice Broadcasts
- 3 built-in voice broadcasts
- 1 voice broadcast customization by Hik-Connect
- Audio over Coaxial
- Built-in dual mic, dual noise reduction (with DVR)
- 20 m lighting distance
- Active strobe light and audio alarm to warn intruders off
- IP67

2 MP

DS-2CE12DF3T-PIRX0S
Live Guard Audio Fixed Bullet Camera
- 0.0005 lux @ F1.0
- 3 + 1 Voice Broadcasts
- 3 built-in voice broadcasts
- 1 voice broadcast customization by Hik-Connect
- Audio over Coaxial
- Built-in dual mic, dual noise reduction (with DVR)
- 40 m lighting distance
- Red and blue strobe light alarm, audible alarm
- IP67

2 MP

DS-2CE72DF3T-PIRX0S
Live Guard Audio Turret Bullet Camera
- 0.0005 lux @ F1.0
- 3 + 1 Voice Broadcasts
- 3 built-in voice broadcasts
- 1 voice broadcast customization by Hik-Connect
- Audio over Coaxial
- Built-in dual mic, dual noise reduction (with DVR)
- 20 m lighting distance
- Red and blue strobe light alarm, audible alarm
- IP67

ColorVu+X

HIKVISION