



DL SERIES

Wall-Mounted Digital Signage

43" 50" 55" 65" 75"



**Multiple
Sizes**

4K

**4K
Display**



**500 nits Brightness
with 25% Haze**




**Wide
FOV**

4K Ultra HD


25% haze, exceptionally clear images
and videos, cost-effective for
professional advertising

4K



Sleek Design

All-plastic slim body, four-sided even bezel, lightweight and attractive, ideal for retail advertising




Multiple Screen Sizes

Designed for diverse advertising needs in catering, shopping malls, stores, and office buildings

HCF Powers Integrated Retail Solution

Combining HCF's one-stop smart retail solution with content design, information release, and device management to drive business growth



Remote Device Management



Powerful Program Editing



Diverse Material Types



Flexible Schedule Settings



Supervisor Approval Feature



Weather Forecast Plugin



Built-in Templates



RSS Content Display

Model	DS-D6043UN-DL	DS-D6050UN-DL	DS-D6055UN-DL
-------	---------------	---------------	---------------

Display Panel

Screen Size	43 inch	50 inch	55 inch
Resolution	3840 × 2160	3840 × 2160	3840 × 2160
Active Display Area (mm)	941.184 (H) × 529.416 (V)	1095.84 (H) × 616.411 (V)	1219.70 (H) × 691.89 (V)
Pixel Pitch (mm)	0.2451 (H) × 0.2451 (V)	0.09513 (H) × 0.28539 (V)	0.105 (H) × 0.315 (V)
Backlight	D-LED	D-LED	D-LED
Viewing Angle	178°(H)/178°(V)	178°(H)/178°(V)	178°(H)/178°(V)
Contrast Ratio	4000:1	1200:1	4000:1
Brightness	500 cd/m²	500 cd/m²	500 cd/m²
Color Depth	10 bit (8 bit + FRC)	10 bit (8 bit + FRC)	10 bit (8 bit + FRC)
Response Time	8 ms	8 ms	8 ms
Color Gamut	85% NTSC	85% NTSC	85% NTSC
Reliability	7 × 24 h	7 × 24 h	7 × 24h
Refresh Rate	60 Hz	60 Hz	60 Hz
Haze	25%	25%	25%

Built-in System

Operation System	Android 13.0		
Processor	Cortex-A55, 4-core, main frequency 1.92GHz		
Memory	4 GB		
Built-in Storage	32 GB eMMC		

Interface

Video & Audio Input	HDMI × 3, DP × 1		
Video & Audio Output	LINE OUT × 1, speaker (6Ω 10W) × 2		
Network Interface	RJ45 × 1, Wi-Fi (2.4G/5G, 802.11 a/b/g/n/ac/ax) × 1, RS232 in × 1, RS232 out × 1		
Data Transmission Interface	USB 2.0 × 1, USB 3.0 × 1, BT 5.4 × 1		

Power

Standby Consumption	≤ 0.5 W	≤ 0.5 W	≤ 0.5 W
Input Voltage	100 to 240 VAC, 50/60 Hz	100 to 240 VAC, 50/60 Hz	100 to 240 VAC, 50/60 Hz
Power Consumption (Max.)	Typical 98W, Max 160W	Typical 121W, Max 178W	Typical 134W, Max 195W

Working Environment

Working Temperature	0°C to 40°C (32°F to 104°F)		
Working Humidity	10% to 80% RH (Condensation)		
Storage Temperature	-20°C to 60°C (-4°F to 140°F)		
Storage Humidity	10% to 90% RH (Condensation)		

General

Material Type	Metal and plastic	Metal and plastic	Metal and plastic
Mounting Type	Wall mounting (horizontally or vertically)	Wall mounting (horizontally or vertically)	Wall mounting (horizontally or vertically)
Product Dimensions (mm)	967.4 (W) × 555.9 (H) × 70 (D) (without wall-mounted backboard)	1124.6 (W) × 644.8 (H) × 68.5 (D) (without wall-mounted backboard)	1238.4 (W) × 70.92 (H) × 70 (D) (without wall-mounted backboard)
	967.4 (W) × 555.9 (H) × 100 (D) (with wall-mounted backboard)	1124.6 (W) × 644.8 (H) × 98.5 (D) (with wall-mounted backboard)	1238.4 (W) × 70.92 (H) × 99.8 (D) (with wall-mounted backboard)
Package Dimensions (mm)	1075 (W) × 652 (H) × 144 (D)	1250 (W) × 760 (H) × 144 (D)	1390 (W) × 830 (H) × 144 (D)
Gross Weight	8.0 kg	10.4 kg	13 kg
	11.5 kg	14.8 kg	19.5 kg

Model	DS-D6065UN-DL	DS-D6075UN-DL
-------	---------------	---------------

Display Panel

Screen Size	65 inch	75 inch
Resolution	3840 × 2160	3840 × 2160
Active Display Area (mm)	1428.48 (H) × 803.52 (V)	1650.24 (H) × 928.26 (V)
Pixel Pitch (mm)	0.124 (H) × 0.372 (V)	0.14325 (H) × 0.42975 (V)
Backlight	D-LED	D-LED
Viewing Angle	178°(H)/178°(V)	178°(H)/178°(V)
Contrast Ratio	4000:1	4000:1
Brightness	500 cd/m²	500 cd/m²
Color Depth	10 bit (8 bit + FRC)	10 bit (8 bit + FRC)
Response Time	8 ms	6.5 ms
Color Gamut	85% NTSC	85% NTSC
Reliability	7 × 24 h	7 × 24 h
Refresh Rate	60 Hz	60 Hz
Haze	25%	25%

Built-in System

Operation System	Android 13.0
Processor	Cortex-A55, 4-core, main frequency 1.92GHz
Memory	4 GB
Built-in Storage	32 GB eMMC

Interface

Video & Audio Input	HDMI × 3, DP × 1	HDMI × 3, DP × 1
Video & Audio Output	LINE OUT × 1, speaker (6Ω 10W) × 2	LINE OUT × 1, speaker (6Ω 10W) × 2
Network Interface	RJ45 × 1, Wi-Fi (2.4G/5G, 802.11 a/b/g/n/ac/ax) × 1, RS232 in × 1, RS232 out × 1	RJ45 × 1, Wi-Fi (2.4G/5G, 802.11 a/b/g/n/ac/ax) × 1, RS232 IN × 1, RS232 OUT × 1
Data Transmission Interface	USB 2.0 × 1, USB 3.0 × 1, BT 5.4 × 1	USB 2.0 × 1, USB 3.0 × 1, BT 5.4 × 1

Power

Standby Consumption	≤ 0.5 W	≤ 0.5 W
Input Voltage	100 to 240 VAC, 50/60 Hz	100 to 240 VAC, 50/60 Hz
Power Consumption (Max.)	Typical 180W, Max 240W	Typical 218W, Max 280W

Working Environment

Working Temperature	0°C to 40°C (32°F to 104°F)
Working Humidity	10% to 80% RH (Condensation)
Storage Temperature	-20°C to 60°C (-4°F to 140°F)
Storage Humidity	10% to 90% RH (Condensation)

General

Material Type	Metal and plastic	Metal and plastic
Mounting Type	Wall mounting (horizontally or vertically)	Wall mounting (horizontally or vertically)
Product Dimensions (mm)	1457.7 (W) × 832.4 (H) × 68.8 (D) (without wall-mounted backboard) 1457.7 (W) × 832.4 (H) × 88.8 (D) (with wall-mounted backboard)	1679 (W) × 957 (H) × 68.8 (D) (without wall-mounted backboard) 1679 (W) × 957 (H) × 88.8 (D) (with wall-mounted backboard)
Package Dimensions (mm)	1640 (W) × 990 (H) × 190 (D)	1840 (W) × 1112 (H) × 177 (D)
Net Weight	17.7 kg	27.7 kg
Gross Weight	28.4 kg	39.1 kg



www.hikvision.com
support@hikvision.com



HIKVISION