Controler decodeur via 1100KI

1.Ajouter le decodeur



2.Entrer dans "Region"

< Switch Mode	Keyb	ooard	⊡ admin		
Device	<u>A</u> User	Channel	Bog Region	Macro	Group

3.Cliquer"+"

	Region Management							
+ 1	7		Thereit is a strength of the					
ID	Video Wall	Start Coordinate	End Coordinate	Edit	Config Delete			
1	1	Row 1, Column 1	Row 2, Column 2	Ľ	63	団		
2	2	Row 1, Column 1	Row 3, Column 3	C	63	団		
3	3	Row 2, Column 2	Row 3, Column 3	Ľ	6 3	Ū		
4	4	Row 1, Column 1	Row 4, Column 4	C	6 3	Ū		
Total 4	Page 1/1		K < > :	> 1	/1	-		

4.Créer le mur d'image



5.Cliquer "Config"

6	Region Management							
+ 🕁								
ID	Video Wall	Start Coordinate	End Coordinate	Edit	Config Delete			
1	1	Row 1, Column 1	Row 2, Column 2	C	(<u>j</u>)	団		
2	2	Row 1, Column 1	Row 3, Column 3	C	63	団		
3	3	Row 2, Column 2	Row 3, Column 3	C	6	뒨		
4	4	Row 1, Column 1	Row 4, Column 4	C	6 3	쿱		
Total 4 Pag	e 1/1		1< < >	>1 1	. /1			

6.Choisir l'écran



7.Cliquer "Edit"



8.Choisir Output

