

**DS-VBD1HH-UF/H/D631**

- Supports fuzzy search via setting searching conditions for example time range, camera, and human face/vehicle/vehicle attribute.
- Supports data area comparison to find data that meet searching conditions.
- Adopts cluster linear expansion to realize the flexible expansion of storage and performance.
- Support single deployment or cluster deployment within 5 machines.
- Supports system disaster tolerance to keep the server running when any node in cluster has fault.
- Supports trace information statistics via model comparison.
- Supports similarity matched searching for single model or multiple models.
- Single server supports storing 1.8 billion facial/human/vehicle data, with daily increase of 10 million data accesses.
- Supports multi-dimensional data integration and storage, and data association.
- Adopts multi-duplicate data saving and fault tolerance mechanism to realize automatic recovery.

## ▪ Specification

Product Performance	
Data Type	Human face data, Human body data, Vehicle data
Hardware Specifications	
CPU	Intel® Xeon® 5418Y x 2
Memory	512GB DDR4
Network Interfaces	10 Gigabit Ethernet interface × 2+1 Gigabit Ethernet interface × 2
Max. Power Consumption	1400W
Device Dimensions	772.13 mm × 482 mm × 86.8 mm (30.39" × 19.0" × 3.41") With package: 1010 mm × 667 mm × 327 mm (39.76" × 26.26" × 12.87")
HDD Specifications	960GB SSD × 2(RAID1) 800G SAS Mix SSD(FIPS-140) × 6(JBod) 16T 7.2K SAS HDD(FIPS-140) × 6(JBod)
PSU	Hot-plugged efficient 1+1 redundant power module
External Interfaces	USB 3.0 × 2 + USB 2.0 × 2 + VGA × 1
Physical and Environmental Parameters	
Working Temperature	+5°C to +35°C (41°F to 95 °F)
Working Humidity	8 % to 90 % (without condensation)
Net Weight (Without Package)	36.1 kg (79.58 lb)
Storage and Transportation Temperature	-40°C to +70°C (-40°F to 158 °F)

## ▪ Available Model

DS-VBD1HH-UF/H/D631

# See Far, Go Further



[www.hikvision.com](http://www.hikvision.com)  
[support@hikvision.com](mailto:support@hikvision.com)

