

iDS-2ZMN2312S(B) 8 MP 23 × Network Zoom Camera Module



Hikvision iDS-2ZMN2312S(B) 8 MP 23 × Network Zoom Camera Module adopts 1/1.8" progressive scan CMOS chip. With the 23 × optical zoom lens, the camera module offers more details over expansive areas. This series of camera modules can be used for different types of PTZ cameras and positioning systems.

- 1/1.8" progressive scan CMOS
- Up to 3840 × 2160 resolution
- 23 × optical zoom, focal length 5.9 mm to 135.7 mm
- Min. illumination: Color: 0.005 Lux @ (F1.5, AGC ON)
- IR cut filter with auto switch
- EIS, 120 dB WDR, 3D DNR
- Smart events: intrusion detection, line crossing detection, region entrance detection, region exiting detection, unattended baggage detection, object removal detection
- Face capture
- Quick and accurate focus
- Efficient H.265 compression technology
- Multiple interfaces for extended functionality
- Network output
- Small size and low power consumption
- Easy to connect to PTZ cameras and positioning systems
- Seamless access to mainstream platforms and other network devices



▪ Specification

| Camera Module | |
|---------------------------|---|
| Heartbeat | yes |
| Image Sensor | 1/1.8" progressive scan CMOS |
| Min. Illumination | Color: 0.005 Lux @ (F1.5, AGC ON); B/W: 0.0005 Lux @(F1.5, AGC ON) |
| Resolution and Frame Rate | Main Stream 50 Hz: 25 fps (3840 × 2160, 2560 × 1440, 1920 × 1080, 1280 × 960, 1280 × 720) 60 Hz: 24 fps (3840 × 2160, 2560 × 1440, 1920 × 1080, 1280 × 960, 1280 × 720) Sub-Stream 50 Hz: 25 fps (704 × 576, 640 × 480, 352 × 288) 60 Hz: 24 fps (704 × 480, 640 × 480, 352 × 240) Third Stream 50 Hz: 25 fps (3840 × 2160, 2560 × 1440, 1920 × 1080, 1280 × 960, 1280 × 720, 704 × 576, 640 × 480, 352 × 288) 60 Hz: 24 fps (3840 × 2160, 2560 × 1440, 1920 × 1080, 1280 × 960, 1280 × 720, 704 × 480, 640 × 480, 352 × 240) |
| Video Compression | H.264/H.265 |
| Audio Compression | G.722.1, G.711alaw, G.711ulaw, MP2L2, G.726, PCM |
| White Balance | auto, ATW, sodium lamp, fluorescent lamp, indoor, outdoor, MWB, Locked WB |
| Gain Control | Auto/Manual |
| SNR | >52 dB |
| 3D DNR | yes |
| BLC | yes |
| Regional Focus | yes |
| Shutter | 1/1 s to 1/30,000 s |
| Day & Night | Auto/Color/BW/Triggered by Alarm Input/Scheduled-Switch |
| Digital Zoom | 12 × |
| Focus | auto, semi-auto, manual |
| Privacy Mask | up to 8 masks |
| Regional Exposure | yes |
| Video Bit Rate | 32 kbps to 16384 kbps |
| Exposure Mode | auto, iris priority, shutter priority, manual |
| Day/Night Switch | ICR |
| Lens | |
| Focal Length | 5.9 mm to 135.7 mm, 23 × optical |
| Zoom Speed | Approx. 4.8 s (Optical, Wide-Tele) |
| Horizontal FOV | 60.2° to 3.4° (Wide-Tele) |
| Aperture | F1.5 to F3.4 |
| Function | |
| Image Enhancement | 120 dB WDR, HLC, BLC, electronic defog, EIS with built-in gyroscope |
| Smart Encoding | low bit rate, ROI |
| Exception Detection | illegal login |
| Power-off Memory | yes |
| Smart Detection | intrusion detection, line crossing detection, region entrance detection, region exiting detection, unattended baggage detection, object removal detection |

| | |
|-------------------------|--|
| Face Capture | yes |
| Network | |
| Protocols | IPv4/IPv6, HTTP, HTTPS, 802.1x, Qos, FTP, SMTP, UPnP, DNS, DDNS, NTP, RTSP, RTCP, RTP, TCP/IP, DHCP, Bonjour |
| API | Open-ended API, ONVIF, PSIA, CGI, Hikvision SDK, Third-party management platform, ISUP, Hik-Connect |
| Web Browser | IE 10-11, Chrome 57+, Firefox 52+, Safari 12+ |
| Simultaneous Live View | Up to 20 channels |
| User | Up to 32 users. 3 levels: Administrator, Operator and User |
| Security Measures | Authenticated username and password, MAC address binding, HTTPS encryption, 802.1X authenticated access |
| Interface | |
| Power Interface | 12 VDC \pm 10% |
| Communication Interface | 10 M/100 M Ethernet interface |
| Communication | RS232 interface, HIKVISION protocol, RS485 interface, Pelco protocol |
| Audio I/O | 1 audio input, 1 audio output |
| Alarm I/O | 1 alarm input, 1 alarm output |
| RS-485 | yes |
| On-board Storage | Micro SD/Micro SDHC/Micro SDXC card, up to 256 GB |
| Interface | 36pin FFC (including network interface, RS485, RS232, alarm in/out, line in/out, power supply) |
| General | |
| Power Consumption | Static: 5 W, Dynamic: 7 W |
| Operating Conditions | Temperature: -10 °C to 60 °C (14°F to 140°F) Humidity: \leq 90% |
| Dimensions | 57 mm \times 67 mm \times 119 mm (2.24" \times 2.64" \times 4.69") |
| Weight | Approx. 420 g (0.93 lb.) |

▪ Available Model

iDS-2ZMN2312S(B)

Typical Application

Hikvision products are classified into three levels according to their anti-corrosion performance. Refer to the following description to choose for your using environment.





This model has NO SPECIFIC PROTECTION.

| Level | Description |
|----------------------|--|
| Top-level protection | Hikvision products at this level are equipped for use in areas where professional anti-corrosion protection is a must. Typical application scenarios include coastlines, docks, chemical plants, and more. |
| Moderate protection | Hikvision products at this level are equipped for use in areas with moderate anti-corrosion demands. Typical application scenarios include coastal areas about 2 kilometers (1.24 miles) away from coastlines, as well as areas affected by acid rain. |

No specific protection

Hikvision products at this level are equipped for use in areas where no specific anti-corrosion protection is needed.

▪ **Dimension**



Unit:mm

Distributed by

**HIKVISION®****Headquarters**

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
overseasbusiness@hikvision.com

Hikvision USA
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Australia
T +61-2-8599-4233
salesau@hikvision.com

Hikvision India
T +91-22-28469900
sales@pramahikvision.com

Hikvision Canada
T +1-866-200-6690
sales.canada@hikvision.com

Hikvision Thailand
T +662-275-9949
sales.thailand@hikvision.com

Hikvision Europe
T +31-23-5542770
sales.eu@hikvision.com

Hikvision Italy
T +39-0438-6902
info.it@hikvision.com

Hikvision Brazil
T +55 11 3318-0050
Latam.support@hikvision.com

Hikvision Turkey
T +90 (216)521 7070- 7074
sales.tr@hikvision.com

Hikvision Malaysia
T +601-7652-2413
sales.my@hikvision.com

Hikvision UK & Ireland
T +01628-902140
sales.uk@hikvision.com

Hikvision South Africa
Tel: +27 (10) 0351172
sale.africa@hikvision.com

Hikvision France
T +33(0)1-85-330-450
info.fr@hikvision.com

Hikvision Kazakhstan
T +7-727-9730667
nikia.panfilov@hikvision.ru

Hikvision Vietnam
T +84-974270888
sales.vt@hikvision.com

Hikvision UAE
T +971-4-4432090
salesme@hikvision.com

Hikvision Singapore
T +65-6684-4718
sg@hikvision.com

Hikvision Spain
T +34-91-737-16-55
info.es@hikvision.com

Hikvision Tashkent
T +99-87-1238-9438
uzb@hikvision.ru

Hikvision Hong Kong
T +852-2151-1761
info.hk@hikvision.com

Hikvision Russia
T +7-495-669-67-99
saleru@hikvision.com

Hikvision Korea
T +82-(0)31-731-8817
sales.korea@hikvision.com

Hikvision Poland
T +48-22-460-01-50
info.pl@hikvision.com

Hikvision Indonesia
T +62-21-2933759
Sales.Indonesia@hikvision.com

Hikvision Colombia
sales.colombia@hikvision.com