

DS-A72XX-CVS Storage System



Features and Functions

High Reliability Design

- Redundancy design for key parts; modular drawer design.
- Cluster-based technology to implement load balance and backup among storage nodes.
- Supports automatic network replenishment (ANR) to restore videos during network disconnection.
- The cloud backup function stores multiple copies of a single video within the cloud storage system; supports internal cloud backup and multiple-cloud backup.

High Performance Application

- Based on discrete storage technology, multiple devices are able to respond simultaneously to data read/write services, finish massive data search at second level, and download data at high speed.
- Based on virtualization technology, all storage nodes are virtualized as a unified resource which is accessible through specified port; storage space can be flexibility divided and can be adjust dynamically without data loss.
- A single device can respond to the concurrent writing requests of several hundred video channels.
- Supports frame analysis and offers key frame search and playback.
- Supports video stream frame extraction storage.

Cost-efficient System

- Supports direct video storage. No stream media server is required.
- Supports stream forwarding. No media switch server is required.

Efficient Maintenance Service

- Complete maintenance system, with provided maintenance tools.
- Operating status monitoring for CPU, memory, NIC and HDD.
- Active alarm for software and hardware failures.
- Active alarm for device failure and disconnection.

High Scalability

- Increase storage space and performance by stacking and cascading without interrupting services. Easily and quickly expand your storage capacity at TB or even PB level.

HDD Detection

- Pre-detection before using HDD.
- In-process detection when using HDD.
- Restoration and recovery technology after HDD failure.



RAID Optimization

- Supports RAID 0, 1, 3, 5, 6, 10, 50.
- Instant application of RAID mode; supports dynamic online expansion of logical volume.

Green & Energy-efficient

- CPU dynamically adjusts operating frequency according to workload.
- Intelligent fan speed adjustment; higher heat dissipation efficiency and lower noise.
- High quality power supply to increase power conversion efficiency and reduce power loss.

Compatible & Open

- Provides complete API interfaces for third-party cloud storage system connection.
- Supports standard ONVIF access.
- Supports Smart IPC access.

Software Module

- Cloud Video Access (CVA): Recording task management, recording service and device status management, etc.
- Cloud Video Storage (CVS): Video data read/write operation.

Specifications

Model		DS-A72024R-CVS	DS-A72048R-CVS
Performance	Video: recording + playback (2 Mbps)	300-ch + 64-ch	360-ch + 32-ch
	Controller	Processor 2 × Xeon hexa-core processor Cache 16 GB (extendable to 64 GB) SSD 64 GB	
Storage	HDD slot	24	48
	Interface	SATA (SSD optional)	
	Capacity	1 TB, 2 TB, 3 TB, 4 TB, 6 TB, 8 TB	
	Hot-plugging	Supported	
	RAID	RAID 0, 1, 3, 5, 6, 10, 50, JBOD, hot spare	
Software module	CVA	Device access management, recording schedule, stream forwarding, VCA	
	CVS	Video access service, storage space management, data read/write	
	Storage management	StorOS storage system, RAID management, HDD detection and restoration, alarm	
External interface	Data	4, 1000M Ethernet interface, extendable to 4 × GE or 2 × 10GE	
	Management	1, 100M Ethernet interface	
	COM	1	
	USB	4	
	VGA	1	
General	Power supply	Redundant power supply	
	Power Consumption (with HDD)	Operating: ≤ 410 W Rated: ≤ 875 W	Operating: ≤ 620 W Rated: ≤ 1360 W
	Temperature	Operating: 5 °C to 35 °C (41 °F to 95 °F) Storing: -20 °C to +70 °C (-4 °F to +158 °F)	
	Humidity	Operating: 20% to 80% RH (non-condensing/frozen) Storing: 5% to 90% RH (non-condensing/frozen)	
	Chassis	19-inch 4U standard chassis	19-inch 8U standard chassis
	Dimensions (W × D × H)	430 × 730 × 180 mm (16.9 × 28.7 × 7.1 inch)	447 × 843 × 344 mm (17.6 × 33.2 × 13.5 inch)
	Weight (without HDD)	≤ 40 kg (88.2 lb)	≤ 50 kg (110.2 lb)

Available Models

DS-A72024R-CVS, DS-A72048R-CVS

Distributed by



HIKVISION®

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
overseasbusiness@hikvision.com

Hikvision USA
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Italy
T +39-0438-6902
info.it@hikvision.com

Hikvision Singapore
T +65-6684-4718
sg@hikvision.com

Hikvision Africa
T +27 (10) 0351172
sale.africa@hikvision.com

Hikvision Europe
T +31-23-55-42-770
info.eu@hikvision.com

Hikvision France
T +33(0)1-85-330-450
info.fr@hikvision.com

Hikvision Oceania
T +61-2-8599-4233
salesau@hikvision.com

Hikvision Hong Kong
T +852-2151-1761

Hikvision Middle East
T +971-4-8816086
salesme@hikvision.com

Hikvision Spain
T +34-91-737-16-55
info.es@hikvision.com

Hikvision Canada
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Russia
T +7-495-669-67-99
saleru@hikvision.com

Hikvision Poland
T +48-22-460-01-50
poland@hikvision.com

Hikvision Korea
T +82-31-731-8841
sales.korea@hikvision.com

Hikvision India
T +91-22-28469900
sales@pramahikvision.com

Hikvision UK
T +01628-902140
support.uk@hikvision.com

Hikvision Brazil
T +55 11 3318-0050
Latam.support@hikvision.com