

DS-2CE56D0T-VPIR3E 2 MP Vandal PoC Manual Varifocal Dome Camera



- 2 MP vari-focal PoC dome camera
- 2.8 mm to 12 mm varifocal lens
- Up to 40 m IR distance for bright night imaging
- Water and dust resistant (IP67) and vandal proof (IK10)
- Transmits both HD video and power over the same coaxial cable

▪ Specification


Camera	
Image Sensor	2 MP CMOS
Max. Resolution	1920 (H) × 1080 (V)
Min. Illumination	0.01 Lux @ (F1.4, AGC ON), 0 Lux with IR
Shutter Time	PAL: 1/25 s to 1/50,000 s; NTSC: 1/30 s to 1/50,000 s
Day & Night	IR Cut Filter
Angle Adjustment	Pan: 0° to 355°, Tilt: 0° to 75°, Rotation: 0° to 355°
Signal System	PAL/NTSC
Lens	
Lens Type	Varifocal lens, 2.8 mm to 12 mm
Focal Length & FOV	Horizontal FOV: 105.2° to 32.8°
Lens Mount	Φ14
Illuminator	
Supplement Light Range	Up to 40 m
Smart Supplement Light	Yes
Image	
Image Settings	Brightness, Mirror, Sharpness, AGC
Frame Rate	PAL: 1080p @ 25 fps NTSC: 1080p @ 30 fps
Day/Night Mode	Auto/Color/BW (Black and White)
Wide Dynamic Range (WDR)	Digital WDR
Image Enhancement	BLC
Noise Reduction	2D DNR
Interface	
Video Output	1 HD analog output
General	
Power	12 VDC ±15%/PoC.af, max. 4.1 W
Material	Metal
Dimension	Ø 145.3 × 124.2 mm (Ø 5.72" × 4.89")
Weight	Approx. 1300 g (2.87 lb.)
Operating Condition	-40 °C to 60 °C (-40 °F to 140 °F), humidity 90% or less (non-condensing)
Language	English
Approval	
Protection	IP67, IK10

▪ Available Model

DS-2CE56D0T-VPIR3E(2.8-12mm)

▪ **Accessory**

▪ **Optional**

DS-1273ZJ-140 Wall mount	DS-1273ZJ-140B Wall mount	DS-1271ZJ-140 Pendant Mount	DS-1275ZJ-SUS Vertical pole mount	DS-1241ZJ In-ceiling mount
				
DS-1276ZJ-SUS Corner mount	DS-1240ZJ Inclined ceiling mount	DS-1253ZJ-L Water-proof	DS-1250ZJ Water-proof	DS-1273ZJ-140(BLA CK) Wall mount
				

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
www.hikvision.com



Follow us on social media to get the latest product and solution information.

