

DS-UC8 4K Web Camera





- High quality imaging with 3840 × 2160 resolution
- Low distortion lens for reducing image distortion
- Built-in dual-microphone with clear sound
- USB Type-C interface, supporting USB 3.0 protocols
- Plug-and-play, no need to install driver software
- Support auto focus



Specification

Camera	
Image Sensor	8 MP CMOS
Signal System	PAL/NTSC
	MJPG:
	3840 × 2160 @ 30 fps/25 fps
	2560 × 1440 @ 30 fps/25 fps
	1920 × 1080 @ 30 fps/25 fps
	1280 × 960 @ 30 fps/25 fps
	1280 × 720 @ 30 fps/25 fps
	640 × 480 @ 30 fps/25 fps
	640 × 360 @ 30 fps/25 fps
	YUV:
Frame Rate	1920 × 1080 @ 30 fps/25 fps
	1280 × 960 @ 30 fps/25 fps
	1280 × 720 @ 30 fps/25 fps
	640 × 480 @ 30 fps/25 fps
	640 × 360 @ 30 fps/25 fps
	NV12:
	1920 × 1080 @ 5 fps
	1280 × 960 @ 10 fps
	1280 × 720 @ 15 fps
	640 × 480 @ 30 fps
Resolution	3840 (H) × 2160 (V)
Min. Illumination	0.1 Lux @ (F1.2, AGC ON)
Shutter Time	PAL: 1/25 s to 1/50,000 s;NTSC: 1/30 s to 1/50,000 s
Lens	3.6 mm fixed focal lens
Field of View	horizontal FOV: 83°, vertical FOV: 53°, diagonal FOV: 91°
Lens Mount	M8
Day & Night	24/7 Color Imaging
Angle Adjustment	pan: 0° to 360°; tilt: 0° to 90°; rotation: 0°
Cable Length	2 m
Lens	
Depth of Field	5 cm to ∞
Image	
Wide Dynamic Range (WDR)	Digital WDR
Image Enhancement	Distortion Correction
White Balance	Auto
Audio	
Audio Sampling Rate	
_	16 kHz
Interface	16 kHz





	Recommended systems
	Windows 7/8/10/11 (resolution higher than 1080P is only available in Windows 8.1
	and above version)
Operating System	Android 8.1 and above version
	Linux 4.14 and above version
	macOS 10.12 and above version
	Chrome OS
Built-in Microphone	2 built-in microphones, picking up sounds in the radius up to 5 meters
Indicator	White: Normally Working
General	
Operating Conditions	-10°C to 45°C (-40°F to 113°F), Humidity: 90% or less (non-condensing)
Power Supply	DC 5V ± 5% (USB)
Consumption	4.5 W MAX
Material	Metal
Dimension	120 mm × 27.9 mm × 25.6 mm (4.72" × 1.10" × 1.01")
Weight	Approx. 150 g (0.33 lb.)
Accessory	
	Camera × 1
Packing List	USB Cable × 1
	Quick Start Guide × 1


Available Model


DS-UC8 DS-UC8(JAPAN)

Dimension













Headquarters No.555 Qianmo Road, Binjiang District, Hangzhou 310051, China T +86-571-8807-5998 www.hikvision.com

Follow us on social media to get the latest product and solution information.





HikvisionHQ



HikvisionHQ







