

## DS-D4250FO

### Outdoor Fixed LED Displays



- Widely applied in outdoor permanent advertising scenes
- Thin and light cabinet with the die-casting aluminum design
- IP 65 rating for both the front and back panels
- Free of air conditioners with multiple ventilation modes working together inside the cabinets
- Rear maintenance available and front maintenance customizable
- Standing, wall mount, and lifting available for installation
- Customizable as stadium LED screens



## ▪ Specification

Model		DS-D4250FO
Cabinet	Pixel Configuration	SMD Triad LED
	Pixel Pitch Category	P5
	Pixel Pitch	5.0 mm
	Lamp Dimensions	1.9 × 2.1 mm
	Modules Component	3 × 6
	Dimensions (W × H × D)	960 mm × 960 mm × 102.5 mm (37.8" × 37.8" × 4.0")
	Resolution	192 × 192
	Area	0.9216 m <sup>2</sup>
	Weight	29 Kg (63.9 lb)
	Pixel Density	40000 dots/m <sup>2</sup>
	Lamp Board Housing	With housing
	Cabinet Material	Magnalium
	Maintenance Method	Back maintenance
	Cabinet Flatness	0.2 mm
Protection Level	IP65 both front and back	
Key Material	Lamp Encapsulation	Nationstar 1921
	Driver IC	ICN2153
	Control System	DS-D42C04-H、DS-D42C08-H
Display	White Balance Brightness	5500 cd/m <sup>2</sup>
	Color Temperature	2000 K to 9300 K adjustable
	Viewing Angle	Horizontal 140°, vertical 140°
	Contrast Ratio	≥ 5000:1
	Color Uniformity	≤ ± 0.003Cx, Cy
	Brightness Uniformity	≥ 97%
Processing Performance	Driving Method	Constant current driving
	Frame Frequency	60 Hz
	Refresh Rate	Up to 3840 Hz
	Grey Level	Up to 16 bit
	Display Color	281 trillion
Power	Power Supply	110~220 VAC ± 15%
	Max. Consumption	≤ 850 W/m <sup>2</sup>
	Average Consumption	< 280 W/m <sup>2</sup>
Working Environment	Working Temperature	-10-55 °C
	Working Humidity	10%~80%RH
	Storage Humidity	10%~85%RH
	Storage Temperature	-20~60 °C
General	Gross Weight	120 Kg (21.2 lb) /4 in 1
	Package Dimension (W × H × D)	1030 mm × 680 mm × 1150 mm (40.6" × 26.8" × 45.3")
	Lifespan	Lamp 100,000 hours

- Accessory
- Optional

DS-D42C08-H LED Controll Card	DS-D42C04-H LED Controll Card
	

## ▪ Available Model

DS-D4250FO

Distributed by



## HIKVISION®

### Headquarters

No.555 Qianmo Road, Binjiang District,  
Hangzhou 310051, China  
T +86-571-8807-5998  
overseasbusiness@hikvision.com

**Hikvision USA**  
T +1-909-895-0400  
sales.usa@hikvision.com

**Hikvision Australia**  
T +61-2-8599-4233  
salesau@hikvision.com

**Hikvision India**  
T +91-22-28469900  
sales@pramahikvision.com

**Hikvision Canada**  
T +1-866-200-6690  
sales.canada@hikvision.com

**Hikvision Thailand**  
T +662-275-9949  
sales.thailand@hikvision.com

**Hikvision Europe**  
T +31-23-5542770  
sales.eu@hikvision.com

**Hikvision Italy**  
T +39-0438-6902  
info.it@hikvision.com

**Hikvision Brazil**  
T +55 11 3318-0050  
Latam.support@hikvision.com

**Hikvision Turkey**  
T +90 (216)521 7070- 7074  
sales.tr@hikvision.com

**Hikvision Malaysia**  
T +601-7652-2413  
sales.my@hikvision.com

**Hikvision UK & Ireland**  
T +01628-902140  
sales.uk@hikvision.com

**Hikvision South Africa**  
Tel: +27 (10) 0351172  
sale.africa@hikvision.com

**Hikvision France**  
T +33(0)1-85-330-450  
info.fr@hikvision.com

**Hikvision Kazakhstan**  
T +7-727-9730667  
nikia.panfilov@hikvision.ru

**Hikvision Vietnam**  
T +84-974270888  
sales.vt@hikvision.com

**Hikvision UAE**  
T +971-4-4432090  
salesme@hikvision.com

**Hikvision Singapore**  
T +65-6684-4718  
sg@hikvision.com

**Hikvision Spain**  
T +34-91-737-16-55  
info.es@hikvision.com

**Hikvision Tashkent**  
T +99-87-1238-9438  
uzb@hikvision.ru

**Hikvision Hong Kong**  
T +852-2151-1761  
info.hk@hikvision.com

**Hikvision Russia**  
T +7-495-669-67-99  
saleru@hikvision.com

**Hikvision Korea**  
T +82-(0)31-731-8817  
sales.korea@hikvision.com

**Hikvision Poland**  
T +48-22-460-01-50  
info.pl@hikvision.com

**Hikvision Indonesia**  
T +62-21-2933759  
Sales.Indonesia@hikvision.com

**Hikvision Colombia**  
sales.colombia@hikvision.com