

DS-D44A0FO-BKI Outdoor Fixed LED Displays



- Widely applied in outdoor permanent advertising scenes
- Thin and light cabinet with the die-casting aluminum design
- Front IP65, Back IP54
- Free of air conditioners with multiple ventilation modes working together inside the cabinets
- Standing, wall mount, and lifting available for installation
- Customizable as stadium LED screens



Specification

	Model	DS-D44A0FO-BKI
Cabinet	Pixel Configuration	1R1G1B
	Pixel Pitch Category	P10.0
	Pixel Pitch	10.0 mm
	Modules Component	3 × 6
	Dimensions (W × H × D)	960 mm × 960 mm × 138 mm (37.80'' × 37.80'' × 5.43'')
	Resolution	96 × 96
	Area	0.9216 m ²
	Weight	50 kg (110.23 lb.)
	Pixel Density	10000 dots/m ²
	Lamp Board Housing	With housing
	Cabinet Material	Waterproof sheet metal box
	Maintenance Method	Back maintenance
	Cabinet Flatness	0.2 mm
	Protection Level	Front IP65/Back IP54
Key Material	Lamp Encapsulation	Nationstar 3535
	Control System	DS-D42C04-N, DS-D42C06-N
Display	White Balance Brightness	6000 nits
	Color Temperature	3500K to 9300K adjustable
	Viewing Angle	Horizontal 140°, vertical 120°
	Contrast Ratio	≥ 5000:1
	Color Uniformity	≤±0.003Cx, Cy
	Brightness Uniformity	≥ 97%
Processing Performance	Driving Method	Constant current driving
	Frame Frequency	60 Hz
	Refresh Rate	Up to 3840 Hz
	Grey Level	Up to 14 bit
	Display Color	16777216
Power	Power Supply	110 to 220 VAC ± 15%
	Max. Consumption	≤ 1000 W/m²
	Average Consumption	< 300 W/m ²
Working Environment	Working Temperature	-20 °C to 50 °C (-4 °F to 120 °F)
	Working Humidity	10% to 80% RH
	Storage Humidity	10% to 85% RH
	Storage Temperature	-20 °C to 60 °C (-4 °F to 140 °F)
General	Gross Weight	270 kg/5 in 1 (595.25 lb.)
	Package Dimension (W × H × D)	1370 mm × 1090 mm × 1180 mm (53.93'' × 43.91'' × 46.46'')
	Lifespan	Lamp 100,000 hours




Available Model


DS-D44A0FO-BKI

Dimension









Unit: mm



Follow us on social media to get the latest product and solution information.



A HikvisionHQ



192





Hikvision Corporate Channel

O hikvisionhq

©Hikvision Digital Technology Co., Ltd. 2023 | Data subject to change without notice |