

DS-D2046NH-C LCD Display



The DS-D2046NH-C LCD display uses an industry-level ultra-narrow bezel design, which enables a bezel width of 3.5 mm between neighboring displays. The adopted direct-lit LED backlighting technology helps achieve ultra-high and uniform brightness of 700 cd/m² without boundary shadows. The display has abundant interfaces for video inputs, such as DVI, VGA, and HDMI.


- Direct-lit LED backlight with uniform brightness and no boundary shadows
- 1920 × 1080 resolution, 178° viewing angle
- Ultra-narrow 3.5 mm bezel design
- Factory calibration for color uniformity
- Anti-glare, high definition, high brightness, high color gamut, and vivid images with rich colors
- Stable and 24-hour continuous working
- Metal casing for preventing from radiation and magnetic & electric field interference
- Wall-mount and modular brackets available to meet various installation requirements



▪ Specification

| Model | | DS-D2046NH-C |
|----------------------------|-------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product Model | Product Model | DS-D2046NH-C |
| Display | Screen Size | 46 inch |
| | Active Display Area | 1018.08 (H) mm × 572.67 (V) mm |
| | Backlight | Direct-lit LED backlight |
| | Pixel Pitch | 0.53 mm |
| | Physical Seam | 3.5 mm |
| | Bezel Width | 2.3 mm (top/left), 1.2 mm (bottom/right) |
| | Resolution | 1920 × 1080@60 Hz (downward compatible) |
| | Brightness | 700 cd/m ² |
| | Viewing Angle | Horizontal 178°, vertical 178° |
| | Color Depth | 8 bit, 16.7 M |
| | Contrast Ratio | 3500:1 |
| | Response Time | 8 ms (G to G) |
| | Color Gamut | 72% NTSC |
| Surface Treatment | Haze 25%, 2H | |
| Interface | Video & Audio Input | HDMI × 1, DVI × 1, VGA × 1, CVBS × 1, USB × 1 |
| | Video & Audio Output | DVI × 1, VGA × 1, CVBS × 1 |
| | Control Interface | RS232 IN × 1, RS232 OUT × 1 |
| Power | Power Supply | 100-240 VAC, 50/60 Hz |
| | Power Consumption | ≤ 139 W |
| | Standby Consumption | ≤ 0.5 W |
| Working Environment | Working Temperature | 0°C to 40°C (32°F to 104°F) |
| | Working Humidity | 20% to 90% RH (non-condensing) |
| | Storage Temperature | -20°C to 65°C (-4°F to 149°F) |
| | Storage Humidity | 5% to 90% RH (non-condensing) |
| General | Casing Material | SECC |
| | VESA | 600 (H) mm × 400 (V) mm |
| | Product Dimension (W × H × D) | 1021.98 mm × 576.57 mm × 72.2 mm (40.24" × 22.7" × 2.84") |
| | Package Dimension (W × H × D) | Carton with two displays: 1214 mm × 783 mm × 414 mm (47.8" × 30.83" × 16.3") Carton with a single display: 1214 mm × 783 mm × 414 mm (47.8" × 30.83" × 16.3") |
| | Net Weight | 18.91 ± 0.5 Kg (41.69 ± 1.1 lb) for single display |
| | Gross Weight | Carton with two displays: 47.02 ± 0.5 Kg (103.66 ± 1.1 lb) Carton with a single display: 25.75 ± 0.5 Kg (56.77 ± 1.1 lb) |
| | Packing List | LCD display × 1, power cable × 1, network cable × 1, screw × 4, installation instruction × 1, remote control × 1, IR receiver × 1, CD-ROM × 1, RS-232 converter × 1 |


▪ Physical Interface



| Interface | Description | Interface | Description |
|-----------|--------------------------------------------|-----------|-------------------------------------------|
| POWER | Power indicator | HDMI IN | HDMI input interface |
| DVI OUT | DVI-I output interface for digital signals | DVI IN | DVI-I input interface for digital signals |
| VGA OUT | VGA output interface for analog signals | VGA IN | VGA input interface for analog signals |
| CVBS OUT | CVBS output interface for signals | CVBS IN | CVBS input interface for signals |

| | | | |
|-----------|----------------------------------|----------|---------------------------------|
| USB | USB interface | RS232 IN | Serial loopback input interface |
| RS232 OUT | Serial loopback output interface | IR IN | IR input interface |

Dimension



Available Model

DS-D2046NH-C

Distributed by



HIKVISION®

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
overseasbusiness@hikvision.com

Hikvision USA
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Australia
T +61-2-8599-4233
salesau@hikvision.com

Hikvision India
T +91-22-28469900
sales@pramahikvision.com

Hikvision Canada
T +1-866-200-6690
sales.canada@hikvision.com

Hikvision Thailand
T +662-275-9949
sales.thailand@hikvision.com

Hikvision Europe
T +31-23-5542770
sales.eu@hikvision.com

Hikvision Italy
T +39-0438-6902
info.it@hikvision.com

Hikvision Brazil
T +55 11 3318-0050
Latam.support@hikvision.com

Hikvision Turkey
T +90 (216)521 7070- 7074
sales.tr@hikvision.com

Hikvision Malaysia
T +601-7652-2413
sales.my@hikvision.com

Hikvision UK & Ireland
T +01628-902140
sales.uk@hikvision.com

Hikvision South Africa
Tel: +27 (10) 0351172
sale.africa@hikvision.com

Hikvision France
T +33(0)1-85-330-450
info.fr@hikvision.com

Hikvision Kazakhstan
T +7-727-9730667
nikia.panfilov@hikvision.ru

Hikvision Vietnam
T +84-974270888
sales.vt@hikvision.com

Hikvision UAE
T +971-4-4432090
salesme@hikvision.com

Hikvision Singapore
T +65-6684-4718
sg@hikvision.com

Hikvision Spain
T +34-91-737-16-55
info.es@hikvision.com

Hikvision Tashkent
T +99-87-1238-9438
uzb@hikvision.ru

Hikvision Hong Kong
T +852-2151-1761
info.hk@hikvision.com

Hikvision Russia
T +7-495-669-67-99
saleru@hikvision.com

Hikvision Korea
T +82-(0)31-731-8817
sales.korea@hikvision.com

Hikvision Poland
T +48-22-460-01-50
info.pl@hikvision.com

Hikvision Indonesia
T +62-21-2933759
Sales.Indonesia@hikvision.com

Hikvision Colombia
sales.colombia@hikvision.com