

## DS-K1T671M-L Face Recognition Terminal



- Forced mask wearing alert: If the recognizing face does not wear a mask, the device will prompt a voice reminder. At the same time, the authentication or attendance will be failed
- Face mask wearing alert: If the recognizing face does not wear a mask, the device will prompt a voice reminder. At the same time, the authentication or attendance is valid
- 7-inch LCD touch screen, 2 Mega pixel wide-angle lens, built-in Mifare card reading module
- Face recognition distance (without face mask): 0.3 m to 3 m, Duration < 0.2 s/User, Accuracy rate ≥ 99%
- Max.6000 faces, Max.6000 cards
- Two-way audio with client software, indoor station, and mainstation
- Supports TCP/IP
- Configuration via the web client
- Supports ISAPI and ISUP5.0 protocol
- IP65



## ▪ Specification

System	
CPU	800MHz
Memory	1GB
Flash	4G
Operation system	Linux
Display	
Dimensions	7-inch
Resolution	1024 × 600
Type	LCD
Operation method	Capacitive touch screen
Lumens	≥350cd
Video	
Pixel	2 MP
Lens	2
Focal length	4 mm
WDR	≥ 120DB
Aperture	F 1.6
HOV	HFOV=46; VFOV= 87
Video standard	PAL (Default) and NTSC
Audio	
Audio input	Built-in omnidirectional microphone
Audio output	Built-in loudspeaker
Volume adjustment	Adjust via device or client
Power output	2 W
Audio compression standard	G.711U
Audio compression bitrate	64Kbps
Tone quality	Noise suppression and echo cancellation
Network	
Wired network	10 M/100 M/1000 M self-adaptive
Wi-Fi	Not support
3G/4G	Not support
Bluetooth	Not support
Communication protocol	SDK; ISUP5.0; ISAPI; HikCentral Pro OpenAPI; Hik-ProConnect OpenAPI
Interface	
Network interface	1
RS-485	1
Wiegand	1
Lock output	1
Exit button	1
Door contact input	1
IO input	2
IO output	1

Power interface	2-pin
TAMPER	1
USB	2
TF card	-
SIM card	-
PSAM card	Reserved
<b>Capacity</b>	
Card capacity	6000
Face capacity	6000
Fingerprint capacity	Not support
Event capacity	50,000
Schedule template	255
Weekly plan	128
Holiday schedule	1024
Holiday group	64
<b>Authentication</b>	
Card type	Mifare 1 card
Card reading frequency	13.56MHz
Card reading distance	0 to 5 cm
Card reading duration	< 1 s
Face recognition duration	< 0.2 s per person
Face recognition accuracy rate	≥ 99%
Face recognition distance	0.3 to 3 m (Without face mask)
Fingerprint recognition duration	Not support
Fingerprint False Acceptance Rate (FAR)	Not support
Fingerprint False Rejection Rate (FRR)	Not support
<b>Function</b>	
QR code recognition	Support
Multiple faces detection	Not support
Face anti-spoofing	Support
Live view	Support
Two-way audio	Support
Advertisement	Support
Doorbell	Not support
Audio prompt	Support
M1 card encryption	Support
CPU card encryption	Support
Anti-passback	Support
First person in	Support
Multi-factor authentication	Support
Time synchronization	Support


## General

Supplement light	White light and IR light
Power supply method	2-pin connector
Power supply	12 VDC/2 A
Working temperature	-30 °C to 60 °C (-22 °F to 140 °F)
Working humidity	10 to 90% (No condensing)
Dimensions	239 mm × 116.5 mm × 33 mm (9.4" × 4.6" × 1.3")
Application environment	Indoor
Protective level	IP65
Installation	Surface
Language	English, Spanish (South America), Arabic, Thai, Indonesian, Russian, Vietnamese, Portuguese (Brazil)
Platform	Hik-ProConnect and HikCentral Professional

## ▪ Available Model















DS-K1T671M(海外标配)/HIK BR/DS-K1T671M-L,DS-K1T671MF(海外标配)/HIK BR/DS-K1T671MF-L,

## ▪ Dimension



▪ **Accessory**

▪ **Optional**

DS-KAB671-P1	DS-KAB671F Fingerprint Module	DS-KAB671-S Protective Shield	DS-K3H4411-120	DS-K3H4420-120
				
				
DS-K3H4410-120		DS-KAB671-B Stand Stick		
				
				



Distributed by

**HIKVISION®****Headquarters**

No.555 Qianmo Road, Binjiang District,  
Hangzhou 310051, China  
T +86-571-8807-5998  
overseasbusiness@hikvision.com

**Hikvision USA**  
T +1-909-895-0400  
sales.usa@hikvision.com

**Hikvision Australia**  
T +61-2-8599-4233  
salesau@hikvision.com

**Hikvision India**  
T +91-22-28469900  
sales@pramahikvision.com

**Hikvision Canada**  
T +1-866-200-6690  
sales.canada@hikvision.com

**Hikvision Thailand**  
T +662-275-9949  
sales.thailand@hikvision.com

**Hikvision Europe**  
T +31-23-5542770  
sales.eu@hikvision.com

**Hikvision Italy**  
T +39-0438-6902  
info.it@hikvision.com

**Hikvision Brazil**  
T +55 11 3318-0050  
Latam.support@hikvision.com

**Hikvision Turkey**  
T +90 (216)521 7070- 7074  
sales.tr@hikvision.com

**Hikvision Malaysia**  
T +601-7652-2413  
sales.my@hikvision.com

**Hikvision UK & Ireland**  
T +01628-902140  
sales.uk@hikvision.com

**Hikvision South Africa**  
Tel: +27 (10) 0351172  
sale.africa@hikvision.com

**Hikvision France**  
T +33(0)1-85-330-450  
info.fr@hikvision.com

**Hikvision Kazakhstan**  
T +7-727-9730667  
nikia.panfilov@hikvision.ru

**Hikvision Vietnam**  
T +84-974270888  
sales.vt@hikvision.com

**Hikvision UAE**  
T +971-4-4432090  
salesme@hikvision.com

**Hikvision Singapore**  
T +65-6684-4718  
sg@hikvision.com

**Hikvision Spain**  
T +34-91-737-16-55  
info.es@hikvision.com

**Hikvision Tashkent**  
T +99-87-1238-9438  
uzb@hikvision.ru

**Hikvision Hong Kong**  
T +852-2151-1761  
info.hk@hikvision.com

**Hikvision Russia**  
T +7-495-669-67-99  
saleru@hikvision.com

**Hikvision Korea**  
T +82-(0)31-731-8817  
sales.korea@hikvision.com

**Hikvision Poland**  
T +48-22-460-01-50  
info.pl@hikvision.com

**Hikvision Indonesia**  
T +62-21-2933759  
Sales.Indonesia@hikvision.com

**Hikvision Colombia**  
sales.colombia@hikvision.com