

## DS-K5604A-3XF/V Face Recognition Terminal

DS-K5604A-3XF/V face recognition terminal is a kind of access control device integrated with temperature screening function, which supports plug & play (rapid deployment, free of wiring, installation, or configuration). It can fast take skin-surface temperature, which can be widely applied in multiple scenarios, such as enterprises, stations, dwellings, factories, schools, campus and so on.



- Plug & play: Supports rapid deployment. Free of wiring, installation, or configuration
- Supports Vanadium Oxide uncooled sensor to measure target's temperature
- Temperature measuring range: 30 °C to 45 °C (86 °F to 113 °F), accuracy: 0.1 ° C, deviation: ± 0.5 ° C (without black body calibration)
- Recognition distance: 0.3 to 2 m
- Fast temperature measurement mode: Detects face and takes temperature without identity authentication
- Multiple authentication modes are available: card and temperature, face and temperature, card and face and temperature, etc
- Face mask wearing alert: If the recognizing face does not wear a mask, the device will prompt a voice reminder. At the same time, the authentication or attendance is valid.
- Displays temperature measurement results on the authentication page
- Forced mask wearing alert: If the recognizing face does not wear a mask, the device will prompt a voice reminder. At the same time, the authentication or attendance will be failed
- Triggers voice prompt when detecting abnormal temperature
- Configurable door status (open/close) when detecting abnormal temperature
- Transmits online and offline temperature information to the client software via TCP/IP communication and saves the data on the client software
- Integrated design with stand bracket
- Communicates with the third-party turnstile via IO output or Wiegand
- Adjustable supplement light brightness
- High performance processor with deep learning algorithm
- 50,000 face capacity and 100,000 event capacity
- Face recognition duration < 0.2 s/User; face recognition accuracy rate ≥ 99%
- Transmits and saves the comparison results and the captured pictures to the client software or others
- NTP, manually time synchronization, and auto synchronization




- Watchdog design for protecting the device and ensuring device running properly
- Audio prompt for authentication result
- \* In order to get an accurate temperature, after the device is powered on, you should wait for 90 min to warm the device up.
- \* Biometric recognition products are not 100% applicable to anti-spoofing environments. If you require a higher security level, use multiple authentication modes.

## ▪ Specification

<b>Temperature measurement</b>	
Temperature range	30 °C to 45 °C (86 °F to 113 °F)
Sensor	Vanadium Oxide uncooled sensor
Resolution	120 × 160
Frame rate	25 fps
Measurement accuracy	0.1 °C
Measurement deviation	± 0.5 °C, without black body calibration
Measuring distance	0.3 to 2 m
<b>Screen</b>	
Size	10.1-inch
Type	Touch screen
<b>Camera</b>	
Pixel	2 MP
Lens	Dual-lens
<b>Network</b>	
Wired network	Support, 10/100/1000 Mbps self-adaptive
<b>Interface</b>	
Network interface	1
RS-485	1
Wiegand	1
Lock output	1
Exit button	1
Door contact input	1
TAMPER	1
<b>Capacity</b>	
Face capacity	50,000
Event capacity	100,000
<b>Authentication</b>	
Face recognition duration	< 0.2 s per person
Face recognition distance	0.3 to 2 m
<b>Function</b>	
Face anti-spoofing	Support
Audio prompt	Support
<b>Others</b>	
Power supply	12 VDC/2 A
Working temperature	0 °C to 50 °C (32 °F to 122 °F) For temperature measurement: 10 °C to 35 °C (50 °F to 95 °F)
Working humidity	10 to 90% (No condensing)
Application environment	Indoor and windless environment use only

## ▪ Dimension



## ▪ Available Model

DS-K5604A-3XF/V

Distributed by



**HIKVISION®**

### Headquarters

No.555 Qianmo Road, Binjiang District,  
Hangzhou 310051, China  
T +86-571-8807-5988  
[overseasbusiness@hikvision.com](mailto:overseasbusiness@hikvision.com)

Hikvision USA  
T +1-909-895-0400  
[sales.usa@hikvision.com](mailto:sales.usa@hikvision.com)

Hikvision Australia  
T +61-2-8599-4233  
[salesau@hikvision.com](mailto:salesau@hikvision.com)

Hikvision India  
T +91-22-28469900  
[sales@pramahikvision.com](mailto:sales@pramahikvision.com)

Hikvision Canada  
T +1-866-200-5690  
[sales.canada@hikvision.com](mailto:sales.canada@hikvision.com)

Hikvision Thailand  
T +662-275-9940  
[sales.thailand@hikvision.com](mailto:sales.thailand@hikvision.com)

Hikvision Europe  
T +31-23-5542770  
[sales.eu@hikvision.com](mailto:sales.eu@hikvision.com)

Hikvision Italy  
T +39-0438-6902  
[info.it@hikvision.com](mailto:info.it@hikvision.com)

Hikvision Brazil  
T +55 11 3318-0050  
[Latam.support@hikvision.com](mailto:Latam.support@hikvision.com)

Hikvision Turkey  
T +90 (216)521 7070- 7074  
[sales.tr@hikvision.com](mailto:sales.tr@hikvision.com)

Hikvision Malaysia  
T +601-7652-2413  
[sales.my@hikvision.com](mailto:sales.my@hikvision.com)

Hikvision UK & Ireland  
T +01628-902140  
[sales.uk@hikvision.com](mailto:sales.uk@hikvision.com)

Hikvision South Africa  
Tel: +27 (10) 0351172  
[sale.sfrica@hikvision.com](mailto:sale.sfrica@hikvision.com)

Hikvision France  
T +33(0)1-85-330-460  
[info.fr@hikvision.com](mailto:info.fr@hikvision.com)

Hikvision Kazakhstan  
T +7-727-9730667  
[nikia.panfilov@hikvision.ru](mailto:nikia.panfilov@hikvision.ru)

Hikvision Vietnam  
T +84-974270888  
[sales.vt@hikvision.com](mailto:sales.vt@hikvision.com)

Hikvision UAE  
T +971-4-4432090  
[salesme@hikvision.com](mailto:salesme@hikvision.com)

Hikvision Singapore  
T +65-6884-4718  
[sg@hikvision.com](mailto:sg@hikvision.com)

Hikvision Spain  
T +34-91-737-16-55  
[info.es@hikvision.com](mailto:info.es@hikvision.com)

Hikvision Tashkent  
T +99-87-1238-9438  
[uzb@hikvision.ru](mailto:uzb@hikvision.ru)

Hikvision Hong Kong  
T +852-2151-1761  
[info.hk@hikvision.com](mailto:info.hk@hikvision.com)

Hikvision Russia  
T +7-495-669-67-99  
[saleru@hikvision.com](mailto:saleru@hikvision.com)

Hikvision Korea  
T +82-(0)31-731-8817  
[sales.korea@hikvision.com](mailto:sales.korea@hikvision.com)

Hikvision Poland  
T +48-22-460-01-50  
[info.pl@hikvision.com](mailto:info.pl@hikvision.com)

Hikvision Indonesia  
T +62-21-2933759  
[Sales.Indonesia@hikvision.com](mailto:Sales.Indonesia@hikvision.com)

Hikvision Colombia  
[sales.colombia@hikvision.com](mailto:sales.colombia@hikvision.com)