

DS-K5671-ZU Face Recognition Terminal



The face recognition terminal adopts deep learning algorithm, which helps to recognize the face faster and more accurate. It also supports multiple authentication modes: 1:N face match, etc. When installed on the turnstile, it can be applied in multiple scenarios, such as buildings, businesses, financial industries, and other important areas.

- Forced mask wearing alert: If the recognizing face does not wear a mask, the device will prompt a voice reminder. At the same time, the authentication or attendance will be failed
- Face mask wearing alert: If the recognizing face does not wear a mask, the device will prompt a voice reminder. At the same time, the authentication or attendance is valid
- Face recognition terminal for turnstile
- Built-in IO output or Wiegand output to communicate with the third-party turnstile
- 7 inch LCD Touch Screen, 2 M camera
- Max. 50,000 faces, and Max. 100,000 events
- Face recognition distance: 0.3 m to 3 m; Face recognition duration < 0.2 s/User; Accuracy rate ≥ 99%
- TCP/IP, Wi-Fi communication
- Remote live view via RTSP protocol
- IP65



Specification


- Specification						
Display						
Screen size	7 inch					
Operation method	Capacitive touch screen					
Туре	LCD					
Video						
Lens	2					
Resolution	2 MP					
FOV	HFOV = 87°; VFOV = 46°					
Network						
Wired network	Support					
Wi-Fi	Support, 2.4 G, 802.11b/g/n					
Interface						
Network interface	1 RJ-45, 10/100/1000 M self-adaptive					
Lock control	1					
Door contact input	1					
Alarm input	2					
Alarm output	1					
RS-485	1 RS-485 (Half duplex, HIKVISION)					
Wiegand	and 1 Wiegand(Hik 26bit,Hik 34bit)					
USB	1					
General						
Power supply	12 VDC, 2 A					
Working temperature	-30 °C to 60 °C (-22 °F to 140 °F)					
Working humidity	10 to 90% (no condensing)					
Language	English, Spanish (South America), Arabic, Thai, Indonesian, Russian, Vietnamese, Portuguese (Brazil)					
Platform	Hik-ProConnect and HikCentral Professional					
Function						
Support. The dimension of the recognized QR code picture should be larger than 6 × 6 cm.						


Available Model


DS-K5671-ZU



Dimension







Accessory

Optional

Optional				
DS-K3B601A Pro Swing Barrier Plus	DS-K3B601 Pro Swing Barrier	DS-K3B801 Ultra Swing Barriers	DS-K3B801A Ultra Swing Barriers	DS-K3G401 Pro Series Tripod Turnstile
DS-KAB5671-S Protective Shield	DS-K3B801#CD Ultra Swing Barriers			
Trotective Sinelu				



Headquarters No.555 Qianmo Road, Binjiang District, Hangzhou 310051, China T +86-571-8807-5998 www.hikvision.com

Follow us on social media to get the latest product and solution information.





HikvisionHQ



HikvisionHQ







